

RDW Data Model

for use with Invantive SQL

23.0

Auteursrecht

(C) Copyright 2004-2023 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Alle rechten voorbehouden. Niets uit deze uitgave mag worden vervoelvoudigd, opgeslagen in een geautomatiseerd gegevensbestand, of openbaar gemaakt, in enige vorm of op enige wijze, hetzij elektronisch, mechanisch, door fotokopieën, opnamen, of enig andere manier, zonder voorafgaande schriftelijke toestemming van de uitgever.

Onlangs alle aan de samenstelling van deze tekst bestede zorg, kan noch de schrijver noch de uitgever aansprakelijkheid aanvaarden voor eventuele schade, die zou kunnen voortvloeien uit enige fout, die in deze uitgave zou kunnen voorkomen.

Deze handleiding is een naslagwerk bedoeld om het gebruik te verduidelijken. Indien gegevens in de voorbeeldafbeeldingen overeenkomen met gegevens in uw systeem, dan is de overeenkomst toevallig.

Belangrijke Informatie over Veiligheid en Gebruik

Beoogd gebruik en beperkingen: Deze software, ontwikkeld door Invantive, is ontworpen om een verscheidenheid aan zakelijke en informatietechnologische gegevensverwerkingsfuncties te ondersteunen, zoals boekhouding, financiële rapportage en verkooprapportage. Het is belangrijk om op te merken dat deze software niet is ontworpen, getest of goedgekeurd voor gebruik in omgevingen waar een storing of defect kan leiden tot levensbedreigende situaties, ernstige fysieke schade of milieuschade. Dit omvat, maar is niet beperkt tot:

- Nucleaire faciliteiten: de software mag niet worden gebruikt voor operaties of functies die verband houden met de controle, het onderhoud of de werking van nucleaire faciliteiten.
- Defensie en militaire toepassingen: deze software is niet geschikt voor gebruik in defensiegerelateerde toepassingen, inclusief maar niet beperkt tot wapenbeheer, militaire strategieplanning of andere aspecten van nationale defensie.
- Luchtvaart: de software is niet bedoeld voor gebruik in de bediening, navigatie of communicatiesystemen van vliegtuigen of luchtverkeersleidingomgevingen.
- Gezondheidszorg en medicijnproductie: deze software mag niet worden gebruikt voor de werking van medische apparaten, de analyse van patiëntgegevens voor kritieke gezondheidsbeslissingen, farmaceutische productie of medisch onderzoek waarbij een storing of defect de gezondheid van de patiënt kan beïnvloeden.
- Verwerking van chemische en/of gevaarlijke stoffen: deze software is niet bedoeld voor het beheer, de controle of de operationele aspecten van chemische fabrieken of faciliteiten voor de verwerking van chemische en/of gevaarlijke stoffen. Elke storing in de software die in deze omgevingen wordt gebruikt kan leiden tot gevaarlijke chemische lozingen, explosies of milieurampen.
- Transport- en verkeerscontrolesystemen: de software mag niet worden gebruikt voor de besturing, bediening of het beheer van transportsystemen, waaronder de besturing van spoorwegsignalen, metrosystemen of verkeerslichten. Storingen in dergelijke kritieke systemen kunnen tot ernstige ongelukken leiden en de openbare veiligheid in gevaar brengen.
- Energienetwerk- en nutsbesturingssystemen: deze software is niet ontworpen voor de besturing of bediening van energienetwerksystemen, waaronder elektrische onderstations, besturingssystemen voor hernieuwbare energie of besturingssystemen van waternutsbedrijven. Het falen van software op deze gebieden kan leiden tot aanzienlijke stroomonderbrekingen, onderbrekingen in de watervoorziening of andere storingen in openbare voorzieningen, waardoor gemeenschappen in gevaar kunnen komen en grote schade kan worden aangericht.
- Andere omgevingen met een hoog risico: alle andere kritieke infrastructuren en omgevingen waar een storing in de software kan leiden tot aanzienlijke schade aan personen of het milieu.

Gebruikersverantwoordelijkheid: gebruikers moeten ervoor zorgen dat ze het beoogde gebruik van de software begrijpen en de software niet gebruiken in een omgeving die buiten het beoogde doel valt. Het is de verantwoordelijkheid van de gebruiker om de geschiktheid van de software voor de beoogde toepassing te beoordelen, vooral in scenario's die een risico kunnen vormen voor leven, gezondheid en/of milieu.

Afwijzing van aansprakelijkheid: Invantive wijst elke verantwoordelijkheid af voor schade, letsel of wettelijke gevolgen die voortvloeien uit het gebruik of misbruik van deze software in verboden en/of onbedoelde toepassingen.

Inhoud

1	SQL Driver for rdw.nl API	1
2	SQL Driver Attributes for rdw.nl API	2
3	Schema: Native	13
3.1	Tables	13
3.1.1	NATIVEPLATFORMSCALARREQUESTS	13
4	Schema: RDW	15
4.1	Tables	15
4.1.1	rdw_acknowledged_companies	15
4.1.2	rdw_acknowledgments	16
4.1.3	rdw_availability_expansions	16
4.1.4	rdw_availability_restrictions	17
4.1.5	rdw_axis_data_eeg_versions	18
4.1.6	rdw_basic_data_eeg_versions	19
4.1.7	rdw_brand_version_allowed	22
4.1.8	rdw_callback_action_risks	23
4.1.9	rdw_callback_action_statuses	23
4.1.10	rdw_callback_actions	24
4.1.11	rdw_callback_inform_owners	25
4.1.12	rdw_callback_vehicles_brand_types	25
4.1.13	rdw_chassis_version_classes	26
4.1.14	rdw_chassis_version_numeric_codes	26
4.1.15	rdw_chassis_versions	27
4.1.16	rdw_clutch_versions	28
4.1.17	rdw_contacts	28
4.1.18	rdw_eeg_vehicle_acceptances	29
4.1.19	rdw_engine_fuel_versions	30
4.1.20	rdw_engine_versions	32
4.1.21	rdw_entrances_and_exits	34
4.1.22	rdw_geological_selling_points	35
4.1.23	rdw_gps_coordinates	36
4.1.24	rdw_indexes_static_and_dynamic: rdw.nl trade_name	36
4.1.25	rdw_licensed_fuel_vehicles	37
4.1.26	rdw_licensed_vehicle_chassis_specifications	38
4.1.27	rdw_licensed_vehicles_axis	38
4.1.28	rdw_licensed_vehicles_chassis	39
4.1.29	rdw_licensed_vehicles_classes	40
4.1.30	rdw_location_pinpoint_versions	40
4.1.31	rdw_open_parkings	41
4.1.32	rdw_parking_accesses	42
4.1.33	rdw_parking_adresses	42
4.1.34	rdw_parking_area	43
4.1.35	rdw_parking_area_contacts	44
4.1.36	rdw_parking_area_geometries	44
4.1.37	rdw_parking_area_managers	45
4.1.38	rdw_parking_area_regulation	46
4.1.39	rdw_parking_areas	46
4.1.40	rdw_parking_areaspecifications	47
4.1.41	rdw_parking_time_frames	48

4.1.42	rdw_payment_method_areas	48
4.1.43	rdw_payment_method_selling_points	49
4.1.44	rdw_price_calculations	50
4.1.45	rdw_price_parts	50
4.1.46	rdw_product_catalogs	51
4.1.47	rdw_regulations	52
4.1.48	rdw_selling_points	52
4.1.49	rdw_special_days	53
4.1.50	rdw_subcategory_versions	54
4.1.51	rdw_trade_name_versions: rdw.nl trade_name	54
4.1.52	rdw_user_goals	55
4.1.53	rdw_vehicles	56
4.1.54	rdw_vehicles_by_tag	57
4.1.55	rdw_version_user_data_per_delivery	58

Index

60

1 SQL Driver for rdw.nl API

Invantive SQL is the fastest, easiest and most reliable way to exchange data with the rdw.nl API.

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the [user community](#). Other users or Invantive Support will try to help you to our best.

RDW is the Dutch register for vehicles. The RDW data is available online, even up to specific license plates registered in the Netherlands.

The rdw.nl driver covers 56 tables and 665 columns.

rdw.nl API Clients

Invantive SQL is available on many user interfaces ("clients" in traditional server-client paradigm). All Invantive SQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL. High-volume replication of data taken from the rdw.nl API into traditional databases such as SQL Server (on-premise and Azure), MySQL, PostgreSQL and Oracle is possible using [Invantive Data Replicator](#). Invantive Data Replicator automatically creates and maintains rdw.nl datawarehouses, possibly in combination with data from over 70 other (cloud) platforms. Data Replicator supports data volumes up to over 1 TB and over 5.000 companies. The on-premise edition of Invantive Bridge offers an rdw.nl ADO.net provider.

Monitor API Calls

When a query or DML-statement has been executed on Invantive SQL a developer can evaluate the actual calls made to the rdw.nl API using a query on sessionios@DataDictionary. As an alternative, extensive request and response logging can be enabled by setting log-native-calls-to-disk to true. In the %USERPROFILE%\Invantive\NativeLog folder Invantive SQL will create log files per API request and response.

Specifications

The SQL driver for rdw.nl does not support partitioning. Define one data container in a database for each company in rdw.nl to enable parallel access for data from multiple companies.

An introduction into the concepts of Invantive SQL such as databases, data containers and partitioning can be found in the [Invantive SQL grammar](#).

The configuration can be changed using various attributes during log on and use. A full list of configuration options is listed in the [driver attributes](#) ².

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On rdw.nl the comparison of two texts is case sensitive by default.

Changes and bug fixes on the rdw.nl SQL driver can be found in the [release notes](#). There is currently no specific section on the [Invantive forums](#) for rdw.nl. Please reach out to other users of rdw.nl by leaving a question or contact request.

Driver code for use in settings.xml: RdwNl

Alias: rdwnl

Recommended alias: rdw

More technical documentation as provided by the supplier of the rdw.nl API on the native APIconnection used can be found at <https://www.rdw.nl/opendata/Paginas/default.aspx>.

Updated: 29-05-2022 00:59 using Invantive SQL version 22.0.196-PROD+3400.

2 SQL Driver Attributes for rdw.nl API

The SQL driver for rdw.nl has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the API server of rdw.nl or high-volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The rdw.nl driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Drivers file: the providers.xml file (obsolete starting release 17.32).
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for rdw.nl can be found in the settings*.xml file used for the database. Settings*.xml files are typically located in the %USERPROFILE%\invantive folder in most deployment scenarios. The reference manuals contain instructions how to relocate the settings*.xml files. Each data container of a database in the connection string can have a connectionString element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: set NAME VALUE, or for a distributed database: set NAME@ALIAS VALUE. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The rdw.nl driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
add-odata-mandatory-filters	Whether to automatically add OData filters deemed necessary by the platform.	OData	False	✓	✓	✓	
analysis-enforce-row-uniqueness	Use for analysis only! Enforce rows to be unique.	Shared	False	✓	✓	✓	
api-url	URL to access the API.	OData		✓		✓	
bulk-delete-page-size-rows	Number of rows to delete per batch when bulk deleting	Shared	10000	✓	✓	✓	
bulk-insert-page-size-bytes	Approximate maximum size in bytes of batch when bulk inserting	Shared	10000000	✓	✓	✓	
bulk-insert-page-size-rows	Number of rows to insert per batch when bulk inserting	Shared	250	✓	✓	✓	
download-error-400-bad-request-max-tries	Maximum number of tries when OData server reports bad format during retrieval of data.		30	✓	✓	✓	
download-error-400-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		10000	✓	✓	✓	
download-error-400-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		300000	✓	✓	✓	
download-error-400-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
download-error-408-request-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 408.		10	✓	✓	✓	
download-error-408-request-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 408.		10000	✓	✓	✓	
download-error-408-request-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 408.		300000	✓	✓	✓	
download-error-408-request-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 408.		2	✓	✓	✓	
download-error-422-bad-request-max-tries	Maximum number of tries when OData server reports unprocessable entity during retrieval of data.		30	✓	✓	✓	
download-error-422-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports unprocessable entity during retrieval of data.		10000	✓	✓	✓	
download-error-422-bad-request-	Maximum sleep in milliseconds between retries when OData server		300000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
sleep-max-ms	reports unprocessable entity during retrieval of data.						
dow nload-error-422-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports unprocessable entity during retrieval of data.		2	✓	✓	✓	
dow nload-error-429-too-many-requests-max-tries	Maximum number of tries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10000	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		300000	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		2	✓	✓	✓	
dow nload-error-502-server-unavailable-max-tries	Maximum number of tries when OData server reports a bad gateway during retrieval of data.		30	✓	✓	✓	
dow nload-error-502-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports a bad gateway during retrieval of data.		10000	✓	✓	✓	
dow nload-error-502-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that a bad gateway during retrieval of data.		300000	✓	✓	✓	
dow nload-error-502-server-unavailable-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports a bad gateway during retrieval of data.		2	✓	✓	✓	
dow nload-error-503-server-unavailable-max-tries	Maximum number of tries when OData server reports that the API server is unavailable during retrieval of data.		30	✓	✓	✓	
dow nload-error-503-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		10000	✓	✓	✓	
dow nload-error-503-server-	Maximum sleep in milliseconds between retries when OData server		300000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
unavailable-sleep-max-ms	reports that the API server is unavailable during retrieval of data.						
dow nload-error-503-server-unavailable-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
dow nload-error-504-gateway-timeout-max-tries	Maximum number of tries when the website reports a gateway timeout.		10	✓	✓	✓	
dow nload-error-504-gateway-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a gateway timeout.		10000	✓	✓	✓	
dow nload-error-504-gateway-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a gateway timeout.		300000	✓	✓	✓	
dow nload-error-504-gateway-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a gateway timeout.		2	✓	✓	✓	
dow nload-error-590-netw ork-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 590.		10	✓	✓	✓	
dow nload-error-590-netw ork-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 590.		10000	✓	✓	✓	
dow nload-error-590-netw ork-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 590.		300000	✓	✓	✓	
dow nload-error-590-netw ork-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 590.		2	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 599.		10	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 599.		10000	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 599.		300000	✓	✓	✓	
dow nload-error-599-netw ork-	Multiplication factor for sleep between retries when the website		2	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
connect-timeout-sleep-multiplicator	reports a HTTP status 599.						
dow nload-error-argument-exception-max-tries	Maximum number of tries w hen an argument exception is returned w hen dow nloading a blob.		10	✓	✓	✓	
dow nload-error-argument-exception-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen an argument exception is returned w hen dow nloading a blob.		10000	✓	✓	✓	
dow nload-error-argument-exception-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen an argument exception is returned w hen dow nloading a blob.		300000	✓	✓	✓	
dow nload-error-argument-exception-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen an argument exception is returned w hen dow nloading a blob.		2	✓	✓	✓	
dow nload-error-internet-dow n-max-tries	Maximum number of tries w hen the Internet connection seems dow n during retrieval of data.		10	✓	✓	✓	
dow nload-error-internet-dow n-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen the Internet connection seems dow n during retrieval of data.		10000	✓	✓	✓	
dow nload-error-internet-dow n-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen the Internet connection seems dow n during retrieval of data.		300000	✓	✓	✓	
dow nload-error-internet-dow n-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen the Internet connection seems dow n during retrieval of data.		2	✓	✓	✓	
dow nload-error-io-exception-max-tries	Maximum number of tries w hen a netw ork I/O connection failure occurs during retrieval of data.		10	✓	✓	✓	
dow nload-error-io-exception-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen a netw ork I/O connection failure occurs during retrieval of data.		10000	✓	✓	✓	
dow nload-error-io-exception-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen a netw ork I/O connection failure occurs during retrieval of data.		300000	✓	✓	✓	
dow nload-error-io-exception-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen a netw ork I/O connection failure occurs during retrieval of data.		2	✓	✓	✓	
dow nload-error-json-exception-max-tries	Maximum number of tries w hen an invalid JSON body is returned.		3	✓	✓	✓	
dow nload-error-json-exception-	Initial sleep in milliseconds betw een retries w hen an invalid JSON body is		1000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
sleep-initial-ms	returned.						
download-error-json-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an invalid JSON body is returned.		10000	✓	✓	✓	
download-error-json-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an invalid JSON body is returned.		2	✓	✓	✓	
download-error-other-exception-max-tries	Maximum number of tries when an unqualified error occurs during retrieval of data.		3	✓	✓	✓	
download-error-other-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an unqualified error occurs during retrieval of data.		10000	✓	✓	✓	
download-error-other-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an unqualified error occurs during retrieval of data.		300000	✓	✓	✓	
download-error-other-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an unqualified error occurs during retrieval of data.		2	✓	✓	✓	
download-error-socket-exception-max-tries	Maximum number of tries when the network connection is forcibly dropped during retrieval of data.		10	✓	✓	✓	
download-error-socket-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when the network connection is forcibly dropped during retrieval of data.		10000	✓	✓	✓	
download-error-socket-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when the network connection is forcibly dropped during retrieval of data.		300000	✓	✓	✓	
download-error-socket-exception-sleep-multiplicator	Multiplication factor for sleep between retries when the network connection is forcibly dropped during retrieval of data.		2	✓	✓	✓	
download-error-web-exception-max-tries	Maximum number of tries when a web connection failure occurs during retrieval of data.		10	✓	✓	✓	
download-error-web-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		10000	✓	✓	✓	
download-error-web-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		300000	✓	✓	✓	
download-error-web-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a web connection failure occurs during retrieval of data.		2	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
dow nload-error-web-not-implemented-max-tries	Maximum number of tries w hen the connection reports not implemented.		1	✓	✓	✓	
dow nload-error-web-not-implemented-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen the connection reports not implemented.		10000	✓	✓	✓	
dow nload-error-web-not-implemented-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen the connection reports not implemented.		300000	✓	✓	✓	
dow nload-error-web-not-implemented-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen the connection reports not implemented.		2	✓	✓	✓	
dow nload-error-web-timeout-max-tries	Maximum number of tries w hen the connection reports a timeout.		10	✓	✓	✓	
dow nload-error-web-timeout-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen the connection reports a timeout.		10000	✓	✓	✓	
dow nload-error-web-timeout-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen the connection reports a timeout.		300000	✓	✓	✓	
dow nload-error-web-timeout-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen the connection reports a timeout.		2	✓	✓	✓	
dow nload-error-web-unauthorized-max-tries	Maximum number of tries w hen the connection reports an unauthorized error.		1	✓	✓	✓	
dow nload-error-web-unauthorized-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen the connection reports an unauthorized error.		10000	✓	✓	✓	
dow nload-error-web-unauthorized-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen the connection reports an unauthorized error.		300000	✓	✓	✓	
dow nload-error-web-unauthorized-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen the connection reports an unauthorized error.		2	✓	✓	✓	
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	Shared	False	✓	✓	✓	
forced-casing-identifiers	Forced casing of identifiers. Choose from Unset, Low er, Upper and Mixed.	Shared		✓	✓	✓	
http-disk-cache-compression-level	Compression level for the HTTP disk cache, ranging from 1 (little) to 9 (intense). Default is 5.	Shared	5	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
http-disk-cache-directory	Directory where HTTP cache is stored.	Shared	C:\Users\gle3.WS212\Invasive\Cache\http\gle3\shared	✓	✓	✓	
http-disk-cache-ignore-write-errors	Whether to ignore write errors to disk cache.	Shared	False	✓	✓	✓	
http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP disk cache.	Shared	2592000	✓	✓	✓	
http-get-timeout-ms	HTTP GET timeout (ms).		300000	✓	✓	✓	
http-memory-cache-compression-level	Compression level for the HTTP memory cache, ranging from 1 (little) to 9 (intense). Default is 5.	OData	5	✓	✓	✓	
http-memory-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP memory cache.	OData	14400	✓	✓	✓	
http-post-timeout-ms	HTTP POST timeout (ms).		300000	✓	✓	✓	
ignore-http-400-errors	Ignore HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-401-errors	Ignore HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-402-errors	Ignore HTTP 402 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-403-errors	Ignore HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-404-errors	Ignore HTTP 404 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-422-errors	Ignore HTTP 422 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-429-errors	Ignore HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-500-errors	Ignore HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-502-errors	Ignore HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-503-errors	Ignore HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
invalid-json-on-get-max-tries	Maximum number of tries when the JSON received on GET is invalid.		10	✓	✓	✓	
invalid-json-on-get-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on GET is invalid.		10000	✓	✓	✓	
invalid-json-on-get-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on GET is invalid.		300000	✓	✓	✓	
invalid-json-on-get-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on GET is invalid.		2	✓	✓	✓	
invalid-json-on-post-max-tries	Maximum number of tries when the JSON received on POST is invalid.		1	✓	✓	✓	
invalid-json-on-post-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on POST is invalid.		10000	✓	✓	✓	
invalid-json-on-post-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on POST is invalid.		300000	✓	✓	✓	
invalid-json-on-post-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on POST is invalid.		2	✓	✓	✓	
invantive-sql-compress-sparse-arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753.	SQL Engine V1	False	✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-shuffle-fetch-results-data-containers	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	✓	✓	✓	
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	✓	✓	✓	
join-set-points-per-request	Maximum number of values in a request when executing a join set.	OData	60	✓	✓	✓	
limit-partition-calls-left	Minimum number of remaining API calls on a partition towards a hard limit. When below, an error is raised.	OData	500	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
log-native-calls-to-disk-max-events	Maximum number of events to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-max-seconds	Maximum number of seconds to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-on-error	Registers native calls to data container backend as disk files w hen an error occurred.	Shared	False	✓	✓	✓	
log-native-calls-to-disk-on-success	Registers native calls to data container backend as disk files w hen successful.	Shared	False	✓	✓	✓	
log-native-calls-to-trace	Log native calls to data container backend on the trace.	Shared	False	✓	✓	✓	
maximum-length-identifiers	Non-default maximum length in characters of identifier names.	Shared		✓	✓	✓	
max-odata-filters	The maximum number of OData filter elements.	OData	100	✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	Shared	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	Shared	8000	✓	✓	✓	
metadata-cache-max-age-sec	Maximum acceptable age in seconds for re-use of metadata.	OData		✓	✓	✓	
oauth-unauthorized-max-tries	Maximum number of tries w hen an OAuth exception occurs.	OData	2	✓	✓	✓	
oauth-unauthorized-sleep-initial-ms	Initial sleep in milliseconds betw een OAuth reauthentication tries w hen the OAuth authentication fails.	OData	10000	✓	✓	✓	
oauth-unauthorized-sleep-max-ms	Maximum sleep in milliseconds betw een OAuth reauthentication tries w hen the OAuth authentication fails.	OData	1000	✓	✓	✓	
oauth-unauthorized-sleep-multiplicator	Multiplication factor for sleep betw een OAuth reauthentication tries w hen the OAuth authentication fails.	OData	2	✓	✓	✓	
partition-slot-based-rate-limit-length-ms	Total length in ms across all slots of a partition-based rate limit.	Shared	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	Shared	0	✓	✓	✓	
requested-page-size	Preferred number of row s to exchange per round trip; only effective on limited platforms such as AFAS Online	Shared		✓	✓	✓	
requests-parallel-max	Maximum number of parallel data requests from individual partitions on	Shared	32	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
	the data container.						
simulate-http-400-errors	Simulate HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-400-errors-percentage	Percentage of simulated HTTP 400 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-401-errors	Simulate HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-401-errors-percentage	Percentage of simulated HTTP 401 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-403-errors	Simulate HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-403-errors-percentage	Percentage of simulated HTTP 403 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-408-errors	Simulate HTTP 408 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-408-errors-percentage	Percentage of simulated HTTP 408 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-429-errors	Simulate HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-429-errors-percentage	Percentage of simulated HTTP 429 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-500-errors	Simulate HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-500-errors-percentage	Percentage of simulated HTTP 500 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-502-errors	Simulate HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-502-errors-percentage	Percentage of simulated HTTP 502 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-503-errors	Simulate HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-503-errors-percentage	Percentage of simulated HTTP 503 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
simulate-http-protocol-errors	Simulate HTTP protocol errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-protocol-errors-percentage	Percentage of simulated HTTP protocol errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-timeout-errors	Simulate HTTP timeout errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-timeout-errors-percentage	Percentage of simulated HTTP timeout errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
slot-based-rate-limit-length-ms	Total length in ms across all slots of a slot-based rate limit.	Shared	60000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	✓	✓	✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	Shared	True	✓	✓	✓	
use-batch-insert	Whether to use batch insert.	OData	True	✓	✓	✓	
use-http-disk-cache-read	Whether to use HTTP responses from previous queries stored on disk to answer the current query.	Shared	False	✓	✓	✓	
use-http-disk-cache-write	Whether to memorize HTTP responses on disk.	Shared	False	✓	✓	✓	
use-http-memory-cache-read	Whether to use HTTP responses from previous queries stored in memory that can answer the current query.	OData	True	✓	✓	✓	
use-http-memory-cache-write	Whether to memorize HTTP responses from previous queries for use by future queries.	OData	True	✓	✓	✓	

3 Schema: Native

3.1 Tables

3.1.1 NATIVEPLATFORMSCALARREQUESTS

Direct access to native API.

Catalog: RDW

Schema: Native

Alias: npt

Documentation:

The NativePlatformScalarRequests table provides direct access to the native API protocol over an established connection to the rdw.nl API server. It will contain a new row for every row inserted with a native API request in PAYLOAD_TEXT with the results of unaltered forwarding of the payload to the rdw.nl API server.

Retrieve: true

Insert: true

Update: false

Delete: false

View Columns

The columns of the view NATIVEPLATFORMSCALARREQUESTS are shown below. Each column has an SQL data type. A new non-null value must be provided for every required column at all times during insert.

Name	Data Type	Label	Required	Documentation
BLOB_PREFERRED	boolean		☒	Indicator whether a BLOB result is preferred over text.
BOL_RESPONSE_CACHE_MAX_AGE_SEC	int32		☐	Maximum age in seconds of Bridge Online response cache entries to be used.
CONTENT_TYPE	string(240)		☐	
DATE_ENDED	datetime		☒	
DATE_STARTED	datetime		☒	
DRY_RUN	boolean		☒	
DURATION_MS	int32		☒	
ERROR_MESSAGE_CODE	string(30)		☐	
ERROR_MESSAGE_TEXT	string(32000)		☐	
FAIL_ON_ERROR	boolean		☒	Whether to raise an exception when processing the native request triggered an error from the provider.
HTTP_DISK_CACHE_MAX_AGE_SEC	int32		☐	Maximum age in seconds of HTTP disk cache entries to be used.
HTTP_DISK_CACHE_SAVE	boolean		☐	Whether results can be stored in HTTP disk cache.
HTTP_DISK_CACHE_USE	boolean		☐	Whether results can be fetched from HTTP disk cache.
HTTP_MEMORY_CACHE_MAX_AGE_SEC	int32		☐	Maximum age in seconds of HTTP memory cache entries to be used.
HTTP_MEMORY_CACHE_SAVE	boolean		☐	Whether results can be stored in HTTP memory cache.
HTTP_MEMORY_CACHE_USE	boolean		☐	Whether results can be fetched from HTTP memory cache.

Name	Data Type	Label	Required	Documentation
HTTP_METHOD	string(30)		☐	
HTTP_STATUS_CODE	int16		☐	
ORIG_SYSTEM_GROUP	string(4000)		☐	
ORIG_SYSTEM_REFERENCE	string(4000)		☐	
PAYLOAD_TEXT	string		☐	
RESULT_BLOB	byte[]		☐	
RESULT_DATE_TIME_UTC	datetime		☐	
RESULT_NUMBER	decimal		☐	
RESULT_TEXT	string		☐	
SUCCESSFUL	boolean		☒	
TIMEOUT_SEC	int32		☐	Timeout in seconds.
TRANSACTION_ID	int32		☒	Incrementing ID of the transaction.
URL	string(4000)		☐	

4 Schema: RDW

4.1 Tables

4.1.1 rdw_acknowledged_companies

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/w22j-fpxa.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/w22j-fpxa.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/w22j-fpxa.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/w22j-fpxa.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_acknowledged_companies` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
api_bedrijf_erkenningen	string		☐	
gevelnaam	string		☐	
huisnummer_toevoeging	string		☐	
huisnummer	string		☐	

Name	Data Type	Label	Required	Documentation
naam_bedrijf	string		☐	
plaats	string		☐	
postcode_alfanumeriek	string		☐	
postcode_numeriek	decimal		☐	
straat	string		☐	
volgnummer	decimal		☐	

4.1.2 rdw_acknowledgments

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/pgca-kait.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/pgca-kait.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/pgca-kait.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/pgca-kait.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_acknowledgments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
erkenning	string		☐	
volgnummer	int64		☐	

4.1.3 rdw_availability_expansions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/tqt3-ecbk.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/tqt3-ecbk.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/tqt3-ecbk.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/tqt3-ecbk.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_availability_expansions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areaidvalidityextension	string		☐	
areamanagerid	decimal		☐	
endvalidityextension	string		☐	
startvalidityextension	string		☐	
usageid	string		☐	
validityextensiontype	string		☐	

4.1.4 rdw_availability_restrictions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/d8gy-rw99.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/d8gy-rw99.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/d8gy-rw99.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/d8gy-rw99.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_availability_restrictions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areaidvalidityextension	string		☐	
areamanagerid	decimal		☐	
enddaytimeframevalidityrestriction	string		☐	
enddurationvalidityrestriction	decimal		☐	
indexnumbervalidityrestriction	decimal		☐	

Name	Data Type	Label	Required	Documentation
startdaytimeframevalidityrestriction	string		☐	
startdurationvalidityrestriction	decimal		☐	
startvalidityextension	string		☐	
usageid	string		☐	

4.1.5 rdw_axis_data_eeg_versions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/3x93-gmvu.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/3x93-gmvu.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/3x93-gmvu.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/3x93-gmvu.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_axis_data_eeg_versions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
aangedreven_as	string		☐	
afstand_volgende_as_bovengrens	decimal		☐	
afstand_volgende_as_ondergrens	decimal		☐	
asnummer	string		☐	
dubbele_montage	string		☐	
eeg_uitvoeringscode	string		☐	
eeg_variantcode	string		☐	
eu_type_goedkeuringssleutel	string		☐	
gelijkwaardig_aan_luchtvering	string		☐	
gestuurde_as_indicator	string		☐	
hefas	string		☐	
luchtvering	string		☐	
plaats_as_code	string		☐	
rolstraat_bovengrens	decimal		☐	
rolstraat_ondergrens	decimal		☐	
snelheidssymbool_ondergrens	string		☐	

Name	Data Type	Label	Required	Documentation
spoorbreedte_bovengrens	decimal		☐	
spoorbreedte_ondergrens	decimal		☐	
techn_max_last_as_bovengrens	decimal		☐	
techn_max_last_as_ondergrens	decimal		☐	
techn_max_last_asstel_bovengr	decimal		☐	
techn_max_last_asstel_ondergr	decimal		☐	
uitvoering_w_izigingsnummer	decimal		☐	

4.1.6 rdw_basic_data_eeg_versions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/3qit-y5pc.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/3qit-y5pc.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/3qit-y5pc.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/3qit-y5pc.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table rdw_basic_data_eeg_versions are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
_24ghz_kortbereik_radar	string		☐	
aant_zitpl_stilst_vrtg_bovengrens	decimal		☐	
aant_zitpl_stilst_vrtg_ondergrens	decimal		☐	
aantal_aangedreven_assen	decimal		☐	
aantal_deuren_bovengrens	decimal		☐	
aantal_deuren_ondergrens	decimal		☐	
aantal_passagier_zittend_bovengrens	decimal		☐	
aantal_passagier_zittend_ondergrens	decimal		☐	
aantal_passagiers_bovengrens	decimal		☐	
aantal_passagiers_ondergrens	decimal		☐	
aantal_rolstoel_plaats_bovengrens	decimal		☐	
aantal_rolstoel_plaats_ondergrens	decimal		☐	

Name	Data Type	Label	Required	Documentation
aantal_wielen	decimal		☐	
aantal_zitplaatsen_bovengrens	decimal		☐	
aantal_zitplaatsen_ondergrens	decimal		☐	
afst_hart_koppeling_as_bovengrens	decimal		☐	
afst_hart_koppeling_as_ondergrens	decimal		☐	
begindatum_restant_voorraad	decimal		☐	
begindatum_uitvoering	decimal		☐	
breedte_voertuig_uitvoering_bovengrens	decimal		☐	
breedte_voertuig_uitvoering_ondergrens	decimal		☐	
code_status_intrekking_uitvoering	string		☐	
compleet_voertuig_indicator	string		☐	
datum_status_wijziging	decimal		☐	
eeg_uitvoering_cat_toevoeging	string		☐	
eeg_uitvoeringscode	string		☐	
eeg_variantcode	string		☐	
eindatum_restant_voorraad	decimal		☐	
einddatum_uitvoering	decimal		☐	
eu_type_goedkeuringssleutel	string		☐	
eur_codering_carrosserietype	string		☐	
handelsbenaming	string		☐	
hoogte_voertuig_uitvoering_bovengrens	decimal		☐	
hoogte_voertuig_uitvoering_ondergrens	decimal		☐	
inhoud_brandstoftank	decimal		☐	
inrichtingscode	decimal		☐	
intrekdatum_uitvoering	decimal		☐	
kant_van_het_stuur	string		☐	
lengte_laadruimte_bovengrens	decimal		☐	
lengte_laadruimte_ondergrens	decimal		☐	
lengte_voertuig_uitvoering_bovengrens	decimal		☐	
lengte_voertuig_uitvoering_ondergrens	decimal		☐	
links_rechts_rijdend	string		☐	
massa_bedrijfsklaar_toestand_bovengrens	decimal		☐	
massa_bedrijfsklaar_toestand_ondergrens	decimal		☐	
massa_leeg_voertuig_bovengrens	decimal		☐	

Name	Data Type	Label	Required	Documentation
massa_leeg_voertuig_ondergrens	decimal		☐	
max_breedte_voertuig_bovengren s	decimal		☐	
max_breedte_voertuig_ondergrens	decimal		☐	
max_constructie_snelheid_boveng rens	decimal		☐	
max_constructie_snelheid_ondergr ens	decimal		☐	
max_lengte_voertuig_bovengren s	decimal		☐	
max_lengte_voertuig_ondergrens	decimal		☐	
max_massa_geremd_bovengren s	decimal		☐	
max_massa_geremd_ondergrens	decimal		☐	
max_massa_ongeremd_bovengren s	decimal		☐	
max_massa_ongeremd_ondergren s	decimal		☐	
max_massa_samenstel_bovengre ns	decimal		☐	
max_massa_samenstel_ondergren s	decimal		☐	
max_massa_voertuig_bovengren s	decimal		☐	
max_massa_voertuig_ondergrens	decimal		☐	
max_massa_vrtg_techn_bovengre ns	decimal		☐	
max_massa_vrtg_techn_ondergre ns	decimal		☐	
max_ondersteunde_snelheid	decimal		☐	
max_ondersteuning_snelheid_bov engren s	decimal		☐	
max_ondersteuning_snelheid_ond ergren s	decimal		☐	
min_massa_voertuig	decimal		☐	
status_voertiug_kentekening	string		☐	
techn_max_last_koppelpunt_boven grens	decimal		☐	
techn_max_last_koppelpunt_ond ergren s	decimal		☐	
techn_max_massa_autonoom_bov engren s	decimal		☐	
techn_max_massa_autonoom_ond ergren s	decimal		☐	
techn_max_massa_middenas_bov engren s	decimal		☐	
techn_max_massa_middenas_ond ergren s	decimal		☐	
techn_max_massa_oplegger_bove ngren s	decimal		☐	

Name	Data Type	Label	Required	Documentation
techn_max_massa_oplegger_ondergrens	decimal		☐	
techn_max_massa_samenst_bovengrens	decimal		☐	
techn_max_massa_samenst_ondergrens	decimal		☐	
tw_eede_brandstofcode_voertuig	string		☐	
uitvoering_registratie_datum	decimal		☐	
uitvoering_w_ijzigingsnummer	decimal		☐	
variant_status	string		☐	
wielbasis_bovengrens	decimal		☐	
wielbasis_ondergrens	decimal		☐	
zelfdragende_carrosserie	string		☐	

4.1.7 rdw_brand_version_allowed

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/98t6-6fxk.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/98t6-6fxk.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/98t6-6fxk.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/98t6-6fxk.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table rdw_brand_version_allowed are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
eeg_uitvoeringscode	string		☐	
eeg_variantcode	string		☐	
eu_type_goedkeuringssleutel	string		☐	
merk_registratie_datum	decimal		☐	
merkcode	string		☐	
uitvoering_w_ijzigingsnummer	decimal		☐	

4.1.8 rdw_callback_action_risks

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/pjc7-386e.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/pjc7-386e.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/pjc7-386e.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/pjc7-386e.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_callback_action_risks` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>code_mogelijk_gevaar</code>	string		☐	
<code>mogelijk_gevaar</code>	string		☐	
<code>referentiecode_rdw</code>	string		☐	

4.1.9 rdw_callback_action_statuses

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/jct3-vb8s.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/jct3-vb8s.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/jct3-vb8s.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/jct3-vb8s.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_callback_action_statuses` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code_status	string		☐	
kenteken	string		☐	
referentiecode_rdw	string		☐	
status	string		☐	

4.1.10 rdw_callback_actions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/af5r-44mf.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/af5r-44mf.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/af5r-44mf.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/af5r-44mf.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table rdw_callback_actions are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
api_terugroep_actie_risico	string		☐	
api_terugroep_actie_status	string		☐	
api_terugroep_infomeren_eigenaar	string		☐	
api_terugroep_voertuig_merk_type	string		☐	
beschrijving_van_het_herstel	string		☐	
categorie_defect	string		☐	
materi_le_gevolgen	string		☐	
meer_informatie_op_internet	string		☐	
meer_informatie_via_telefoonnummer	string		☐	
meldende_producent_distributeur	string		☐	
omschrijving_defect	string		☐	
opmerkingen_rdw	string		☐	
publicatiedatum_rdw	string		☐	
referentiecode_producent	string		☐	
referentiecode_rdw	string		☐	

4.1.11 rdw_callback_inform_owners

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/223d-3w9w.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/223d-3w9w.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/223d-3w9w.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/223d-3w9w.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_callback_inform_owners` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code_w ijze_informeren	string		☐	
referentiecode_rdw	string		☐	
w ijze_w aarop_u_w ordt_ge_nform eerd	string		☐	

4.1.12 rdw_callback_vehicles_brand_types

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/4kb9-9jb9.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/4kb9-9jb9.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/4kb9-9jb9.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/4kb9-9jb9.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_callback_vehicles_brand_types` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
merk	string		☐	
referentiecode_rdw	string		☐	
type	string		☐	

4.1.13 `rdw_chassis_version_classes`

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The `rdw.nl` API may not support changing the data or the Invantive SQL driver for `rdw.nl` does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the `rdw.nl` API.

Select `rdw.nl` API URL: <https://opendata.rdw.nl/resource/3x4u-4kdz.json?>

Insert `rdw.nl` API URL: <https://opendata.rdw.nl/resource/3x4u-4kdz.json?>

Update `rdw.nl` API URL: <https://opendata.rdw.nl/resource/3x4u-4kdz.json?>

Delete `rdw.nl` API URL: <https://opendata.rdw.nl/resource/3x4u-4kdz.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_chassis_version_classes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
carrosserie_klasse_europees	string		☐	
carrosserie_klasse_volgnummer	decimal		☐	
carrosserie_volgnummer	decimal		☐	
eeg_variantcode	string		☐	
eu_type_goedkeuringssleutel	string		☐	
uitvoering_w_izigingsnummer	decimal		☐	

4.1.14 `rdw_chassis_version_numeric_codes`

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The `rdw.nl` API may not support changing the data or the Invantive SQL driver for `rdw.nl` does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the `rdw.nl` API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/f9hb-wus3.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/f9hb-wus3.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/f9hb-wus3.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/f9hb-wus3.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_chassis_version_numeric_codes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>carrosserie_uitvoering_numeriek_europees</code>	string		☐	
<code>carrosserie_uitvoering_numeriek_volnummer</code>	decimal		☐	
<code>carrosserie_volnummer</code>	decimal		☐	
<code>eeg_uitvoeringscode</code>	string		☐	
<code>eeg_variantcode</code>	string		☐	
<code>eu_type_goedkeuringssleutel</code>	string		☐	
<code>uitvoering_w_izigingsnummer</code>	decimal		☐	

4.1.15 rdw_chassis_versions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/dexd-4khr.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/dexd-4khr.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/dexd-4khr.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/dexd-4khr.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_chassis_versions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>carrosserie_volnummer</code>	decimal		☐	
<code>eeg_uitvoeringscode</code>	string		☐	

Name	Data Type	Label	Required	Documentation
eeg_variantcode	string		☐	
eu_type_goedkeuringssleutel	string		☐	
type_carrosserie_europees	string		☐	
uitvoering_w_izigingsnummer	decimal		☐	

4.1.16 rdw_clutch_versions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/2ei8-phf6.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/2ei8-phf6.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/2ei8-phf6.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/2ei8-phf6.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_clutch_versions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
aantal_versnellingen_bovengrens	decimal		☐	
aantal_versnellingen_ondergrens	decimal		☐	
eeg_uitvoeringscode	string		☐	
eeg_variantcode	string		☐	
eu_type_goedkeuringssleutel	string		☐	
type_versnellingsbak	string		☐	
uitvoering_w_izigingsnummer	decimal		☐	
volgnummer	decimal		☐	

4.1.17 rdw_contacts

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/y8p5-qjbb.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/y8p5-qjbb.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/y8p5-qjbb.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/y8p5-qjbb.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_contacts` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactpersonid	string		☐	
emailadress	string		☐	
faxnumber	string		☐	
firstname	string		☐	
name	string		☐	
phonenumber	string		☐	
position	string		☐	

4.1.18 rdw_eeg_vehicle_acceptances

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_eeg_vehicle_acceptances` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areamanagerid	decimal		☐	
location_coordinates	string		☐	
location_type	string		☐	
sellingpointdesc	string		☐	
sellingpointid	decimal		☐	
startdatesellingpoint	datetime		☐	

4.1.19 rdw_engine_fuel_versions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/imyf-gsp6.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/imyf-gsp6.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/imyf-gsp6.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/imyf-gsp6.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_engine_fuel_versions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actieradius_brandstof_extern_oplaadbaar	decimal		☐	
actieradius_brandstof	decimal		☐	
brandstof_volnummer	decimal		☐	
brandstofcode	string		☐	
brandstofverbruik_buitenweg	decimal		☐	
brandstofverbruik_combin_rit	decimal		☐	
brandstofverbruik_stadsrit	decimal		☐	
eeg_uitvoeringscode	string		☐	
eeg_variantcode	string		☐	
elektrisch_verbruik_combinatie	decimal		☐	
elektrisch_verbruik_gecomb	decimal		☐	
emissie_aant_deeltjes_esc_test	decimal		☐	
emissie_aant_deeltjes_etc_test	decimal		☐	

Name	Data Type	Label	Required	Documentation
emissie_aant_deeltjes_t1_test	decimal		☐	
emissie_ch4_volgens_w hsc	decimal		☐	
emissie_ch4_volgens_w htc	decimal		☐	
emissie_co_bij_koude_start	decimal		☐	
emissie_co_volgens_w hsc	decimal		☐	
emissie_co_volgens_w htc	decimal		☐	
emissie_co2_buitenweg	decimal		☐	
emissie_co2_combinatie rit	decimal		☐	
emissie_co2_gecombineerd	decimal		☐	
emissie_co2_stadsrit	decimal		☐	
emissie_deeltjes_aantal_w hsc	decimal		☐	
emissie_deeltjes_aantal_w htc	decimal		☐	
emissie_deeltjes_massa_w hsc	decimal		☐	
emissie_deeltjes_massa_w htc	decimal		☐	
emissie_hc_bij_koude_start	decimal		☐	
emissie_hc_en_nox_type1	decimal		☐	
emissie_koolmonoxide_etc_test	decimal		☐	
emissie_koolmonoxide_esc_test	decimal		☐	
emissie_koolmonoxide_type_1	decimal		☐	
emissie_koolw aterstof_type_1	decimal		☐	
emissie_koolw aterstoffen_esc_test	decimal		☐	
emissie_koolw aterstoffen_etc_test	decimal		☐	
emissie_methaan_etc_test	decimal		☐	
emissie_nh3_volgens_w hsc	decimal		☐	
emissie_nh3_volgens_w htc	decimal		☐	
emissie_nmhc_volgens_w hsc	decimal		☐	
emissie_nmhc_volgens_w htc	decimal		☐	
emissie_non_methaan_koolw_etc_test	decimal		☐	
emissie_nox_volgens_w hsc	decimal		☐	
emissie_nox_volgens_w htc	decimal		☐	
emissie_stikstofoxide_type_1	decimal		☐	
emissie_stikstofoxiden_esc_test	decimal		☐	
emissie_stikstofoxiden_etc_test	decimal		☐	
emissie_thc_volgens_w hsc	decimal		☐	
emissie_thc_volgens_w htc	decimal		☐	
emissie_vaste_stofdeeltjes_esc_test	decimal		☐	
emissie_vaste_stofdeeltjes_etc_test	decimal		☐	
emissie_vaste_stofdeeltjes	decimal		☐	

Name	Data Type	Label	Required	Documentation
emissiecode	string		☐	
eu_type_goedkeuringssleutel	string		☐	
geluidsniveau_bovengrens	decimal		☐	
geluidsniveau_ondergrens	decimal		☐	
geluidsniveau_rijdend	decimal		☐	
lucht_injectie_indicator	string		☐	
max_vermogen_continu_bovengrens	decimal		☐	
max_vermogen_continu_ondergrens	decimal		☐	
maximale_biobrandstof_percentage	decimal		☐	
netto_max_vermogen_bovengrens	decimal		☐	
netto_max_vermogen_ondergrens	decimal		☐	
roet_uitstoot_acc	decimal		☐	
rookw_aarde_elr_test	decimal		☐	
soort_inspuiting_motor	string		☐	
station_toerental_bovengrens_acc	decimal		☐	
station_toerental_ondergrens_acc	decimal		☐	
toerental_max_vermogen_bovengrens	decimal		☐	
toerental_max_vermogen_ondergrens	decimal		☐	
uitlaatgas_circulatie_indicator	string		☐	
uitvoering_w_izigingsnummer	string		☐	
verbruik_gecombineerd	decimal		☐	
vermogen_bovengrens	decimal		☐	
vermogen_ondergrens	decimal		☐	
volgnummer	decimal		☐	

4.1.20 rdw_engine_versions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/datq-99xh.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/datq-99xh.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/datq-99xh.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/datq-99xh.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_engine_versions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
aantal_cilinders	decimal		☐	
brandstofcode	string		☐	
brandstofverbruik_buitenweg	decimal		☐	
brandstofverbruik_combin_rit	decimal		☐	
brandstofverbruik_stadsrit	decimal		☐	
cilinderinhoud_cm3	decimal		☐	
cng_systeem	string		☐	
eeg_uitvoeringscode	string		☐	
eeg_variantcode	string		☐	
electromotor_af_fabriek_indicator	string		☐	
emissie_co_bij_koude_start	decimal		☐	
emissie_co2_buitenweg	decimal		☐	
emissie_co2_combinatierit	decimal		☐	
emissie_co2_stadsrit	decimal		☐	
emissie_hc_bij_koude_start	decimal		☐	
emissie_hc_en_nox	decimal		☐	
emissie_koolmonoxide	decimal		☐	
emissie_koolwaterstof	decimal		☐	
emissie_stikstofoxide	decimal		☐	
emissie_vaste_stofdeeltjes	decimal		☐	
emissiecode	string		☐	
enkel_electrische_indicator	string		☐	
eu_type_goedkeuringssleutel	string		☐	
extern_oplaadbaar	string		☐	
geluidsniveau_bovengrens	decimal		☐	
geluidsniveau_ondergrens	decimal		☐	
geluidsniveau_rijdend	decimal		☐	
hybride_elektrisch_voertuig	string		☐	
katalysator_indicator	string		☐	
lpg_systeem	string		☐	
lucht_injectie_indicator	string		☐	
max_vermogen_continu_bovengrens	decimal		☐	
max_vermogen_continu_ondergrens	decimal		☐	

Name	Data Type	Label	Required	Documentation
motor_registratiedatum	decimal		☐	
motorcode	string		☐	
roet_uitstoot	decimal		☐	
soort_inspuiting_motor	string		☐	
stationair_toerental_bovengr	decimal		☐	
stationair_toerental_ondergr	decimal		☐	
toerental_geluidsniveau_bovengren s	decimal		☐	
toerental_geluidsniveau_ondergren s	decimal		☐	
uitlaatgas_circulatie_indicator	string		☐	
uitvoering_w_ijsigingsnummer	decimal		☐	
vermogen_bovengrens	decimal		☐	
vermogen_ondergrens	decimal		☐	
voertuigbrandstof_type	string		☐	
volgnummer	decimal		☐	
w erkingsbeginssel_verbrandingsmo tor	string		☐	

4.1.21 rdw_entrances_and_exits

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/ih4v-gzm4.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/ih4v-gzm4.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/ih4v-gzm4.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/ih4v-gzm4.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_entrances_and_exits` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
alias	string		☐	
areaid	string		☐	
areamanagerid	decimal		☐	

Name	Data Type	Label	Required	Documentation
enddateentranceorexit	datetime		☐	
entranceexitid	decimal		☐	
pedestrianentrance	decimal		☐	
pedestrianexit	decimal		☐	
startdateentranceorexit	datetime		☐	
vehicleentrance	decimal		☐	
vehicleexit	decimal		☐	

4.1.22 rdw_geological_selling_points

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table rdw_geological_selling_points are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areamanagerid	decimal		☐	
enddatesellingpoint	datetime		☐	
location_adress	string		☐	
location_city	string		☐	
location_coordinates	string		☐	
location_state	string		☐	
location_type	string		☐	
location_zip	string		☐	
sellingpointdesc	string		☐	
sellingpointid	decimal		☐	
startdatesellingpoint	datetime		☐	

4.1.23 rdw_gps_coordinates

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/dkei-vb2p.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/dkei-vb2p.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/dkei-vb2p.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/dkei-vb2p.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_gps_coordinates` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
enddatelocation	datetime		☐	
latitude	decimal		☐	
locationreference	decimal		☐	
locationreferencetype	string		☐	
longitude	decimal		☐	
startdatelocation	datetime		☐	

4.1.24 rdw_indexes_static_and_dynamic: rdw.nl trade_name

Catalog: RDW

Schema: RDW

Primary Keys: id

Label: trade_name

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/f6v7-gjpa?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/f6v7-gjpa?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/f6v7-gjpa?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/f6v7-gjpa?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_indexes_static_and_dynamic` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dynamic_parking_data	string		☐	
organization_id	decimal		☐	
organization	string		☐	
standard_static_parking_data	string		☐	
static_parking_data	string		☐	

4.1.25 rdw_licensed_fuel_vehicles

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The `rdw.nl` API may not support changing the data or the Invantive SQL driver for `rdw.nl` does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the `rdw.nl` API.

Select `rdw.nl` API URL: <https://opendata.rdw.nl/resource/8ys7-d773.json?>

Insert `rdw.nl` API URL: <https://opendata.rdw.nl/resource/8ys7-d773.json?>

Update `rdw.nl` API URL: <https://opendata.rdw.nl/resource/8ys7-d773.json?>

Delete `rdw.nl` API URL: <https://opendata.rdw.nl/resource/8ys7-d773.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_licensed_fuel_vehicles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
brandstof_omschrijving	string		☐	
brandstof_volgnummer	string		☐	
brandstofverbruik_buiten	string		☐	
brandstofverbruik_gecombineerd	string		☐	
brandstofverbruik_stad	string		☐	
co2_uitstoot_gecombineerd	string		☐	
co2_uitstoot_gew_ogen	string		☐	
emissiecode_omschrijving	string		☐	
geluidsniveau_rijdend	string		☐	
geluidsniveau_stationair	string		☐	
kenteken	string		☐	

Name	Data Type	Label	Required	Documentation
milieuklasse_eg_goedkeuring_licht	string		☐	
milieuklasse_eg_goedkeuring_zwaar	string		☐	
nettomaximumvermogen	string		☐	
nominaal_continu_maximumvermogen	string		☐	
roetuitstoot	string		☐	
toerental_geluidsniveau	string		☐	
uitstoot_deeltjes_licht	string		☐	
uitstoot_deeltjes_zwaar	string		☐	

4.1.26 rdw_licensed_vehicle_chassis_specifications

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/jhie-znh9.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/jhie-znh9.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/jhie-znh9.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/jhie-znh9.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table rdw_licensed_vehicle_chassis_specifications are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
carrosserie_voertuig_nummer_code_volgnummer	string		☐	
carrosserie_voertuig_nummer_europese_omschrijving	string		☐	
carrosserie_volgnummer	string		☐	
carrosseriecode	string		☐	
kenteken	string		☐	

4.1.27 rdw_licensed_vehicles_axis

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/3huj-srit.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/3huj-srit.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/3huj-srit.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/3huj-srit.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_licensed_vehicles_axis` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
aangedreven_as	string		☐	
aantal_assen	string		☐	
as_nummer	string		☐	
hefas	string		☐	
kenteken	string		☐	
plaatscode_as	string		☐	
spoorbreedte	string		☐	
technisch_toegestane_maximum_aslast	string		☐	
weggedrag_code	string		☐	
wettelijk_toegestane_maximum_aslast	string		☐	

4.1.28 rdw_licensed_vehicles_chassis

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/vezc-m2t6.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/vezc-m2t6.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/vezc-m2t6.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/vezc-m2t6.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_licensed_vehicles_chassis` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>carrosserie_volnummer</code>	string		☐	
<code>carrosserietype</code>	string		☐	
<code>kenteken</code>	string		☐	
<code>type_carrosserie_europese_omsc hrijving</code>	string		☐	

4.1.29 `rdw_licensed_vehicles_classes`

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The `rdw.nl` API may not support changing the data or the Invariantive SQL driver for `rdw.nl` does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the `rdw.nl` API.

Select `rdw.nl` API URL: `https://opendata.rdw.nl/resource/kmfi-hrps.json?`

Insert `rdw.nl` API URL: `https://opendata.rdw.nl/resource/kmfi-hrps.json?`

Update `rdw.nl` API URL: `https://opendata.rdw.nl/resource/kmfi-hrps.json?`

Delete `rdw.nl` API URL: `https://opendata.rdw.nl/resource/kmfi-hrps.json?`

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_licensed_vehicles_classes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>carrosserie_klasse_volnummer</code>	string		☐	
<code>carrosserie_volnummer</code>	string		☐	
<code>enddateregulation</code>	datetime		☐	
<code>kenteken</code>	string		☐	
<code>maximumdaycharge</code>	string		☐	
<code>voertuigklasse omschrijving</code>	string		☐	
<code>voertuigklasse</code>	string		☐	

4.1.30 `rdw_location_pinpoint_versions`

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/swii-yk2t.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/swii-yk2t.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/swii-yk2t.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/swii-yk2t.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_location_pinpoint_versions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
eeg_uitvoeringscode	string		☐	
eeg_variantcode	string		☐	
eu_type_goedkeuringssleutel	string		☐	
plaats_aanduiding_volgnummer	decimal		☐	
plaatsaanduiding_registratie_datum	decimal		☐	
plaatscode_voeruijg_identificatie	string		☐	
uitvoering_w_ijzigingsnummer	decimal		☐	

4.1.31 rdw_open_parkings

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/9wqn-uhve.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/9wqn-uhve.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/9wqn-uhve.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/9wqn-uhve.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_open_parkings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areamanagerid	decimal		☐	
endofperiod	string		☐	
exitpossibleallday	decimal		☐	
openallyear	decimal		☐	
periodname	string		☐	
startofperiod	string		☐	

4.1.32 rdw_parking_accesses

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/3fak-cvu3.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/3fak-cvu3.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/3fak-cvu3.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/3fak-cvu3.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_accesses` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areamanagerid	decimal		☐	
days	string		☐	
endofperiod	string		☐	
enterfrom	decimal		☐	
enteruntil	decimal		☐	
startofperiod	string		☐	

4.1.33 rdw_parking_adresses

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/r7mi-cxck.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/r7mi-cxck.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/r7mi-cxck.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/r7mi-cxck.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_adresses` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
country	string		☐	
emailadress	string		☐	
faxnumber	string		☐	
houzenumber	string		☐	
parkingaddressreference	string		☐	
parkingaddressreferencetype	string		☐	
parkingadresstype	string		☐	
place	string		☐	
province	string		☐	
streetname	string		☐	
telephonenumber	string		☐	
zipcode	string		☐	

4.1.34 rdw_parking_area

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_area` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areamanagerid	string		☐	
areaname	string		☐	
uuid	string		☐	

4.1.35 rdw_parking_area_contacts

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The `rdw.nl` API may not support changing the data or the Invariantive SQL driver for `rdw.nl` does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the `rdw.nl` API.

Select `rdw.nl` API URL: <https://opendata.rdw.nl/resource/ig3u-asme.json?>

Insert `rdw.nl` API URL: <https://opendata.rdw.nl/resource/ig3u-asme.json?>

Update `rdw.nl` API URL: <https://opendata.rdw.nl/resource/ig3u-asme.json?>

Delete `rdw.nl` API URL: <https://opendata.rdw.nl/resource/ig3u-asme.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_area_contacts` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areamanagerid	string		☐	
contactpersonid	string		☐	
validityendofperiod	string		☐	
validitystartofperiod	string		☐	

4.1.36 rdw_parking_area_geometries

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariant SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_area_geometries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areageometryastext	string		☐	
areaid	string		☐	
areamanagerid	decimal		☐	
enddatearea	datetime		☐	
startdatearea	datetime		☐	

4.1.37 rdw_parking_area_managers

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invariant SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/t6n6-h9zf.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/t6n6-h9zf.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/t6n6-h9zf.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/t6n6-h9zf.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_area_managers` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areamanagerdesc	string		☐	
areamanagerid	decimal		☐	

Name	Data Type	Label	Required	Documentation
enddateareamanagerid	datetime		☐	
startdateareamanagerid	datetime		☐	
url	string		☐	

4.1.38 rdw_parking_area_regulations

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_area_regulations` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areamanagerid	decimal		☐	
enddatearearegulation	datetime		☐	
regulationid	string		☐	
startdatearearegulation	datetime		☐	

4.1.39 rdw_parking_areas

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/8u4d-s4q7.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/8u4d-s4q7.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/8u4d-s4q7.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/8u4d-s4q7.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_areas` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areadesc	string		☐	
areaid	string		☐	
areamanagerid	decimal		☐	
enddatearea	datetime		☐	
startdatearea	datetime		☐	
usageid	string		☐	

4.1.40 rdw_parking_areaspecifications

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/5jne-jcr2.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/5jne-jcr2.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/5jne-jcr2.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/5jne-jcr2.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_parking_areaspecifications` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areamanagerid	decimal		☐	
capacity	decimal		☐	
chargingpointcapacity	decimal		☐	
disabledaccess	decimal		☐	
enddatespecifications	datetime		☐	
limitedaccess	string		☐	

Name	Data Type	Label	Required	Documentation
maximumvehicleheight	decimal		☐	
startdatespecifications	datetime		☐	

4.1.41 rdw_parking_time_frames

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/pwnm-2uua.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/pwnm-2uua.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/pwnm-2uua.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/pwnm-2uua.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table rdw_parking_time_frames are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areamanagerid	decimal		☐	
claimrightpossible	string		☐	
daytimeframe	string		☐	
enddatetimeframe	datetime		☐	
endtimetimeframe	decimal		☐	
farecalculationcode	string		☐	
maxdurationright	decimal		☐	
minparkinginterruption	decimal		☐	
regulationid	string		☐	
startdatetimeframe	datetime		☐	
starttimetimeframe	decimal		☐	

4.1.42 rdw_payment_method_areas

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/a7ai-5exd.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/a7ai-5exd.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/a7ai-5exd.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/a7ai-5exd.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_payment_method_areas` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areamanagerid	decimal		☐	
enddate	datetime		☐	
paymentatexit	decimal		☐	
paymentatpaystation	decimal		☐	
paymentmethod	string		☐	
startdate	datetime		☐	

4.1.43 rdw_payment_method_selling_points

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/nk6m-ezez.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/nk6m-ezez.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/nk6m-ezez.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/nk6m-ezez.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_payment_method_selling_points` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
enddatepaymentmethod	datetime		☐	
paymentmethod	string		☐	
sellingpointnumber	decimal		☐	
startdatepaymentmethod	datetime		☐	

4.1.44 rdw_price_calculations

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/y4xb-4tzy.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/y4xb-4tzy.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/y4xb-4tzy.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/y4xb-4tzy.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_price_calculations` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areamanagerid	decimal		☐	
enddatefare	datetime		☐	
farecalculationcode	string		☐	
farecalculationdesc	string		☐	
periodnametariff	string		☐	
startdatefare	datetime		☐	
vatpercentage	decimal		☐	

4.1.45 rdw_price_parts

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_price_parts` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amountcumulative	decimal		☐	
amountfarepart	decimal		☐	
areamanagerid	string		☐	
enddatefarepart	datetime		☐	
enddurationfarepart	decimal		☐	
farecalculationcode	string		☐	
startdatefarepart	datetime		☐	
startdurationfarepart	decimal		☐	
stepsizefarepart	decimal		☐	

4.1.46 rdw_product_catalogs

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/mw5z-cuyz.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/mw5z-cuyz.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/mw5z-cuyz.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/mw5z-cuyz.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_product_catalogs` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
eenheid	string		☐	

Name	Data Type	Label	Required	Documentation
omschrijving	string		☐	
staatscourant_indeling	string		☐	
tarief	string		☐	
tariefclustering	string		☐	

4.1.47 rdw_regulations

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/gni9-a379.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_regulations` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areamanagerid	decimal		☐	
enddateregulation	datetime		☐	
maximumdaycharge	decimal		☐	
regulationdesc	string		☐	
regulationid	string		☐	
regulationtype	string		☐	
startdateregulation	datetime		☐	

4.1.48 rdw_selling_points

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/hd6i-e96e.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/hd6i-e96e.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/hd6i-e96e.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/hd6i-e96e.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_selling_points` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areaid	string		☐	
areamanagerid	decimal		☐	
enddatesellingpoint	datetime		☐	
sellingpointdesc	string		☐	
sellingpointid	decimal		☐	
sellingpointnumber	decimal		☐	
startdatesellingpoint	datetime		☐	

4.1.49 rdw_special_days

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/k3tu-wvib.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/k3tu-wvib.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/k3tu-wvib.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/k3tu-wvib.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_special_days` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
areamanagerid	decimal		☐	
datespecialday	datetime		☐	
namespecialday	string		☐	

4.1.50 rdw_subcategory_versions

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/u9r6-xz3p.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/u9r6-xz3p.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/u9r6-xz3p.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/u9r6-xz3p.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_subcategory_versions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
eeg_uitvoeringscode	string		☐	
eeg_variantcode	string		☐	
eu_type_goedkeuringssleutel	string		☐	
subcateg_uitvoering_europees	string		☐	
subcategorie_uitvoering_volgnr	decimal		☐	
uitvoering_w_izigingsnummer	decimal		☐	

4.1.51 rdw_trade_name_versions: rdw.nl trade_name

Catalog: RDW

Schema: RDW

Primary Keys: id

Label: trade_name

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/wpg6-hw5s.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/wpg6-hw5s.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/wpg6-hw5s.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/wpg6-hw5s.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_trade_name_versions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>eeg_uitvoeringscode</code>	string		☐	
<code>eeg_variantcode</code>	string		☐	
<code>eu_type_goedkeuringssleutel</code>	string		☐	
<code>handelsbenaming_fabrikant</code>	string		☐	
<code>registratiedatum_handelsbenaming</code>	decimal		☐	
<code>uitvoering_w_izigingsnummer</code>	decimal		☐	
<code>volgnummer</code>	decimal		☐	

4.1.52 `rdw_user_goals`

Catalog: RDW

Schema: RDW

Primary Keys: `id`

This is a read-only table. The `rdw.nl` API may not support changing the data or the Invariantive SQL driver for `rdw.nl` does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the `rdw.nl` API.

Select `rdw.nl` API URL: `https://opendata.rdw.nl/resource/bh3w-cud9.json?`

Insert `rdw.nl` API URL: `https://opendata.rdw.nl/resource/bh3w-cud9.json?`

Update `rdw.nl` API URL: `https://opendata.rdw.nl/resource/bh3w-cud9.json?`

Delete `rdw.nl` API URL: `https://opendata.rdw.nl/resource/bh3w-cud9.json?`

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_user_goals` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>areamanagerid</code>	decimal		☐	
<code>enddateusageid</code>	datetime		☐	
<code>specificationindicator</code>	string		☐	
<code>startdateusageid</code>	datetime		☐	
<code>superiorareamanagerid</code>	decimal		☐	
<code>superiorusageid</code>	string		☐	
<code>usageid</code>	string		☐	
<code>usageiddesc</code>	string		☐	

4.1.53 rdw_vehicles

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/m9d7-ebf2.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/m9d7-ebf2.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/m9d7-ebf2.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/m9d7-ebf2.json>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_vehicles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
brand	string		☐	
cylinder_volume_wrong	string		☐	
date_ascription	datetime		☐	
date_first_admission	datetime		☐	
date_first_issue_netherlands	datetime		☐	
distance_front_to_stick_shift	decimal		☐	
distance_stick_shift_to_back	decimal		☐	
empty_vehicle_weight	decimal		☐	
eu_approval_number_change	string		☐	
european_release_category	string		☐	
european_vehicle_category_add	string		☐	
european_vehicle_category	string		☐	
export_indicator	string		☐	
first_color	string		☐	
interior	string		☐	
kerb_weight	decimal		☐	
length	decimal		☐	
license_plate	string		☐	
location_chassis_number	string		☐	
max_weight_vehicle	decimal		☐	
number_of_cylinders_wrong	string		☐	
number_of_cylinders	decimal		☐	

Name	Data Type	Label	Required	Documentation
number_of_doors	decimal		☐	
number_of_wheels	decimal		☐	
open_recall_indication	string		☐	
power_per_kilo_curb	string		☐	
second_color	string		☐	
tax	decimal		☐	
trade_name	string		☐	
type	string		☐	
waiting_for_approval	string		☐	
wheelbase	decimal		☐	
width	decimal		☐	

4.1.54 rdw_vehicles_by_tag

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table function. The rdw.nl API may not support changing the data or the Invariant SQL driver for rdw.nl does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/m9d7-ebf2.json>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/m9d7-ebf2.json>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/m9d7-ebf2.json>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/m9d7-ebf2.json>

Field Selection Method: NotRequired

Table Function Columns

The columns of the table function `rdw_vehicles_by_tag` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
brand	string		☐	
cylinder_volume_wrong	string		☐	
date_ascription	datetime		☐	
date_first_admission	datetime		☐	
date_first_issue_netherlands	datetime		☐	
distance_front_to_stick_shift	decimal		☐	
distance_stick_shift_to_back	decimal		☐	
empty_vehicle_weight	decimal		☐	
eu_approval_number_change	string		☐	

Name	Data Type	Label	Required	Documentation
european_release_category	string		☐	
european_vehicle_category_add	string		☐	
european_vehicle_category	string		☐	
export_indicator	string		☐	
first_color	string		☐	
interior	string		☐	
kerb_weight	decimal		☐	
length	decimal		☐	
license_plate	string		☐	
location_chassis_number	string		☐	
max_weight_vehicle	decimal		☐	
number_of_cilinders_wrong	string		☐	
number_of_cilinders	decimal		☐	
number_of_doors	decimal		☐	
number_of_wheels	decimal		☐	
open_recall_indication	string		☐	
power_per_kilo_curb	string		☐	
second_color	string		☐	
tax	decimal		☐	
trade_name	string		☐	
type	string		☐	
waiting_for_approval	string		☐	
wheelbase	decimal		☐	
width	decimal		☐	

4.1.55 rdw_version_user_data_per_delivery

Catalog: RDW

Schema: RDW

Primary Keys: id

This is a read-only table. The rdw.nl API may not support changing the data or the Invantive SQL driver for rdw.nl does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the rdw.nl API.

Select rdw.nl API URL: <https://opendata.rdw.nl/resource/ug2y-499j.json?>

Insert rdw.nl API URL: <https://opendata.rdw.nl/resource/ug2y-499j.json?>

Update rdw.nl API URL: <https://opendata.rdw.nl/resource/ug2y-499j.json?>

Delete rdw.nl API URL: <https://opendata.rdw.nl/resource/ug2y-499j.json?>

Field Selection Method: NotRequired

Table Columns

The columns of the table `rdw_version_user_data_per_delivery` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>eeg_uitvoeringscode</code>	string		☐	
<code>eeg_variantcode</code>	string		☐	
<code>eu_type_goedkeuringssleutel</code>	string		☐	
<code>uitgavenummer_verbruikboek</code>	string		☐	
<code>uitvoering_w_izigingsnummer</code>	decimal		☐	
<code>verbruikcategorie_uitvoering</code>	string		☐	

Index

- _ -

_24ghz_kortbereik_radar 19

- A -

aangedreven_as 18, 38
 aant_zitpl_stilst_vrtg_bovengrens 19
 aant_zitpl_stilst_vrtg_ondergrens 19
 aantal_aangedreven_assen 19
 aantal_assen 38
 aantal_cilinders 32
 aantal_deuren_bovengrens 19
 aantal_deuren_ondergrens 19
 aantal_passagier_zittend_bovengrens 19
 aantal_passagier_zittend_ondergrens 19
 aantal_passagiers_bovengrens 19
 aantal_passagiers_ondergrens 19
 aantal_rolstoel_plaats_bovengrens 19
 aantal_rolstoel_plaats_ondergrens 19
 aantal_versnellingen_bovengrens 28
 aantal_versnellingen_ondergrens 28
 aantal_wielen 19
 aantal_zitplaatsen_bovengrens 19
 aantal_zitplaatsen_ondergrens 19
 actieradius_brandstof 30
 actieradius_brandstof_extern_oplaadbaar 30
 add-odata-mandatory-filters 2
 afst_hart_koppeling_as_bovengrens 19
 afst_hart_koppeling_as_ondergrens 19
 afstand_volgende_as_bovengrens 18
 afstand_volgende_as_ondergrens 18
 alias 34
 amountcumulative 50
 amountfarepart 50
 analysis-enforce-row-uniqueness 2
 api_bedrijf_erkenningen 15
 api_terugroep_actie_risico 24
 api_terugroep_actie_status 24
 api_terugroep_infomeren_eigenaar 24
 api_terugroep_voertuig_merk_type 24
 api-url 2
 areadesc 46
 areageometryastext 44
 areaid 16, 17, 34, 41, 42, 43, 44, 46, 47, 48, 52
 areaidvalidityextension 16, 17

areamanagerdesc 45
 areamanagerid 16, 17, 29, 34, 35, 41, 42, 43, 44, 45, 46, 47, 48, 50, 52, 53, 55
 areaname 43
 as_nummer 38
 asnummer 18

- B -

begindatum_restant_voorraad 19
 begindatum_uitvoering 19
 beschrijving_van_het_herstel 24
 BLOB_PREFERRED 13
 BOL_RESPONSE_CACHE_MAX_AGE_SEC 13
 brand 56, 57
 brandstof_omschrijving 37
 brandstof_volgnummer 30, 37
 brandstofcode 30, 32
 brandstofverbruik_buiten 37
 brandstofverbruik_buitenweg 30, 32
 brandstofverbruik_combin_rit 30, 32
 brandstofverbruik_gecombineerd 37
 brandstofverbruik_stad 37
 brandstofverbruik_stadsrit 30, 32
 breedte_voertuig_uitvoering_bovengrens 19
 breedte_voertuig_uitvoering_ondergrens 19
 bulk-delete-page-size-rows 2
 bulk-insert-page-size-bytes 2
 bulk-insert-page-size-rows 2

- C -

capacity 47
 carrosserie_klasse_europees 26
 carrosserie_klasse_volgnummer 26, 40
 carrosserie_uitvoering_numeriek_europees 26
 carrosserie_uitvoering_numeriek_volgnummer 26
 carrosserie_voertuig_nummer_code_volgnummer 38
 carrosserie_voertuig_nummer_europese_omschrijving 38
 carrosserie_volgnummer 26, 27, 38, 39, 40
 carrosseriecode 38
 carrosserietype 39
 categorie_defect 24
 chargingpointcapacity 47
 cilinder_volume_wrong 56, 57
 cilinderinhoud_cm3 32
 claimrightpossible 48
 cng_systeem 32
 co2_uitstoot_gecombineerd 37
 co2_uitstoot_gewogen 37

code_mogelijk_gevaar 23
 code_status 23
 code_status_intrekking_uitvoering 19
 code_wijze_informereren 25
 compleet_voertuig_indicator 19
 contactpersonid 28, 44
 CONTENT_TYPE 13
 country 42

- D -

date_ascription 56, 57
 DATE_ENDED 13
 date_first_admission 56, 57
 date_first_issue_netherlands 56, 57
 DATE_STARTED 13
 datespecialday 53
 datum_status_wijziging 19
 days 42

daytimeframe 48
 disabledaccess 47
 distance_front_to_stick_shift 56, 57
 distance_stick_shift_to_back 56, 57
 download-error-400-bad-request-max-tries 2
 download-error-400-bad-request-sleep-initial-ms 2
 download-error-400-bad-request-sleep-max-ms 2
 download-error-400-bad-request-sleep-multiplicator 2
 download-error-408-request-timeout-max-tries 2
 download-error-408-request-timeout-sleep-initial-ms 2
 download-error-408-request-timeout-sleep-max-ms 2
 download-error-408-request-timeout-sleep-multiplicator 2
 download-error-422-bad-request-max-tries 2
 download-error-422-bad-request-sleep-initial-ms 2
 download-error-422-bad-request-sleep-max-ms 2
 download-error-422-bad-request-sleep-multiplicator 2
 download-error-429-too-many-requests-max-tries 2
 download-error-429-too-many-requests-sleep-initial-ms 2
 download-error-429-too-many-requests-sleep-max-ms 2
 download-error-429-too-many-requests-sleep-multiplicator 2
 download-error-502-server-unavailable-max-tries 2
 download-error-502-server-unavailable-sleep-initial-ms 2
 download-error-502-server-unavailable-sleep-max-ms 2

download-error-502-server-unavailable-sleep-multiplicator 2
 download-error-503-server-unavailable-max-tries 2
 download-error-503-server-unavailable-sleep-initial-ms 2
 download-error-503-server-unavailable-sleep-max-ms 2
 download-error-503-server-unavailable-sleep-multiplicator 2
 download-error-504-gateway-timeout-max-tries 2
 download-error-504-gateway-timeout-sleep-initial-ms 2
 download-error-504-gateway-timeout-sleep-max-ms 2
 download-error-504-gateway-timeout-sleep-multiplicator 2
 download-error-590-network-connect-timeout-max-tries 2
 download-error-590-network-connect-timeout-sleep-initial-ms 2
 download-error-590-network-connect-timeout-sleep-max-ms 2
 download-error-590-network-connect-timeout-sleep-multiplicator 2
 download-error-599-network-connect-timeout-max-tries 2
 download-error-599-network-connect-timeout-sleep-initial-ms 2
 download-error-599-network-connect-timeout-sleep-max-ms 2
 download-error-599-network-connect-timeout-sleep-multiplicator 2
 download-error-argument-exception-max-tries 2
 download-error-argument-exception-sleep-initial-ms 2
 download-error-argument-exception-sleep-max-ms 2
 download-error-argument-exception-sleep-multiplicator 2
 download-error-internet-down-max-tries 2
 download-error-internet-down-sleep-initial-ms 2
 download-error-internet-down-sleep-max-ms 2
 download-error-internet-down-sleep-multiplicator 2
 download-error-io-exception-max-tries 2
 download-error-io-exception-sleep-initial-ms 2
 download-error-io-exception-sleep-max-ms 2
 download-error-io-exception-sleep-multiplicator 2
 download-error-json-exception-max-tries 2
 download-error-json-exception-sleep-initial-ms 2
 download-error-json-exception-sleep-max-ms 2
 download-error-json-exception-sleep-multiplicator 2
 download-error-other-exception-max-tries 2
 download-error-other-exception-sleep-initial-ms 2
 download-error-other-exception-sleep-max-ms 2

download-error-other-exception-sleep-multiplicator	2	emissie_co_volgens_whsc	30
download-error-socket-exception-max-tries	2	emissie_co_volgens_whtc	30
download-error-socket-exception-sleep-initial-ms	2	emissie_co2_buitenweg	30, 32
download-error-socket-exception-sleep-max-ms	2	emissie_co2_combinatie	30, 32
download-error-socket-exception-sleep-multiplicator	2	emissie_co2_gecombineerd	30
download-error-web-exception-max-tries	2	emissie_co2_stadsrit	30, 32
download-error-web-exception-sleep-initial-ms	2	emissie_deeltjes_aantal_whsc	30
download-error-web-exception-sleep-max-ms	2	emissie_deeltjes_aantal_whtc	30
download-error-web-exception-sleep-multiplicator	2	emissie_deeltjes_massa_whsc	30
download-error-web-not-implemented-max-tries	2	emissie_deeltjes_massa_whtc	30
download-error-web-not-implemented-sleep-initial-ms	2	emissie_hc_bij_koude_start	30, 32
download-error-web-not-implemented-sleep-max-ms	2	emissie_hc_en_nox	32
download-error-web-not-implemented-sleep-multiplicator	2	emissie_hc_en_nox_type1	30
download-error-web-timeout-max-tries	2	emissie_koolmonoxide_esc_test	30
download-error-web-timeout-sleep-initial-ms	2	emissie_koolmonoxide	32
download-error-web-timeout-sleep-max-ms	2	emissie_koolmonoxide_esc_test	30
download-error-web-timeout-sleep-multiplicator	2	emissie_koolmonoxide_type_1	30
download-error-web-unauthorized-max-tries	2	emissie_koolwaterstof	32
download-error-web-unauthorized-sleep-initial-ms	2	emissie_koolwaterstof_type_1	30
download-error-web-unauthorized-sleep-max-ms	2	emissie_koolwaterstoffen_esc_test	30
download-error-web-unauthorized-sleep-multiplicator	2	emissie_koolwaterstoffen_etc_test	30
Driver	1	emissie_methaan_etc_test	30
DRY_RUN	13	emissie_nh3_volgens_whsc	30
dubbele_montage	18	emissie_nh3_volgens_whtc	30
DURATION_MS	13	emissie_nmhc_volgens_whsc	30
dynamic_parking_data	36	emissie_nmhc_volgens_whtc	30
		emissie_non_methaan_koolw_etc_test	30
		emissie_nox_volgens_whsc	30
		emissie_nox_volgens_whtc	30
		emissie_stikstofoxide	32
		emissie_stikstofoxide_type_1	30
		emissie_stikstofoxiden_esc_test	30
		emissie_stikstofoxiden_etc_test	30
		emissie_thc_volgens_whsc	30
		emissie_thc_volgens_whtc	30
		emissie_vaste_stofdeeltjes	30, 32
		emissie_vaste_stofdeeltjes_esc_test	30
		emissie_vaste_stofdeeltjes_etc_test	30
		emissiecode	30, 32
		emissiecode omschrijving	37
		empty_vehicle_weight	56, 57
		enddate	48
		enddatearea	44, 46
		enddateareamanagerid	45
		enddatearearegulation	46
		enddateentranceorexit	34
		enddatefare	50
		enddatefarepart	50
		enddatelocation	36
		enddatepaymentmethod	49
		enddateregulation	40, 52
eeg_uitvoering_cat_toevoeging	19		
eeg_uitvoeringscode	18, 19, 22, 26, 27, 28, 30, 32, 40, 54, 58		
eeg_variantcode	18, 19, 22, 26, 27, 28, 30, 32, 40, 54, 58		
eenheid	51		
eindatum_restant_voorraad	19		
einddatum_uitvoering	19		
electromotor_af_fabriek_indicator	32		
elektrisch_verbruik_combinatie	30		
elektrisch_verbruik_gecomb	30		
emailadress	28, 42		
emissie_aant_deeltjes_esc_test	30		
emissie_aant_deeltjes_etc_test	30		
emissie_aant_deeltjes_t1_test	30		
emissie_ch4_volgens_whsc	30		
emissie_ch4_volgens_whtc	30		
emissie_co_bij_koude_start	30, 32		

- E -

enddatesellingpoint 35, 52
 enddatespecifications 47
 enddatetimeframe 48
 enddateusageid 55
 enddaytimeframevalidityrestriction 17
 enddurationfarepart 50
 enddurationvalidityrestriction 17
 endofperiod 41, 42
 endtimetimeframe 48
 endvalidityextension 16
 enkel_electrische_indicator 32
 enterfrom 42
 enteruntil 42
 entranceexitid 34
 erkenning 16
 ERROR_MESSAGE_CODE 13
 ERROR_MESSAGE_TEXT 13
 eu_approval_number_change 56, 57
 eu_type_goedkeuringssleutel 18, 19, 22, 26, 27, 28, 30, 32, 40, 54, 58
 eur_codering_carrosserietype 19
 european_release_category 56, 57
 european_vehicle_category 56, 57
 european_vehicle_category_add 56, 57
 exitpossibleallday 41
 export_indicator 56, 57
 extern_oplaadbaar 32

- F -

FAIL_ON_ERROR 13
 farecalculationcode 48, 50
 farecalculationdesc 50
 faxnumber 28, 42
 first_color 56, 57
 firstname 28
 force-case-sensitive-identifiers 2
 forced-casing-identifiers 2

- G -

gelijkwaardig_aan_luchtvering 18
 geluidsniveau_bovengrens 30, 32
 geluidsniveau_ondergrens 30, 32
 geluidsniveau_rijdend 30, 32, 37
 geluidsniveau_stationair 37
 gestuurde_as_indicator 18
 gevelnaam 15

- H -

handelsbenaming 19
 handelsbenaming_fabrikant 54
 hefas 18, 38
 hoogte_voertuig_uitvoering_bovengrens 19
 hoogte_voertuig_uitvoering_ondergrens 19
 housenumber 42
 HTTP_DISK_CACHE_MAX_AGE_SEC 13
 HTTP_DISK_CACHE_SAVE 13
 HTTP_DISK_CACHE_USE 13
 HTTP_MEMORY_CACHE_MAX_AGE_SEC 13
 HTTP_MEMORY_CACHE_SAVE 13
 HTTP_MEMORY_CACHE_USE 13
 HTTP_METHOD 13
 HTTP_STATUS_CODE 13
 http-disk-cache-compression-level 2
 http-disk-cache-directory 2
 http-disk-cache-ignore-write-errors 2
 http-disk-cache-max-age-sec 2
 http-get-timeout-ms 2
 http-memory-cache-compression-level 2
 http-memory-cache-max-age-sec 2
 http-post-timeout-ms 2
 huisnummer 15
 huisnummer_toevoeging 15
 hybride_elektrisch_voertuig 32

- I -

ignore-http-400-errors 2
 ignore-http-401-errors 2
 ignore-http-402-errors 2
 ignore-http-403-errors 2
 ignore-http-404-errors 2
 ignore-http-422-errors 2
 ignore-http-429-errors 2
 ignore-http-500-errors 2
 ignore-http-502-errors 2
 ignore-http-503-errors 2
 indexnumbervalidityrestriction 17
 inhoud_brandstoftank 19
 inrichtingscode 19
 interior 56, 57
 intrekdatum_uitvoering 19
 invalid-json-on-get-max-tries 2
 invalid-json-on-get-sleep-initial-ms 2
 invalid-json-on-get-sleep-max-ms 2
 invalid-json-on-get-sleep-multiplicator 2

invalid-json-on-post-max-tries 2
 invalid-json-on-post-sleep-initial-ms 2
 invalid-json-on-post-sleep-max-ms 2
 invalid-json-on-post-sleep-multiplicator 2
 invantive-sql-compress-sparse-arrays 2
 invantive-sql-correct-invalid-date 2
 invantive-sql-forward-filters-to-data-containers 2
 invantive-sql-share-byte-arrays 2
 invantive-sql-share-strings 2
 invantive-sql-shuffle-fetch-results-data-containers
 invantive-use-cache 2

- J -

join-set-points-per-request 2

- K -

kant_van_het_stuur 19
 katalysator_indicator 32
 kenteken 23, 37, 38, 39, 40
 kerb_weight 56, 57

- L -

latitude 36
 lengte_laadruimte_bovengrens 19
 lengte_laadruimte_ondergrens 19
 lengte_voertuig_uitvoering_bovengrens 19
 lengte_voertuig_uitvoering_ondergrens 19
 length 56, 57
 license_plate 56, 57
 limitedaccess 47
 limit-partition-calls-left 2
 links_rechts_rijdend 19
 location_adress 35
 location_chassis_number 56, 57
 location_city 35
 location_coordinates 29, 35
 location_state 35
 location_type 29, 35
 location_zip 35
 locationreference 36
 locationreferencetype 36
 log-native-calls-to-disk-max-events 2
 log-native-calls-to-disk-max-seconds 2
 log-native-calls-to-disk-on-error 2
 log-native-calls-to-disk-on-success 2
 log-native-calls-to-trace 2
 longitude 36

lpg_systeem 32
 lucht_injectie_indicator 30, 32
 luchtvering 18

- M -

massa_bedrijfsklaar_toestand_bovengrens 19
 massa_bedrijfsklaar_toestand_ondergrens 19
 massa_leeg_voertuig_bovengrens 19
 massa_leeg_voertuig_ondergrens 19
 materi_le_gevolgen 24
 max_breedte_voertuig_bovengrens 19
 max_breedte_voertuig_ondergrens 19
 max_constructie_snelheid_bovengrens 19
 max_constructie_snelheid_ondergrens 19
 max_lengte_voertuig_bovengrens 19
 max_lengte_voertuig_ondergrens 19
 max_massa_gereemd_bovengrens 19
 max_massa_gereemd_ondergrens 19
 max_massa_ongeremd_bovengrens 19
 max_massa_ongeremd_ondergrens 19
 max_massa_samenstel_bovengrens 19
 max_massa_samenstel_ondergrens 19
 max_massa_voertuig_bovengrens 19
 max_massa_voertuig_ondergrens 19
 max_massa_vrtg_techn_bovengrens 19
 max_massa_vrtg_techn_ondergrens 19
 max_ondersteunde_snelheid 19
 max_ondersteuning_snelheid_bovengrens 19
 max_ondersteuning_snelheid_ondergrens 19
 max_vermogen_continu_bovengrens 30, 32
 max_vermogen_continu_ondergrens 30, 32
 max_weight_vehicle 56, 57
 maxdurationright 48
 maximale_biobrandstof_percentage 30
 maximumdaycharge 40, 52
 maximum-length-identifiers 2
 maximumvehicleheight 47
 max-odata-filters 2
 max-url-length-accepted 2
 max-url-length-desired 2
 meer_informatie_op_internet 24
 meer_informatie_via_telefoonnummer 24
 meldende_producent_distributeur 24
 merk 25
 merk_registratie_datum 22
 merkcode 22
 metadata-cache-max-age-sec 2
 milieuklasse_eg_goedkeuring_licht 37
 milieuklasse_eg_goedkeuring_zwaar 37
 min_massa_voertuig 19

minparkinginterruption 48
mogelijk_gevaar 23
motor_registratiedatum 32
motorcode 32

- N -

naam_bedrijf 15
name 28
namespecialday 53
NATIVEPLATFORMSCALARREQUESTS 13
netto_max_vermogen_bovengrens 30
netto_max_vermogen_ondergrens 30
nettomaximumvermogen 37
nominaal_continu_maximumvermogen 37
npt 13
number_of_cilinders 56, 57
number_of_cilinders_wrong 56, 57
number_of_doors 56, 57
number_of_wheels 56, 57

- O -

oauth-unauthorized-max-tries 2
oauth-unauthorized-sleep-initial-ms 2
oauth-unauthorized-sleep-max-ms 2
oauth-unauthorized-sleep-multiplicator 2
omschrijving 51
omschrijving_defect 24
open_recall_indication 56, 57
openallyear 41
opmerkingen_rdw 24
organization 36
organization_id 36
ORIG_SYSTEM_GROUP 13
ORIG_SYSTEM_REFERENCE 13

- P -

parkingaddressreference 42
parkingaddressreferencetype 42
parkingaddresstype 42
partition-slot-based-rate-limit-length-ms 2
partition-slot-based-rate-limit-slots 2
PAYLOAD_TEXT 13
paymentatexit 48
paymentatpaystation 48
paymentmethod 48, 49
pedestrianentrance 34
pedestrianexit 34

periodname 41
periodnametariff 50
phonenummer 28
plaats 15
plaats_aanduiding_volgnummer 40
plaats_as_code 18
plaatsaanduiding_registratie_datum 40
plaatscode_as 38
plaatscode_voeruid_identificatie 40
place 42
position 28
postcode_alfanumeriek 15
postcode_numeriek 15
power_per_kilo_curb 56, 57
pre-request-delay-ms 2
province 42
publicatiedatum_rdw 24

- R -

rdw.nl 1, 13, 15, 16, 17, 18, 19, 22, 23, 24, 25, 26, 27, 28, 29, 30, 32, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58
rdw_acknowledged_companies 15
rdw_acknowledgments 16
rdw_availability_expansions 16
rdw_availability_restrictions 17
rdw_axis_data_eeg_versions 18
rdw_basic_data_eeg_versions 19
rdw_brand_version_allowed 22
rdw_callback_action_risks 23
rdw_callback_action_statuses 23
rdw_callback_actions 24
rdw_callback_inform_owners 25
rdw_callback_vehicles_brand_types 25
rdw_chassis_version_classes 26
rdw_chassis_version_numeric_codes 26
rdw_chassis_versions 27
rdw_clutch_versions 28
rdw_contacts 28
rdw_eeg_vehicle_acceptances 29
rdw_engine_fuel_versions 30
rdw_engine_versions 32
rdw_entrances_and_exits 34
rdw_geological_selling_points 35
rdw_gps_coordinates 36
rdw_indexes_static_and_dynamic 36
rdw_licensed_fuel_vehicles 37
rdw_licensed_vehicle_chassis_specifications 38
rdw_licensed_vehicles_axis 38

rdw_licensed_vehicles_chassis	39	sellingpointdesc	29, 35, 52
rdw_licensed_vehicles_classes	40	sellingpointid	29, 35, 52
rdw_location_pinpoint_versions	40	sellingpointnumber	49, 52
rdw_open_parkings	41	simulate-http-400-errors	2
rdw_parking_accesses	42	simulate-http-400-errors-percentage	2
rdw_parking_adresses	42	simulate-http-401-errors	2
rdw_parking_area	43	simulate-http-401-errors-percentage	2
rdw_parking_area_contacts	44	simulate-http-403-errors	2
rdw_parking_area_geometries	44	simulate-http-403-errors-percentage	2
rdw_parking_area_managers	45	simulate-http-408-errors	2
rdw_parking_area_regulationsn	46	simulate-http-408-errors-percentage	2
rdw_parking_areas	46	simulate-http-429-errors	2
rdw_parking_areaspecifications	47	simulate-http-429-errors-percentage	2
rdw_parking_time_frames	48	simulate-http-500-errors	2
rdw_payment_method_areas	48	simulate-http-500-errors-percentage	2
rdw_payment_method_selling_points	49	simulate-http-502-errors	2
rdw_price_calculations	50	simulate-http-502-errors-percentage	2
rdw_price_parts	50	simulate-http-503-errors	2
rdw_product_catalogs	51	simulate-http-503-errors-percentage	2
rdw_regulations	52	simulate-http-protocol-errors	2
rdw_selling_points	52	simulate-http-protocol-errors-percentage	2
rdw_special_days	53	simulate-http-timeout-errors	2
rdw_subcategory_versions	54	simulate-http-timeout-errors-percentage	2
rdw_trade_name_versions	54	slot-based-rate-limit-length-ms	2
rdw_user_goals	55	slot-based-rate-limit-slots	2
rdw_vehicles	56	snelheidssymbool_ongeregt	18
rdw_vehicles_by_tag	57	soort_inspuiting_motor	30, 32
rdw_version_user_data_per_delivery	58	specificationindicator	55
RdwNI	1	spoorbreedte	38
referentiecode_producent	24	spoorbreedte_bovengrens	18
referentiecode_rdw	23, 24, 25	spoorbreedte_ongeregt	18
registratiedatum_handelsbenaming	54	staatscourant_indeling	51
regulationdesc	52	standard_static_parking_data	36
regulationid	46, 48, 52	standardize-identifiers	2
regulationtype	52	standardize-identifiers-casing	2
requested-page-size	2	startdate	48
requests-parallel-max	2	startdatearea	44, 46
RESULT_BLOB	13	startdateareamanagerid	45
RESULT_DATE_TIME_UTC	13	startdatearearegulation	46
RESULT_NUMBER	13	startdateentranceorexit	34
RESULT_TEXT	13	startdatefare	50
roet_uitstoot	32	startdatefarepart	50
roet_uitstoot_acc	30	startdatelocation	36
roetuitstoot	37	startdatepaymentmethod	49
rolstraat_bovengrens	18	startdateregulation	52
rolstraat_ongeregt	18	startdatesellingpoint	29, 35, 52
rookwaarde_elr_test	30	startdatespecifications	47
		startdatetimeframe	48
		startdateusageid	55
		startdaytimeframevalidityrestriction	17
		startdurationfarepart	50

- S -

second_color 56, 57

startdurationvalidityrestriction 17
 startofperiod 41, 42
 starttimeframe 48
 startvalidityextension 16, 17
 static_parking_data 36
 station_toerental_bovengrens_acc 30
 station_toerental_ondergrens_acc 30
 stationair_toerental_bovengr 32
 stationair_toerental_ondergr 32
 status 23
 status_voertuig_kentekening 19
 stepsizefarepart 50
 straat 15
 streetname 42
 subcateg_uitvoering_europees 54
 subcategorie_uitvoering_volgnr 54
 SUCCESSFUL 13
 superiorareamanagerid 55
 superiorusageid 55

- T -

tarief 51
 tariefclustering 51
 tax 56, 57
 techn_max_last_as_bovengrens 18
 techn_max_last_as_ondergrens 18
 techn_max_last_asstel_bovengr 18
 techn_max_last_asstel_ondergr 18
 techn_max_last_koppelpunt_bovengrens 19
 techn_max_last_koppelpunt_ondergrens 19
 techn_max_massa_autonoom_bovengrens 19
 techn_max_massa_autonoom_ondergrens 19
 techn_max_massa_middenas_bovengrens 19
 techn_max_massa_middenas_ondergrens 19
 techn_max_massa_oplegger_bovengrens 19
 techn_max_massa_oplegger_ondergrens 19
 techn_max_massa_samenst_bovengrens 19
 techn_max_massa_samenst_ondergrens 19
 technisch_toegestane_maximum_aslast 38
 telephonenumber 42
 TIMEOUT_SEC 13
 toerental_geluidsniveau 37
 toerental_geluidsniveau_bovengrens 32
 toerental_geluidsniveau_ondergrens 32
 toerental_max_vermogen_bovengrens 30
 toerental_max_vermogen_ondergrens 30
 trade_name 36, 54, 56, 57
 TRANSACTION_ID 13
 tweede_brandstofcode_voertuig 19
 type 25, 56, 57

type_carrosserie_europees 27
 type_carrosserie_europese_omschrijving 39
 type_versnellingsbak 28

- U -

uitlaatgas_circulatie_indicator 30, 32
 uitstoot_deeltjes_licht 37
 uitstoot_deeltjes_zwaar 37
 uitgavenummer_verbruikboek 58
 uitvoering_registratie_datum 19
 uitvoering_wijzigingsnummer 18, 19, 22, 26, 27, 28, 30, 32, 40, 54, 58
 url 13, 45
 usageid 16, 17, 46, 55
 usageiddesc 55
 use-batch-insert 2
 use-http-disk-cache-read 2
 use-http-disk-cache-write 2
 use-http-memory-cache-read 2
 use-http-memory-cache-write 2
 uuid 43

- V -

validityendofperiod 44
 validityextensiontype 16
 validitystartofperiod 44
 variant_status 19
 vatpercentage 50
 vehicleentrance 34
 vehicleexit 34
 verbruik_gecombineerd 30
 verbruikcategorie_uitvoering 58
 vermogen_bovengrens 30, 32
 vermogen_ondergrens 30, 32
 voertuigbrandstof_type 32
 voertuigklasse 40
 voertuigklasse_omschrijving 40
 volgnummer 15, 16, 28, 30, 32, 54

- W -

waiting_for_approval 56, 57
 weggedrag_code 38
 werkingsbeginsel_verbrandingsmotor 32
 wettelijk_toegestane_maximum_aslast 38
 wheelbase 56, 57
 width 56, 57
 wielbasis_bovengrens 19

wielbasis_ondergrens 19

wijze_waarop_u_wordt_ge_nformeerd 25

- Z -

zelfdragende_carrosserie 19

zipcode 42



invantive ***the SQL company***

Invantive B.V.
Biesteweg 11
3849 RD Hierden
Nederland

Tel: +31 88 00 26 500
Fax: +31 84 22 58 178
info@invantive.nl
invantive.nl

IBAN NL25 BUNQ 2098 2586 07
Kamer van Koophandel 13031406
BTW NL812602377B01
RSIN 8122602377
Algemeen Directeur: Guido Leenders
Statutaire zetel: Roermond