

YouTrack API Data Model

for use with Invantive SQL

23.0

Copyright

(C) Copyright 2004-2023 Invantive Software B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

Important Safety and Usage Information

Intended Use and Limitations: This software, developed by Invantive, is designed to support a variety of business and information technology data processing functions, such as accounting, financial reporting and sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- **Nuclear facilities:** The software should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.
- **Defense and Military Applications:** This software is not suitable for use in defense-related applications, including but not limited to weaponry control, military strategy planning, or any other aspects of national defense.
- **Aviation:** The software is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.
- **Healthcare and Medicine Production:** This software should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.
- **Chemical and Hazardous Material Handling:** This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.
- **Transportation and Traffic Control Systems:** The software should not be used for the control, operation, or management of transportation systems, including railway signal controls, subway systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.
- **Energy Grid and Utility Control Systems:** This software is not designed for the control or operation of energy grid systems, including electrical substations, renewable energy control systems, or water utility control systems. The failure of software in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.
- **Other High-Risk Environments:** Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

User Responsibility: Users must ensure that they understand the intended use of the software and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the software for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment.

Disclaimer of Liability: Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this software in prohibited or unintended applications.

Contents

1	SQL Driver for YouTrack API	1
2	SQL Driver Attributes for YouTrack API	2
3	Schema: Activities	15
3.1	Tables	15
3.1.1	Activities: YouTrack Activities	15
3.1.2	ActivityById	17
3.1.3	ActivityPages	18
3.1.4	ProjectActivityPages	20
4	Schema: Admin	22
4.1	Tables	22
4.1.1	AllowedOriginRestSettings	22
4.1.2	AppearanceSettings	23
4.1.3	GlobalSettings	24
4.1.4	IssueAttachments	26
4.1.5	IssueComments	30
4.1.6	IssueCustomFields	34
4.1.7	IssueLinks	38
4.1.8	Issues	41
4.1.9	IssueTags: YouTrack Issue Tags	45
4.1.10	Licenses	49
4.1.11	LocaleSettings	50
4.1.12	NotificationSettings	50
4.1.13	RestSettings	51
4.1.14	SystemSettings	52
4.1.15	Telemetry	53
4.1.16	TimeTrackingSettings	54
4.1.17	TimeTrackingSettingWorkItemTypes	55
4.1.18	TimeTrackingSettingWorkItemTypesByWorkItemTypeId	55
4.1.19	TimeTrackingWorkTimeSettings	56
4.1.20	WorkItemTypeTimeTrackingSettings	57
5	Schema: Agile	58
5.1	Tables	58
5.1.1	ProjectBySprintId	58
5.1.2	ProjectIssues	65
5.1.3	ProjectIssuesBySprintId	72
5.1.4	Projects	79
5.1.5	SprintById	85
5.1.6	SprintById1	91
5.1.7	SprintById2	97
5.1.8	SprintIssueAttachmentsBySprintId	101
5.1.9	SprintIssueCommentsBySprintId	108
5.1.10	SprintIssueCustomFieldsBySprintId	114
5.1.11	SprintIssueLinksBySprintId	120
5.1.12	SprintIssues	126
5.1.13	SprintIssuesBySprintId	133
5.1.14	SprintIssuesBySprintId1	140
5.1.15	SprintIssueTagsBySprintId	146

5.1.16	Sprints	152
5.1.17	Sprints1	157

6 Schema: Articles 163

6.1	Tables	163
6.1.1	ArticleById	163
6.1.2	Articles: YouTrack Articles	168
6.1.3	AttachmentById	172
6.1.4	Attachments	179
6.1.5	ChildArticleAttachments	185
6.1.6	ChildArticleAttachmentsById	192
6.1.7	ChildArticleComments	200
6.1.8	ChildArticleCommentsById	206
6.1.9	ChildArticles	213
6.1.10	ChildArticlesById	219
6.1.11	ChildChildArticles	226
6.1.12	ChildChildArticlesById	232
6.1.13	CommentAttachments	239
6.1.14	CommentAttachmentsByIssueId	245
6.1.15	Comments	251
6.1.16	CommentsByIssueId	256
6.1.17	GroupById	262
6.1.18	Groups	264
6.1.19	IssueLinkTypes	266
6.1.20	IssueLinkTypesById	266
6.1.21	IssueTagAttachmentIssuesByTagId	268
6.1.22	IssueTagById	273
6.1.23	IssueTagById2	275
6.1.24	IssueTagCommentAttachmentIssuesByTagId	280
6.1.25	IssueTagCommentIssuesByTagId	285
6.1.26	IssueTagCustomFieldIssuesByTagId	290
6.1.27	IssueTagIssueAttachments	295
6.1.28	IssueTagIssueAttachmentsById	299
6.1.29	IssueTagIssueById	304
6.1.30	IssueTagIssueComments	308
6.1.31	IssueTagIssueCommentsById	312
6.1.32	IssueTagIssueCustomFields	316
6.1.33	IssueTagIssueLinks	320
6.1.34	IssueTagIssueLinksById	324
6.1.35	IssueTagIssues	328
6.1.36	IssueTagIssuesCustomFieldsById	332
6.1.37	IssueTagIssuesTags	336
6.1.38	IssueTagIssueTagsById	340
6.1.39	IssueTagLinkIssuesByTagId	345
6.1.40	IssueTagLinkIssuesByTagId1	349
6.1.41	IssueTagLinkTrimmedIssuesByTagId	355
6.1.42	IssueTags: YouTrack Issue Tags	361
6.1.43	TagIssuesByTagId	363
6.1.44	TagIssuesByTagId2	368

7 Schema: Backups 374

7.1	Tables	374
7.1.1	DatabaseBackupById	374
7.1.2	DatabaseBackups	375
7.1.3	DatabaseBackupSettingBackupStatuses	376
7.1.4	DatabaseBackupSettings	377
7.1.5	NotifiedUserSavedQuerySettings	378
7.1.6	NotifiedUserSettings	379

7.1.7	NotifiedUserTagSettings	380
8	Schema: CustomFields	382
8.1	Tables	382
8.1.1	CustomFieldAggregatedUserSavedQueriesByUserBundleId	382
8.1.2	CustomFieldAggregatedUsersByUserBundleId	383
8.1.3	CustomFieldAggregatedUserTagsByUserBundleId	384
8.1.4	CustomFieldBuildBundles	386
8.1.5	CustomFieldBuildByBuildBundleId	386
8.1.6	CustomFieldBuildByBuildBundleIdAndElementId	387
8.1.7	CustomFieldBuildValues	389
8.1.8	CustomFieldBuildValuesByBuildBundleId	390
8.1.9	CustomFieldBuildValuesByBuildBundleId1	392
8.1.10	CustomFieldEnumBundleByEnumFieldBundleId	393
8.1.11	CustomFieldEnumBundles	394
8.1.12	CustomFieldEnumBundleValuesByEnumFieldBundleId	395
8.1.13	CustomFieldEnumByEnumFieldBundleId	396
8.1.14	CustomFieldEnumByEnumFieldBundleIdAndElementId	398
8.1.15	CustomFieldEnumValues	399
8.1.16	CustomFieldIndividualUsers	400
8.1.17	CustomFieldIndividualUserSavedQueries	401
8.1.18	CustomFieldIndividualUserSavedQueriesByUserBundleId	402
8.1.19	CustomFieldIndividualUsersByUserBundleId	404
8.1.20	CustomFieldIndividualUserTags	405
8.1.21	CustomFieldIndividualUserTagsByUserBundleId	406
8.1.22	CustomFieldInstancesByCustomFieldPrototypeId	408
8.1.23	CustomFieldOwnedFieldByOwnedFieldBundleId	410
8.1.24	CustomFieldOwnedFieldByOwnedFieldBundleIdAndElementId	411
8.1.25	CustomFieldOwnedFieldByValueId	413
8.1.26	CustomFieldOwnedFields	414
8.1.27	CustomFieldOwnedFieldValues	415
8.1.28	CustomFieldOwnedFieldValuesByOwnedFieldBundleId	416
8.1.29	CustomFields	418
8.1.30	CustomFieldsByCustomFieldPrototypeId	420
8.1.31	CustomFieldsByCustomFieldPrototypeId2	421
8.1.32	CustomFieldsByCustomFieldPrototypeId3	423
8.1.33	CustomFieldStateBundleById	426
8.1.34	CustomFieldStateBundles	427
8.1.35	CustomFieldStateBundleValues2ByStateBundleId	427
8.1.36	CustomFieldStateBundleValuesByStateBundleId	429
8.1.37	CustomFieldStateByStateBundleIdAndElementId	430
8.1.38	CustomFieldStateValues	432
8.1.39	CustomFieldUserBundles	433
8.1.40	CustomFieldUserBundleUsers	434
8.1.41	CustomFieldUserBundleUserSavedQueries	435
8.1.42	CustomFieldUserBundleUserTags	436
8.1.43	CustomFieldUserByUserBundleId	437
8.1.44	CustomFieldUserByUserBundleId1	438
8.1.45	CustomFieldUserByUserBundleId2	441
8.1.46	CustomFieldUserGroupsByUserBundleId	444
8.1.47	CustomFieldUserGroupsByUserBundleId1	445
8.1.48	CustomFieldUsers	448
8.1.49	CustomFieldUsersByUserBundleId	448
8.1.50	CustomFieldUsersByUserBundleId1	451
8.1.51	CustomFieldUsersByUserBundleId2	454
8.1.52	CustomFieldUsersByUserBundleId3	457
8.1.53	CustomFieldUsersByUserBundleId4	459
8.1.54	CustomFieldUsersByUserBundleId5	461

8.1.55	CustomFieldUsersByUserBundleId6	464
8.1.56	CustomFieldUsersByUserBundleId7	466
8.1.57	CustomFieldUsersByUserBundleId8	470
8.1.58	CustomFieldUsersByUserBundleId9	472
8.1.59	CustomFieldUsersByUserBundleIdAndGroupId	474
8.1.60	CustomFieldUsersByUserId	477
8.1.61	CustomFieldUserTagsByUserBundleId	479
8.1.62	CustomFieldUserTagsByUserBundleId2	482
8.1.63	CustomFieldVersionByProjectVersionBundleId	485
8.1.64	CustomFieldVersions	486
8.1.65	CustomFieldVersionValues	486
8.1.66	CustomFieldVersionValuesByProjectVersionBundleId	488
8.1.67	CustomFieldVersionValuesByProjectVersionBundleId2	489
8.1.68	CustomFieldVersionValuesByProjectVersionBundleId3	491
8.1.69	InstanceCustomFields	492
8.1.70	Types	494

9 Schema: Issues 495

9.1	Tables	495
9.1.1	AttachmentById	495
9.1.2	Attachments	500
9.1.3	CommentAttachments	506
9.1.4	CommentAttachmentsByIssueId	512
9.1.5	Comments	517
9.1.6	CommentsByIssueId	523
9.1.7	CustomFields	528
9.1.8	CustomFieldsByIssueId	533
9.1.9	IssueById	537
9.1.10	IssueLinksByIssueId	541
9.1.11	Issues	543
9.1.12	IssueTags: YouTrack Issue Tags	547
9.1.13	LinkById	554
9.1.14	LinkIssues	558
9.1.15	LinkIssuesByIssueId	565
9.1.16	Links	571
9.1.17	LinkTrimmedIssues	576
9.1.18	LinkTrimmedIssuesByIssueId	581
9.1.19	TagById	587
9.1.20	TagIssuesByTagId	592
9.1.21	Tags	599

10 Schema: Native 604

10.1	Tables	604
10.1.1	NATIVEPLATFORMSCALARREQUESTS: YouTrack Native Platform Scalar Requests	604

11 Schema: SavedQueries 606

11.1	Tables	606
11.1.1	IssueAttachmentsBySavedQueryId	606
11.1.2	IssueById	610
11.1.3	IssueCommentsBySavedQueryId	614
11.1.4	IssueCustomFieldsBySavedQueryId	618
11.1.5	Issues	623
11.1.6	IssuesAttachments	626
11.1.7	IssuesComments	630
11.1.8	IssuesCustomFields	634
11.1.9	IssuesLinks	638
11.1.10	IssuesLinksById	642
11.1.11	IssuesTags	646

11.1.12	IssueTagsBySavedQueryId	650
11.1.13	SavedQueries: YouTrack Saved Queries	654
11.1.14	SavedQueryById	656

12 Schema: Users 658

12.1	Tables	658
12.1.1	IssueTags: YouTrack Issue Tags	658
12.1.2	Me	661
12.1.3	MyIssueTags	662
12.1.4	MySavedQueries	665
12.1.5	MySavedQueriesIssues	667
12.1.6	MyTags	670
12.1.7	ProfileTimeTrackingsByUserId	672
12.1.8	SavedQueries: YouTrack Saved Queries	673
12.1.9	SavedQueryById	675
12.1.10	SavedQueryIssues	678
12.1.11	SavedQueryIssuesByUserId	680
12.1.12	TagById	683
12.1.13	TagIssuesByTagId	686
12.1.14	Tags	689
12.1.15	UserById	691
12.1.16	UserGeneralProfilesBySprintId	693
12.1.17	UserIssueAttachmentSavedQueriesByUserId	694
12.1.18	UserIssueAttachmentTagsByUserId	699
12.1.19	UserIssueCommentSavedQueriesByUserId	703
12.1.20	UserIssueCommentTagsByUserId	707
12.1.21	UserIssueCustomFieldSavedQueriesByUserId	712
12.1.22	UserIssueCustomFieldTagsByUserId	716
12.1.23	UserIssueLinkSavedQueriesByUserId	720
12.1.24	UserIssueLinkSavedQueryTagsByUserId	724
12.1.25	UserIssueSavedQueriesByUserId	729
12.1.26	UserIssueTagSavedQueriesByUserId	733
12.1.27	UserIssueTagsByUserId	737
12.1.28	UserIssueTagsByUserId1	741
12.1.29	UserNotificationProfilesBySprintId	746
12.1.30	Users: YouTrack Users	747
12.1.31	UserSavedQueriesByUserId	748
12.1.32	UserTagsByUserId	751
12.1.33	WorkItemById	753
12.1.34	WorkItems: YouTrack Work Items	757

13 Schema: Views 761

13.1	Views	761
13.1.1	IDTypes	761

Index 763

1 SQL Driver for YouTrack API

Invantive SQL is the fastest, easiest and most reliable way to exchange data with the YouTrack API.

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the [user community](#). Other users or Invantive Support will try to help you to our best.

YouTrack by JetBrains provides bug tracking, issue tracking system and project management.

The YouTrack driver covers 233 tables and 21272 columns.

YouTrack API Clients

Invantive SQL is available on many user interfaces ("clients" in traditional server-client paradigm). All Invantive SQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

The [YouTrack Power BI connector](#) is based on the Invantive SQL driver for YouTrack, completed by a high-performance OData connector which works straight on Power BI without any add-on. The OData protocol is always version 4, independent whether the backing platform uses OData, SOAP or another protocol.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL. High-volume replication of data taken from the YouTrack API into traditional databases such as SQL Server (on-premise and Azure), MySQL, PostgreSQL and Oracle is possible using [Invantive Data Replicator](#). Invantive Data Replicator automatically creates and maintains YouTrack datawarehouses, possibly in combination with data from over 70 other (cloud) platforms. Data Replicator supports data volumes up to over 1 TB and over 5.000 companies. The on-premise edition of Invantive Bridge offers an YouTrack ADO.net provider.

Finally, online web apps can be build for YouTrack using App Online of [Invantive Cloud](#).

Monitor API Calls

When a query or DML-statement has been executed on Invantive SQL a developer can evaluate the actual calls made to the YouTrack API using a query on sessionios@DataDictionary. As an alternative, extensive request and response logging can be enabled by setting log-native-calls-to-disk to true. In the %USERPROFILE%\Invantive\NativeLog folder Invantive SQL will create log files per API request and response.

Specifications

The SQL driver for YouTrack does not support partitioning. Define one data container in a database for each company in YouTrack to enable parallel access for data from multiple companies.

An introduction into the concepts of Invantive SQL such as databases, data containers and partitioning can be found in the [Invantive SQL grammar](#).

The configuration can be changed using various attributes during log on and use. A full list of configuration options is listed in the [driver attributes](#).

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On YouTrack the comparison of two texts is case sensitive by default.

Changes and bug fixes on the YouTrack SQL driver can be found in the [release notes](#). Get access to the YouTrack community through the [YouTrack section](#) of the Invantive forums.

Driver code for use in settings.xml: YouTrack

Alias: youtrack

Recommended alias: ytk

More technical documentation as provided by the supplier of the YouTrack API on the native APIconnection used can be found at <https://www.jetbrains.com/help/youtrack/devportal>.

The format of YouTrack record IDs consists of a value from the view IDTypes, a dash as separator and a numeric value.

Updated: 23-06-2022 19:43 using Invantive SQL version 22.0.248-PROD+3461.

2 SQL Driver Attributes for YouTrack API

The SQL driver for YouTrack has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the API server of YouTrack or high-volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The YouTrack driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Drivers file: the providers.xml file (obsolete starting release 17.32).
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for YouTrack can be found in the settings*.xml file used for the database. Settings*.xml files are typically located in the %USERPROFILE%\invantive folder in most deployment scenarios. The reference manuals contain instructions how to relocate the settings*.xml files. Each data container of a database in the connection string can have a `connectionString` element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: `set NAME VALUE`, or for a distributed database: `set NAME@ALIAS VALUE`. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance

when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The YouTrack driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
add-odata-mandatory-filters	Whether to automatically add OData filters deemed necessary by the platform.	OData	False	✓	✓	✓	
analysis-enforce-row-uniqueness	Use for analysis only! Enforce rows to be unique.	Shared	False	✓	✓	✓	
api-access-token	Access Token is a security token for multiple OAuth2 Flows. With an Access Token you can access protected resources. An Access Token must be stored securely since once compromised allows access to your protected resources.	OData		✓		✓	✓
api-client-id	The client ID is a unique identifier of your application. It is generated by registering an application.	OData		✓		✓	✓
api-client-secret	The client secret is to be kept confidential. Such as a password for a logon code, the client secret is the confidential part of an app identified by a client ID. It is needed during the OAuth2 Code Grant Flow together with the refresh token to get access.	OData		✓		✓	✓
api-pre-expiry-refresh-sec	The number of seconds before the token expires to acquire a new token.	OData		✓	✓	✓	
api-redirect-url	The redirect URI is the website a browser session is redirected to after the OAuth2 authentication process has been completed.	OData		✓		✓	✓
api-refresh-token	Refresh Token is a security token for the OAuth2 Code Grant Flow. With a Refresh Token and client secret you can retrieve a renewed access token to access protected resources. A Refresh Token and client secret must be stored securely since once compromised allows access to your protected resources.	OData		✓		✓	✓
api-scope	The scope to request an OAuth token for.	OData		✓		✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
api-token-url	The token URI is the OAuth2 endpoint to exchange tokens.	OData		✓		✓	
api-url	URL to access the API.	OData		✓		✓	
bulk-delete-page-size-rows	Number of rows to delete per batch when bulk deleting	Shared	10000	✓	✓	✓	
bulk-insert-page-size-bytes	Approximate maximum size in bytes of batch when bulk inserting	Shared	10000000	✓	✓	✓	
bulk-insert-page-size-rows	Number of rows to insert per batch when bulk inserting	Shared	250	✓	✓	✓	
download-error-400-bad-request-max-tries	Maximum number of tries when OData server reports bad format during retrieval of data.		3	✓	✓	✓	
download-error-400-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		500	✓	✓	✓	
download-error-400-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		5000	✓	✓	✓	
download-error-400-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
download-error-408-request-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 408.		10	✓	✓	✓	
download-error-408-request-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 408.		10000	✓	✓	✓	
download-error-408-request-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 408.		300000	✓	✓	✓	
download-error-408-request-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 408.		2	✓	✓	✓	
download-error-422-bad-request-max-tries	Maximum number of tries when OData server reports unprocessable entity during retrieval of data.		30	✓	✓	✓	
download-error-422-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports unprocessable entity during retrieval of data.		10000	✓	✓	✓	
download-error-422-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports unprocessable entity during retrieval of data.		300000	✓	✓	✓	
download-error-422-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server		2	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
	reports unprocessable entity during retrieval of data.						
dow nload-error-429-too-many-requests-max-tries	Maximum number of tries w hen the w ebsite reports that too many requests have been made during a timeslot of one minute or one day.		10	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen the w ebsite reports that too many requests have been made during a timeslot of one minute or one day.		10000	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen the w ebsite reports that too many requests have been made during a timeslot of one minute or one day.		300000	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen the w ebsite reports that too many requests have been made during a timeslot of one minute or one day.		2	✓	✓	✓	
dow nload-error-502-server-unavailable-max-tries	Maximum number of tries w hen OData server reports a bad gatew ay during retrieval of data.		30	✓	✓	✓	
dow nload-error-502-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen OData server reports a bad gatew ay during retrieval of data.		10000	✓	✓	✓	
dow nload-error-502-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen OData server reports that a bad gatew ay during retrieval of data.		300000	✓	✓	✓	
dow nload-error-502-server-unavailable-sleep-multiplicator	Multiplication factor for sleep betw een retries OData server reports a bad gatew ay during retrieval of data.		2	✓	✓	✓	
dow nload-error-503-server-unavailable-max-tries	Maximum number of tries w hen OData server reports that the API server is unavailable during retrieval of data.		30	✓	✓	✓	
dow nload-error-503-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen OData server reports that the API server is unavailable during retrieval of data.		10000	✓	✓	✓	
dow nload-error-503-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen OData server reports that the API server is unavailable during retrieval of data.		300000	✓	✓	✓	
dow nload-error-503-server-	Multiplication factor for sleep betw een retries OData server		2	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
unavailable-sleep-multiplicator	reports that the API server is unavailable during retrieval of data.						
dow nload-error-504-gatew ay-timeout-max-tries	Maximum number of tries w hen the w ebsite reports a gatew ay timeout.		10	✓	✓	✓	
dow nload-error-504-gatew ay-timeout-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen the w ebsite reports a gatew ay timeout.		10000	✓	✓	✓	
dow nload-error-504-gatew ay-timeout-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen the w ebsite reports a gatew ay timeout.		300000	✓	✓	✓	
dow nload-error-504-gatew ay-timeout-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen the w ebsite reports a gatew ay timeout.		2	✓	✓	✓	
dow nload-error-590-netw ork-connect-timeout-max-tries	Maximum number of tries w hen the w ebsite reports a HTTP status 590.		10	✓	✓	✓	
dow nload-error-590-netw ork-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen the w ebsite reports a HTTP status 590.		10000	✓	✓	✓	
dow nload-error-590-netw ork-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen the w ebsite reports a HTTP status 590.		300000	✓	✓	✓	
dow nload-error-590-netw ork-connect-timeout-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen the w ebsite reports a HTTP status 590.		2	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-max-tries	Maximum number of tries w hen the w ebsite reports a HTTP status 599.		10	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds betw een retries w hen the w ebsite reports a HTTP status 599.		10000	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds betw een retries w hen the w ebsite reports a HTTP status 599.		300000	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-sleep-multiplicator	Multiplication factor for sleep betw een retries w hen the w ebsite reports a HTTP status 599.		2	✓	✓	✓	
dow nload-error-argument-exception-	Maximum number of tries w hen an argument exception is returned		10	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
max-tries	when downloading a blob.						
download-error-argument-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		10000	✓	✓	✓	
download-error-argument-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		300000	✓	✓	✓	
download-error-argument-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an argument exception is returned when downloading a blob.		2	✓	✓	✓	
download-error-internet-download-max-tries	Maximum number of tries when the Internet connection seems down during retrieval of data.		10	✓	✓	✓	
download-error-internet-download-sleep-initial-ms	Initial sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		10000	✓	✓	✓	
download-error-internet-download-sleep-max-ms	Maximum sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		300000	✓	✓	✓	
download-error-internet-download-sleep-multiplicator	Multiplication factor for sleep between retries when the Internet connection seems down during retrieval of data.		2	✓	✓	✓	
download-error-io-exception-max-tries	Maximum number of tries when a network I/O connection failure occurs during retrieval of data.		10	✓	✓	✓	
download-error-io-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		10000	✓	✓	✓	
download-error-io-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		300000	✓	✓	✓	
download-error-io-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a network I/O connection failure occurs during retrieval of data.		2	✓	✓	✓	
download-error-json-exception-max-tries	Maximum number of tries when an invalid JSON body is returned.		3	✓	✓	✓	
download-error-json-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an invalid JSON body is returned.		1000	✓	✓	✓	
download-error-json-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an invalid JSON body is returned.		10000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
dow nload-error-json-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an invalid JSON body is returned.		2	✓	✓	✓	
dow nload-error-other-exception-max-tries	Maximum number of tries when an unqualified error occurs during retrieval of data.		3	✓	✓	✓	
dow nload-error-other-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an unqualified error occurs during retrieval of data.		10000	✓	✓	✓	
dow nload-error-other-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an unqualified error occurs during retrieval of data.		300000	✓	✓	✓	
dow nload-error-other-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an unqualified error occurs during retrieval of data.		2	✓	✓	✓	
dow nload-error-socket-exception-max-tries	Maximum number of tries when the network connection is forcibly dropped during retrieval of data.		10	✓	✓	✓	
dow nload-error-socket-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when the network connection is forcibly dropped during retrieval of data.		10000	✓	✓	✓	
dow nload-error-socket-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when the network connection is forcibly dropped during retrieval of data.		300000	✓	✓	✓	
dow nload-error-socket-exception-sleep-multiplicator	Multiplication factor for sleep between retries when the network connection is forcibly dropped during retrieval of data.		2	✓	✓	✓	
dow nload-error-web-exception-max-tries	Maximum number of tries when a web connection failure occurs during retrieval of data.		10	✓	✓	✓	
dow nload-error-web-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		10000	✓	✓	✓	
dow nload-error-web-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		300000	✓	✓	✓	
dow nload-error-web-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a web connection failure occurs during retrieval of data.		2	✓	✓	✓	
dow nload-error-web-not-implemented-max-tries	Maximum number of tries when the connection reports not implemented.		1	✓	✓	✓	
dow nload-error-web-not-	Initial sleep in milliseconds between retries when the connection reports		10000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
implemented-sleep-initial-ms	not implemented.						
dow nload-error-web-not-implemented-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports not implemented.		300000	✓	✓	✓	
dow nload-error-web-not-implemented-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports not implemented.		2	✓	✓	✓	
dow nload-error-web-timeout-max-tries	Maximum number of tries when the connection reports a timeout.		10	✓	✓	✓	
dow nload-error-web-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports a timeout.		1000	✓	✓	✓	
dow nload-error-web-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports a timeout.		30000	✓	✓	✓	
dow nload-error-web-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports a timeout.		2	✓	✓	✓	
dow nload-error-web-unauthorized-max-tries	Maximum number of tries when the connection reports an unauthorized error.		1	✓	✓	✓	
dow nload-error-web-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports an unauthorized error.		10000	✓	✓	✓	
dow nload-error-web-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports an unauthorized error.		300000	✓	✓	✓	
dow nload-error-web-unauthorized-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports an unauthorized error.		2	✓	✓	✓	
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	Shared	False	✓	✓	✓	
forced-casing-identifiers	Forced casing of identifiers. Choose from Unset, Lower, Upper and Mixed.	Shared		✓	✓	✓	
http-disk-cache-compression-level	Compression level for the HTTP disk cache, ranging from 1 (little) to 9 (intense). Default is 5.	Shared	5	✓	✓	✓	
http-disk-cache-directory	Directory where HTTP cache is stored.	Shared	C:\Users\gle3.WS212\Invasive\Cache\http\gle3\shared	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
http-disk-cache-ignore-write-errors	Whether to ignore write errors to disk cache.	Shared	False	✓	✓	✓	
http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP disk cache.	Shared	2592000	✓	✓	✓	
http-get-timeout-max-ms	HTTP GET maximum timeout on retry (ms).		300000	✓	✓	✓	
http-get-timeout-ms	HTTP GET timeout (ms).		60000	✓	✓	✓	
http-memory-cache-compression-level	Compression level for the HTTP memory cache, ranging from 1 (little) to 9 (intense). Default is 5.	OData	5	✓	✓	✓	
http-memory-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP memory cache.	OData	14400	✓	✓	✓	
http-post-timeout-max-ms	HTTP POST maximum timeout on retry (ms).		300000	✓	✓	✓	
http-post-timeout-ms	HTTP POST timeout (ms).		300000	✓	✓	✓	
ignore-http-400-errors	Ignore HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-401-errors	Ignore HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-402-errors	Ignore HTTP 402 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-403-errors	Ignore HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-404-errors	Ignore HTTP 404 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-422-errors	Ignore HTTP 422 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-429-errors	Ignore HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-500-errors	Ignore HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-502-errors	Ignore HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-503-errors	Ignore HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
ignore-unknown-path-type	Whether to ignore path types not yet supported. An error will be generated when an unsupported type occurs.		True	✓	✓	✓	✓
ignore-values-unknown-path	Whether to ignore values outside of processed paths. An error will be generated when a value occurs outside a path otherwise.		True	✓	✓	✓	✓
invalid-json-on-get-max-tries	Maximum number of tries when the JSON received on GET is invalid.		10	✓	✓	✓	
invalid-json-on-get-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on GET is invalid.		10000	✓	✓	✓	
invalid-json-on-get-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on GET is invalid.		300000	✓	✓	✓	
invalid-json-on-get-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on GET is invalid.		2	✓	✓	✓	
invalid-json-on-post-max-tries	Maximum number of tries when the JSON received on POST is invalid.		1	✓	✓	✓	
invalid-json-on-post-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on POST is invalid.		10000	✓	✓	✓	
invalid-json-on-post-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on POST is invalid.		300000	✓	✓	✓	
invalid-json-on-post-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on POST is invalid.		2	✓	✓	✓	
invantive-sql-compress-sparse-arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753.	SQL Engine V1	False	✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-shuffle-fetch	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
results-data-containers							
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	✓	✓	✓	
join-set-points-per-request	Maximum number of values in a request w hen executing a join set.	OData	60	✓	✓	✓	
limit-partition-calls-left	Minimum number of remaining API calls on a partition tow ards a hard limit. When below , an error is raised.	OData	500	✓	✓	✓	
log-native-calls-to-disk-max-events	Maximum number of events to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-max-seconds	Maximum number of seconds to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-on-error	Registers native calls to data container backend as disk files w hen an error occurred.	Shared	False	✓	✓	✓	
log-native-calls-to-disk-on-success	Registers native calls to data container backend as disk files w hen successful.	Shared	False	✓	✓	✓	
log-native-calls-to-trace	Log native calls to data container backend on the trace.	Shared	False	✓	✓	✓	
maximum-discovered-column-count	Maximum number of discovered columns. An error w ill be generated w hen the column exceeds this value.		250	✓	✓	✓	✓
maximum-length-identifiers	Non-default maximum length in characters of identifier names.	Shared		✓	✓	✓	
max-odata-filters	The maximum number of OData filter elements.	OData	100	✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	Shared	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	Shared	8000	✓	✓	✓	
metadata-cache-max-age-sec	Maximum acceptable age in seconds for re-use of metadata.	OData		✓	✓	✓	
oauth-unauthorized-max-tries	Maximum number of tries w hen an OAuth exception occurs.	OData	2	✓	✓	✓	
oauth-unauthorized-sleep-initial-ms	Initial sleep in milliseconds betw een OAuth reauthentication tries w hen the OAuth authentication fails.	OData	10000	✓	✓	✓	
oauth-unauthorized-sleep-max-ms	Maximum sleep in milliseconds betw een OAuth reauthentication tries w hen the OAuth authentication fails.	OData	1000	✓	✓	✓	
oauth-unauthorized-sleep-multiplicator	Multiplication factor for sleep betw een OAuth reauthentication tries w hen the OAuth authentication fails.	OData	2	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
partition-slot-based-rate-limit-length-ms	Total length in ms across all slots of a partition-based rate limit.	Shared	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	Shared	0	✓	✓	✓	
requested-page-size	Preferred number of rows to exchange per round trip; only effective on limited platforms such as AFAS Online	Shared		✓	✓	✓	
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	Shared	32	✓	✓	✓	
service-url	{res:itgen_cloud_database_youtrack_service_url_tip}	YouTrack		✓		✓	✓
simulate-http-400-errors	Simulate HTTP 400 errors w hen exchanging results w ith the OData endpoint.		False	✓	✓	✓	
simulate-http-400-errors-percentage	Percentage of simulated HTTP 400 errors w hen exchanging results w ith the OData endpoint.		0	✓	✓	✓	
simulate-http-401-errors	Simulate HTTP 401 errors w hen exchanging results w ith the OData endpoint.		False	✓	✓	✓	
simulate-http-401-errors-percentage	Percentage of simulated HTTP 401 errors w hen exchanging results w ith the OData endpoint.		0	✓	✓	✓	
simulate-http-403-errors	Simulate HTTP 403 errors w hen exchanging results w ith the OData endpoint.		False	✓	✓	✓	
simulate-http-403-errors-percentage	Percentage of simulated HTTP 403 errors w hen exchanging results w ith the OData endpoint.		0	✓	✓	✓	
simulate-http-408-errors	Simulate HTTP 408 errors w hen exchanging results w ith the OData endpoint.		False	✓	✓	✓	
simulate-http-408-errors-percentage	Percentage of simulated HTTP 408 errors w hen exchanging results w ith the OData endpoint.		0	✓	✓	✓	
simulate-http-429-errors	Simulate HTTP 429 errors w hen exchanging results w ith the OData endpoint.		False	✓	✓	✓	
simulate-http-429-errors-percentage	Percentage of simulated HTTP 429 errors w hen exchanging results w ith the OData endpoint.		0	✓	✓	✓	
simulate-http-500-errors	Simulate HTTP 500 errors w hen exchanging results w ith the OData endpoint.		False	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
simulate-http-500-errors-percentage	Percentage of simulated HTTP 500 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-502-errors	Simulate HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-502-errors-percentage	Percentage of simulated HTTP 502 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-503-errors	Simulate HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-503-errors-percentage	Percentage of simulated HTTP 503 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-protocol-errors	Simulate HTTP protocol errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-protocol-errors-percentage	Percentage of simulated HTTP protocol errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-timeout-errors	Simulate HTTP timeout errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-timeout-errors-percentage	Percentage of simulated HTTP timeout errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
slot-based-rate-limit-length-ms	Total length in ms across all slots of a slot-based rate limit.	Shared	60000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	✓	✓	✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	Shared	True	✓	✓	✓	
swagger-specification-file	The Swagger file path, such as C:\temp\swagger.json.			✓	✓	✓	✓
swagger-specification-http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of Swagger specification data in the HTTP disk cache.		86400	✓	✓	✓	
swagger-specification-url	The Swagger URL such as https://example.org/rest/swagger.json.			✓	✓	✓	✓

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
use-batch-insert	Whether to use batch insert.	OData	True	✓	✓	✓	
use-http-disk-cache-read	Whether to use HTTP responses from previous queries stored on disk to answer the current query.	Shared	False	✓	✓	✓	
use-http-disk-cache-write	Whether to memorize HTTP responses on disk.	Shared	False	✓	✓	✓	
use-http-memory-cache-read	Whether to use HTTP responses from previous queries stored in memory that can answer the current query.	OData	True	✓	✓	✓	
use-http-memory-cache-write	Whether to memorize HTTP responses from previous queries for use by future queries.	OData	True	✓	✓	✓	

3 Schema: Activities

3.1 Tables

3.1.1 Activities: YouTrack Activities

Catalog: YouTrack

Schema: Activities

Label: Activities

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/activities`

Insert YouTrack API URL: `/activities`

Update YouTrack API URL: `/activities`

Delete YouTrack API URL: `/activities`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /activities`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `Activities`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
author	string	☐		Parameter to filter activities by the author. The database id or login, or Hub id, or 'me' for the current logged in user could be specified.
categories	string	☐		
end	string	☐		End timestamp of the time interval the activity timestamp belongs to. If the parameter is not set, it is considered as Long.MAX_VALUE.
issueQuery	string	☐		Issues search query. Read more about Search-and-Command-Attributes.xml >search syntax .
reverse	boolean	☐		Indicates whether the order of returning activities is from newest to oldest or the opposite. If "false", then the oldest activity item that matches a selected filter is returned first. If "true", then the newest activity is returned first. By default, "false".
start	string	☐		Start timestamp of the time interval the activity timestamp belongs to. If the parameter is not set, it is considered to be 0.

Table Function Columns

The columns of the table function `Activities` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
author_login	string		☐	
author_online	boolean		☐	
author_profiles_\$type	string		☐	
author_profiles_id	string		☐	
author_ringId	string		☐	
category_\$type	string		☐	
category_id	string		☐	
field_\$type	string		☐	
field_id	string		☐	
field_name	string		☐	
field_presentation	string		☐	
id	string	ID	☐	
targetMember	string	Target member	☐	
timestamp	int64	Timestamp	☐	

3.1.2 ActivityById

Catalog: YouTrack

Schema: Activities

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the `table NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/activities/{id}`

Insert YouTrack API URL: `/activities/{id}`

Update YouTrack API URL: `/activities/{id}`

Delete YouTrack API URL: `/activities/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /activities/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ActivityById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `ActivityById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_profiles_\$type	string		☐	
author_profiles_id	string		☐	
author_ringId	string		☐	
category_\$type	string		☐	
category_id	string		☐	
field_\$type	string		☐	
field_id	string		☐	
field_name	string		☐	
field_presentation	string		☐	
id	string	ID	☐	
targetMember	string	Target member	☐	
timestamp	int64	Timestamp	☐	

3.1.3 ActivityPages

Catalog: YouTrack

Schema: Activities

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: /activitiesPage

Insert YouTrack API URL: /activitiesPage

Update YouTrack API URL: /activitiesPage

Delete YouTrack API URL: /activitiesPage

Field Selection Method: NotRequired

Select YouTrack API Operation: get /activitiesPage

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ActivityPages. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
activityId	string	☐		ID of the activity that should be included in the page. The activity is allocated to the middle of the page.
author	string	☐		Parameter to filter activities by the author. The database id or login, or Hub id, or 'me' for the current logged in user could be specified.
categories	string	☐		
cursor	string	☐		
end	string	☐		End timestamp of the time interval the activity timestamp belongs to. If the parameter is not set, it is considered as Long.MAX_VALUE.
issueQuery	string	☐		Issues search query. Read more about Search-and-Command-Attributes.xml >search syntax .
reverse	boolean	☐		Indicates whether the order of returning activities is from newest to oldest or the opposite. If "false", then the oldest activity item that matches a selected filter is returned first. If

Name	Data Type	Required	Default Value	Documentation
				"true", then the new est activity is returned first. By default, "false".
start	string	☐		Start timestamp of the time interval the activity timestamp belongs to. If the parameter is not set, it is considered to be 0.

Table Function Columns

The columns of the table function `ActivityPages` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
afterCursor	string	After Cursor	☐	
beforeCursor	string	Before Cursor	☐	
hasAfter	boolean	Has After	☐	
hasBefore	boolean	Has Before	☐	
id	string	ID	☐	
reverse	boolean	Reverse	☐	

3.1.4 ProjectActivityPages

Catalog: YouTrack

Schema: Activities

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/activitiesPage`

Insert YouTrack API URL: `/activitiesPage`

Update YouTrack API URL: `/activitiesPage`

Delete YouTrack API URL: `/activitiesPage`

Field Selection Method: `NotRequired`

Base Path: `activities[*]`

Select YouTrack API Operation: `get /activitiesPage`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ProjectActivityPages`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
activityId	string	☐		ID of the activity that should be included in the page. The activity is allocated to the middle of the page.
author	string	☐		Parameter to filter activities by the author. The database id or login, or Hub id, or 'me' for the current logged in user could be specified.
categories	string	☐		
cursor	string	☐		
end	string	☐		End timestamp of the time interval the activity timestamp belongs to. If the parameter is not set, it is considered as Long.MAX_VALUE.
issueQuery	string	☐		Issues search query. Read more about Search-and-Command-Attributes.xml > search syntax .
reverse	boolean	☐		Indicates whether the order of returning activities is from newest to oldest or the opposite. If "false", then the oldest activity item that matches a selected filter is returned first. If "true", then the newest activity is returned first. By default, "false".
start	string	☐		Start timestamp of the time interval the activity timestamp belongs to. If the parameter is not set, it is considered to be 0.

Table Function Columns

The columns of the table function `ProjectActivityPages` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
afterCursor	string	After Cursor	☐	

Name	Data Type	Label	Required	Documentation
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
beforeCursor	string	Before Cursor	☐	
category_\$type	string		☐	
category_id	string		☐	
field_\$type	string		☐	
field_id	string		☐	
field_name	string		☐	
field_presentation	string		☐	
hasAfter	boolean	Has After	☐	
hasBefore	boolean	Has Before	☐	
id_1	string		☐	
id	string	ID	☐	
reverse	boolean	Reverse	☐	
targetMember	string	Target member	☐	
timestamp	int64	Timestamp	☐	

4 Schema: Admin

4.1 Tables

4.1.1 AllowedOriginRestSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/restSettings`

Insert YouTrack API URL: `/admin/globalSettings/restSettings`

Update YouTrack API URL: `/admin/globalSettings/restSettings`

Delete YouTrack API URL: `/admin/globalSettings/restSettings`

Field Selection Method: NotRequired

Base Path: `allowedOrigins[*]`

Select YouTrack API Operation: `get /admin/globalSettings/restSettings`

Table Function Columns

The columns of the table function `AllowedOriginRestSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
allow AllOrigins	boolean	Allow All Origins	☐	
id	string	ID	☐	
TEXT	string	Text	☐	

4.1.2 AppearanceSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/appearanceSettings`

Insert YouTrack API URL: `/admin/globalSettings/appearanceSettings`

Update YouTrack API URL: `/admin/globalSettings/appearanceSettings`

Delete YouTrack API URL: `/admin/globalSettings/appearanceSettings`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/globalSettings/appearanceSettings`

Table Function Columns

The columns of the table function `AppearanceSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
dateFieldFormat_\$type	string		☐	
dateFieldFormat_datePattern	string		☐	
dateFieldFormat_id	string		☐	
dateFieldFormat_pattern	string		☐	
dateFieldFormat_presentation	string		☐	
id	string	ID	☐	
logo_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
logo_id	string		☐	
logo_url	string		☐	
timeZone_\$type	string		☐	
timeZone_id	string		☐	
timeZone_offset	int32		☐	
timeZone_presentation	string		☐	

4.1.3 GlobalSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings`

Insert YouTrack API URL: `/admin/globalSettings`

Update YouTrack API URL: `/admin/globalSettings`

Delete YouTrack API URL: `/admin/globalSettings`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /admin/globalSettings`

Table Function Columns

The columns of the table function `GlobalSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
appearanceSettings_\$type	string		☐	
appearanceSettings_dateFieldForm at_\$type	string		☐	
appearanceSettings_dateFieldForm at_datePattern	string		☐	
appearanceSettings_dateFieldForm at_id	string		☐	
appearanceSettings_dateFieldForm at_pattern	string		☐	
appearanceSettings_dateFieldForm at_presentation	string		☐	
appearanceSettings_id	string		☐	
appearanceSettings_logo_\$type	string		☐	
appearanceSettings_logo_id	string		☐	
appearanceSettings_logo_url	string		☐	

Name	Data Type	Label	Required	Documentation
appearanceSettings_timezone_\$type	string		☐	
appearanceSettings_timezone_id	string		☐	
appearanceSettings_timezone_offset	int32		☐	
appearanceSettings_timezone_presentation	string		☐	
id	string	ID	☐	
license_\$type	string		☐	
license_error	string		☐	
license_id	string		☐	
license_license	string		☐	
license_username	string		☐	
localeSettings_\$type	string		☐	
localeSettings_id	string		☐	
localeSettings_isRTL	boolean		☐	
localeSettings_locale_\$type	string		☐	
localeSettings_locale_community	boolean		☐	
localeSettings_locale_id	string		☐	
localeSettings_locale_language	string		☐	
localeSettings_locale_locale	string		☐	
localeSettings_locale_name	string		☐	
notificationSettings_\$type	string		☐	
notificationSettings_emailSettings_\$type	string		☐	
notificationSettings_emailSettings_anonymous	boolean		☐	
notificationSettings_emailSettings_from	string		☐	
notificationSettings_emailSettings_host	string		☐	
notificationSettings_emailSettings_id	string		☐	
notificationSettings_emailSettings_isEnabled	boolean		☐	
notificationSettings_emailSettings_login	string		☐	
notificationSettings_emailSettings_mailProtocol	string		☐	
notificationSettings_emailSettings_port	int32		☐	
notificationSettings_emailSettings_replyTo	string		☐	
notificationSettings_id	string		☐	
notificationSettings_jabberSettings_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
notificationSettings_jabberSettings_host	string		☐	
notificationSettings_jabberSettings_id	string		☐	
notificationSettings_jabberSettings_isEnabled	boolean		☐	
notificationSettings_jabberSettings_login	string		☐	
notificationSettings_jabberSettings_port	int32		☐	
notificationSettings_jabberSettings_serviceName	string		☐	
restSettings_\$type	string		☐	
restSettings_allowAllOrigins	boolean		☐	
restSettings_id	string		☐	
systemSettings_\$type	string		☐	
systemSettings_administratorEmail	string		☐	
systemSettings_allowStatisticsCollection	boolean		☐	
systemSettings_baseUrl	string		☐	
systemSettings_id	string		☐	
systemSettings_isApplicationReadOnly	boolean		☐	
systemSettings_maxExportItems	int32		☐	
systemSettings_maxUploadFileSize	int64		☐	

4.1.4 IssueAttachments

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: `NotRequired`

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `IssueAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
archived	boolean	Archived	☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_\$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
description_1	string		☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_\$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
replyToEmail	string	Reply-to Email	☐	

Name	Data Type	Label	Required	Documentation
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
size	int64	Size	☐	
startingNumber	int64	Starting Number	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.5 IssueComments

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: `NotRequired`

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `IssueComments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_\$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
deleted	boolean	Deleted	☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	

Name	Data Type	Label	Required	Documentation
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_\$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	

Name	Data Type	Label	Required	Documentation
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.6 IssueCustomFields

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: `NotRequired`

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `IssueCustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	

Name	Data Type	Label	Required	Documentation
created	int64	Created	☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_\$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_\$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	

Name	Data Type	Label	Required	Documentation
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.7 IssueLinks

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: `NotRequired`

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `IssueLinks` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_\$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.8 Issues

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: /admin/projects

Delete YouTrack API URL: /admin/projects

Field Selection Method: NotRequired

Base Path: issues[*]

Select YouTrack API Operation: get /admin/projects

Table Function Columns

The columns of the table function `Issues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_\$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_\$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.9 IssueTags: YouTrack Issue Tags

Catalog: YouTrack

Schema: Admin

Label: Issue Tags

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: `NotRequired`

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `IssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
archived	boolean	Archived	☐	

Name	Data Type	Label	Required	Documentation
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
createdBy_\$type_1	string		☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id_1	string		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_name	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_\$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
createdBy_untagOnResolve	boolean		☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	

Name	Data Type	Label	Required	Documentation
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_\$type_1	string		☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id_1	string		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_name	string		☐	
leader_online	boolean		☐	
leader_profiles_\$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
leader_untagOnResolve	boolean		☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
untagOnResolve	boolean		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	

Name	Data Type	Label	Required	Documentation
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.10 Licenses

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/license`

Insert YouTrack API URL: `/admin/globalSettings/license`

Update YouTrack API URL: `/admin/globalSettings/license`

Delete YouTrack API URL: `/admin/globalSettings/license`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /admin/globalSettings/license`

Table Function Columns

The columns of the table function `Licenses` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
error	string	Error	☐	
id	string	ID	☐	
license	string	License	☐	
username	string	User Name	☐	

4.1.11 LocaleSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/localeSettings`

Insert YouTrack API URL: `/admin/globalSettings/localeSettings`

Update YouTrack API URL: `/admin/globalSettings/localeSettings`

Delete YouTrack API URL: `/admin/globalSettings/localeSettings`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /admin/globalSettings/localeSettings`

Table Function Columns

The columns of the table function `LocaleSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>isRTL</code>	boolean	Is RTL	☐	
<code>locale_\$type</code>	string		☐	
<code>locale_community</code>	boolean		☐	
<code>locale_id</code>	string		☐	
<code>locale_language</code>	string		☐	
<code>locale_locale</code>	string		☐	
<code>locale_name</code>	string		☐	

4.1.12 NotificationSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/notificationSettings`

Insert YouTrack API URL: `/admin/globalSettings/notificationSettings`

Update YouTrack API URL: `/admin/globalSettings/notificationSettings`

Delete YouTrack API URL: `/admin/globalSettings/notificationSettings`

Field Selection Method: `NotRequired`

Select YouTrack API Operation:

get /admin/globalSettings/notificationSettings

Table Function Columns

The columns of the table function `NotificationSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
emailSettings_\$type	string		☐	
emailSettings_anonymous	boolean		☐	
emailSettings_from	string		☐	
emailSettings_host	string		☐	
emailSettings_id	string		☐	
emailSettings_isEnabled	boolean		☐	
emailSettings_login	string		☐	
emailSettings_mailProtocol	string		☐	
emailSettings_port	int32		☐	
emailSettings_replyTo	string		☐	
emailSettings_sslKey_\$type	string		☐	
emailSettings_sslKey_id	string		☐	
emailSettings_sslKey_name	string		☐	
id	string	ID	☐	
jabberSettings_\$type	string		☐	
jabberSettings_host	string		☐	
jabberSettings_id	string		☐	
jabberSettings_isEnabled	boolean		☐	
jabberSettings_login	string		☐	
jabberSettings_port	int32		☐	
jabberSettings_serviceName	string		☐	

4.1.13 RestSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: /admin/globalSettings/restSettings

Insert YouTrack API URL: /admin/globalSettings/restSettings

Update YouTrack API URL: /admin/globalSettings/restSettings

Delete YouTrack API URL: /admin/globalSettings/restSettings

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/globalSettings/restSettings`

Table Function Columns

The columns of the table function `RestSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
allow AllOrigins	boolean	Allow All Origins	☐	
id	string	ID	☐	

4.1.14 SystemSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/systemSettings`

Insert YouTrack API URL: `/admin/globalSettings/systemSettings`

Update YouTrack API URL: `/admin/globalSettings/systemSettings`

Delete YouTrack API URL: `/admin/globalSettings/systemSettings`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/globalSettings/systemSettings`

Table Function Columns

The columns of the table function `SystemSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
administratorEmail	string	Administrator Email	☐	
allow StatisticsCollection	boolean	Allow Statistics Collection	☐	
baseUrl	string	Base URL	☐	
id	string	ID	☐	
isApplicationReadOnly	boolean	Is Application Read-only	☐	
maxExportItems	int32	Max Export Items	☐	
maxUploadFileSize	int64	Max Upload File Size	☐	

4.1.15 Telemetry

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/telemetry`

Insert YouTrack API URL: `/admin/telemetry`

Update YouTrack API URL: `/admin/telemetry`

Delete YouTrack API URL: `/admin/telemetry`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/telemetry`

Table Function Columns

The columns of the table function `Telemetry` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type</code>	string		☐	
<code>allocatedMemory</code>	string	Allocated Memory	☐	
<code>availableMemory</code>	string	Available Memory	☐	
<code>availableProcessors</code>	int32	Available Processors	☐	
<code>blobStringsCacheHitRate</code>	string	Blob String Cache Hit Rate	☐	
<code>cachedResultsCountInDBQueriesCache</code>	int32	Cached Results Count in DB Queries Cache	☐	
<code>databaseBackgroundThreads</code>	int32	Database Background Threads	☐	
<code>databaseLocation</code>	string	Database Location	☐	
<code>databaseQueriesCacheHitRate</code>	string	Database Queries Cache Hit Rate	☐	
<code>databaseSize</code>	string	Database Size	☐	
<code>fullDatabaseSize</code>	string	Full Database Size	☐	
<code>id</code>	string	ID	☐	
<code>installationFolder</code>	string	Installation Folder	☐	
<code>logsLocation</code>	string	Logs Location	☐	
<code>notificationAnalyzerThreads</code>	int32	Notification Analyzer Threads	☐	
<code>onlineUsers_\$type</code>	string		☐	
<code>onlineUsers_id</code>	string		☐	
<code>onlineUsers_users</code>	int32		☐	
<code>pendingAsyncJobs</code>	int32	Pending Async Jobs	☐	

Name	Data Type	Label	Required	Documentation
reportCalculatorThreads	int32	Report Calculator Threads	☐	
requestsPerSecond	string	Requests per Second	☐	
startedTime	int64	Start Time	☐	
textIndexSize	string	Text Index Size	☐	
totalTransactions	int64	Total Transactions	☐	
transactionsPerSecond	string	Transactions per Second	☐	
uptime	string	Uptime	☐	
usedMemory	string	Used Memory	☐	

4.1.16 TimeTrackingSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings`

Insert YouTrack API URL: `/admin/timeTrackingSettings`

Update YouTrack API URL: `/admin/timeTrackingSettings`

Delete YouTrack API URL: `/admin/timeTrackingSettings`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /admin/timeTrackingSettings`

Table Function Columns

The columns of the table function `TimeTrackingSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
workTimeSettings_\$type	string		☐	
workTimeSettings_daysAWeek	int32		☐	
workTimeSettings_firstDayOfWeek	int32		☐	
workTimeSettings_id	string		☐	
workTimeSettings_minutesADay	int32		☐	

4.1.17 TimeTrackingSettingWorkItemTypes

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes`

Insert YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes`

Update YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes`

Delete YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes`

Field Selection Method: NotRequired

Select YouTrack API Operation:

get `/admin/timeTrackingSettings/workItemTypes`

Table Function Columns

The columns of the table function `TimeTrackingSettingWorkItemTypes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
autoAttached	boolean	Auto-attached	☐	
id	string	ID	☐	
name	string	Name	☐	

4.1.18 TimeTrackingSettingWorkItemTypesByWorkItemId

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes/{workItemId}`

Insert YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes/{workItemId}`

Update YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes/{workItemId}`

Delete YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes/{workItemId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

```
get /admin/timeTrackingSettings/workItemTypes/{workItemId}
```

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `TimeTrackingSettingWorkItemTypesByWorkItemId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
<code>workItemId</code>	string	☒		

Table Function Columns

The columns of the table function

`TimeTrackingSettingWorkItemTypesByWorkItemId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type</code>	string		☐	
<code>autoAttached</code>	boolean	Auto-attached	☐	
<code>id</code>	string	ID	☐	
<code>name</code>	string	Name	☐	

4.1.19 TimeTrackingWorkTimeSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings/workTimeSettings`

Insert YouTrack API URL: `/admin/timeTrackingSettings/workTimeSettings`

Update YouTrack API URL: `/admin/timeTrackingSettings/workTimeSettings`

Delete YouTrack API URL: `/admin/timeTrackingSettings/workTimeSettings`

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/timeTrackingSettings/workTimeSettings

Table Function Columns

The columns of the table function `TimeTrackingWorkTimeSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
daysAWeek	int32	Days a Week	☐	
firstDayOfWeek	int32	First Day of Week	☐	
id	string	ID	☐	
minutesADay	int32	Minutes a Day	☐	

4.1.20 WorkItemTypeTimeTrackingSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: /admin/timeTrackingSettings

Insert YouTrack API URL: /admin/timeTrackingSettings

Update YouTrack API URL: /admin/timeTrackingSettings

Delete YouTrack API URL: /admin/timeTrackingSettings

Field Selection Method: NotRequired

Base Path: `workItemTypes[*]`

Select YouTrack API Operation: get /admin/timeTrackingSettings

Table Function Columns

The columns of the table function `WorkItemTypeTimeTrackingSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
autoAttached	boolean	Auto-attached	☐	
id_1	string		☐	
id	string	ID	☐	
name	string	Name	☐	
workTimeSettings_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
workTimeSettings_daysAWeek	int32		☐	
workTimeSettings_firstDayOfWeek	int32		☐	
workTimeSettings_id	string		☐	
workTimeSettings_minutesADay	int32		☐	

5 Schema: Agile

5.1 Tables

5.1.1 ProjectBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Base Path: `projects[*]`

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ProjectBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `ProjectBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>archived</code>	boolean	Archived	☐	
<code>colorCoding_\$type</code>	string		☐	
<code>colorCoding_id</code>	string		☐	
<code>columnSettings_\$type</code>	string		☐	
<code>columnSettings_field_\$type</code>	string		☐	
<code>columnSettings_field_aliases</code>	string		☐	
<code>columnSettings_field_hasRunningJob</code>	boolean		☐	
<code>columnSettings_field_id</code>	string		☐	
<code>columnSettings_field_isAutoAttached</code>	boolean		☐	
<code>columnSettings_field_isDisplayedInIssueList</code>	boolean		☐	
<code>columnSettings_field_isUpdateable</code>	boolean		☐	
<code>columnSettings_field_localizedName</code>	string		☐	
<code>columnSettings_field_name</code>	string		☐	
<code>columnSettings_field_ordinal</code>	int32		☐	
<code>columnSettings_id</code>	string		☐	
<code>createdBy_\$type</code>	string		☐	
<code>createdBy_avatarUrl</code>	string		☐	
<code>createdBy_banned</code>	boolean		☐	
<code>createdBy_email</code>	string		☐	
<code>createdBy_fullName</code>	string		☐	
<code>createdBy_guest</code>	boolean		☐	
<code>createdBy_id</code>	string		☐	
<code>createdBy_jabberAccountName</code>	string		☐	
<code>createdBy_login</code>	string		☐	
<code>createdBy_online</code>	boolean		☐	
<code>createdBy_ringId</code>	string		☐	
<code>currentSprint_\$type</code>	string		☐	
<code>currentSprint_agile_\$type</code>	string		☐	
<code>currentSprint_agile_hideOrphansSwimlane</code>	boolean		☐	
<code>currentSprint_agile_id</code>	string		☐	
<code>currentSprint_agile_name</code>	string		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
description	string	Description	☐	
estimationField_type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	

Name	Data Type	Label	Required	Documentation
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
fromEmail	string	From Email	☐	
hideOrphansSwimlane	boolean		☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id	string	ID	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	

Name	Data Type	Label	Required	Documentation
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
replyToEmail	string	Reply-to Email	☐	
shortName	string	Short Name	☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_orderId	int32		☐	
startingNumber	int64	Starting Number	☐	
status_type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
team_type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updateableBy_type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.2 ProjectIssues

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: `NotRequired`

Base Path: `projects[*].issues[*]`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `ProjectIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>archived</code>	boolean	Archived	☐	
<code>colorCoding_\$type</code>	string		☐	
<code>colorCoding_id</code>	string		☐	
<code>columnSettings_\$type</code>	string		☐	
<code>columnSettings_field_\$type</code>	string		☐	
<code>columnSettings_field_aliases</code>	string		☐	
<code>columnSettings_field_hasRunningJob</code>	boolean		☐	
<code>columnSettings_field_id</code>	string		☐	
<code>columnSettings_field_isAutoAttached</code>	boolean		☐	
<code>columnSettings_field_isDisplayedInIssueList</code>	boolean		☐	
<code>columnSettings_field_isUpdateable</code>	boolean		☐	
<code>columnSettings_field_localizedName</code>	string		☐	
<code>columnSettings_field_name</code>	string		☐	
<code>columnSettings_field_ordinal</code>	int32		☐	
<code>columnSettings_id</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	

Name	Data Type	Label	Required	Documentation
created	int64	Created	☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_ringId	string		☐	
currentSprint_\$type_1	string		☐	
currentSprint_\$type	string		☐	
currentSprint_agile_\$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_commentsCount	int32		☐	
currentSprint_created	int64		☐	
currentSprint_description	string		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id_1	string		☐	
currentSprint_id	string		☐	
currentSprint_idReadable	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_isDraft	boolean		☐	
currentSprint_name	string		☐	
currentSprint_numberInProject	int64		☐	
currentSprint_previousSprint_\$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_resolved	int64		☐	
currentSprint_start	int64		☐	
currentSprint_summary	string		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
currentSprint_updated	int64		☐	
currentSprint_usesMarkdown	boolean		☐	
currentSprint_votes	int32		☐	
currentSprint_wikifiedDescription	string		☐	
description_1	string		☐	
description	string	Description	☐	
estimationField_\$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_\$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_\$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
fromEmail	string	From Email	☐	

Name	Data Type	Label	Required	Documentation
hideOrphansSw imlane	boolean		☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	

Name	Data Type	Label	Required	Documentation
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
replyToEmail	string	Reply-to Email	☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncFieldType	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_order	int32		☐	
startingNumber	int64	Starting Number	☐	
status_\$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
summary	string	Summary	☐	
swimlaneSettings_\$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.3 ProjectIssuesBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Base Path: `projects[*].issues[*]`

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ProjectIssuesBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `ProjectIssuesBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	

Name	Data Type	Label	Required	Documentation
archived	boolean	Archived	☐	
colorCoding_\$type	string		☐	
colorCoding_id	string		☐	
columnSettings_\$type	string		☐	
columnSettings_field_\$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_ringId	string		☐	
currentSprint_\$type_1	string		☐	
currentSprint_\$type	string		☐	
currentSprint_agile_\$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_commentsCount	int32		☐	
currentSprint_created	int64		☐	
currentSprint_description	string		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id_1	string		☐	
currentSprint_id	string		☐	
currentSprint_idReadable	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_isDraft	boolean		☐	
currentSprint_name	string		☐	
currentSprint_numberInProject	int64		☐	
currentSprint_previousSprint_type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_resolved	int64		☐	
currentSprint_start	int64		☐	
currentSprint_summary	string		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
currentSprint_updated	int64		☐	
currentSprint_usesMarkdown	boolean		☐	
currentSprint_votes	int32		☐	
currentSprint_wikifiedDescription	string		☐	
description_1	string		☐	
description	string	Description	☐	
estimationField_type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_type	string		☐	

Name	Data Type	Label	Required	Documentation
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_\$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
fromEmail	string	From Email	☐	
hideOrphansSwimlane	boolean		☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	

Name	Data Type	Label	Required	Documentation
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
replyToEmail	string	Reply-to Email	☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
sprintsSettings_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_order	int32		☐	
startingNumber	int64	Starting Number	☐	
status_type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	

Name	Data Type	Label	Required	Documentation
summary	string	Summary	☐	
swimlaneSettings_\$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.4 Projects

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: `NotRequired`

Base Path: `projects[*]`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `Projects` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>archived</code>	boolean	Archived	☐	

Name	Data Type	Label	Required	Documentation
colorCoding_\$type	string		☐	
colorCoding_id	string		☐	
columnSettings_\$type	string		☐	
columnSettings_field_\$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
createdBy_\$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_ringId	string		☐	
currentSprint_\$type	string		☐	
currentSprint_agile_\$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_\$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
description	string	Description	☐	
estimationField_\$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_\$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_\$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
fromEmail	string	From Email	☐	
hideOrphansSwimlane	boolean		☐	

Name	Data Type	Label	Required	Documentation
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id	string	ID	☐	
leader_\$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
replyToEmail	string	Reply-to Email	☐	
shortName	string	Short Name	☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_\$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
startingNumber	int64	Starting Number	☐	
status_\$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_\$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
team_\$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.5 SprintById

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
colorCoding_\$type	string		☐	
colorCoding_id	string		☐	
columnSettings_\$type	string		☐	
columnSettings_field_\$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
currentSprint_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_agile_\$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_\$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
estimationField_\$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_\$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
hideOrphansSwimlane	boolean		☐	
id	string	ID	☐	
name	string	Name	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_\$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_order	int32		☐	
status_\$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_\$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.6 SprintByld1

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Base Path: `sprints[*]`

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintByld1`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintById1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
agile_\$type	string		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_orphansAtTheTop	boolean		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
colorCoding_\$type	string		☐	
colorCoding_id	string		☐	
columnSettings_\$type	string		☐	
columnSettings_field_\$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
currentSprint_\$type	string		☐	
currentSprint_agile_\$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
estimationField_type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	

Name	Data Type	Label	Required	Documentation
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
hideOrphansSwimlane	boolean		☐	
id_1	string		☐	
id	string	ID	☐	
isDefault	boolean	Is Default	☐	
name_1	string		☐	
name	string	Name	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
previousSprint_\$type	string		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncFieldType	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_order	int32		☐	
start	int64	Start	☐	
status_\$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_\$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.7 SprintById2

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: /agiles/{id}/sprints

Delete YouTrack API URL: /agiles/{id}/sprints

Field Selection Method: NotRequired

Select YouTrack API Operation: get /agiles/{id}/sprints

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintById2`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintById2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
agile_\$type	string		☐	
agile_colorCoding_\$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_\$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_\$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	

Name	Data Type	Label	Required	Documentation
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_\$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdatable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_\$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdatable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_\$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	

Name	Data Type	Label	Required	Documentation
agile_ow ner_online	boolean		☐	
agile_ow ner_ringId	string		☐	
agile_sprintsSettings_\$type	string		☐	
agile_sprintsSettings_cardOnSeve ralSprints	boolean		☐	
agile_sprintsSettings_disableSprint s	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtask sOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_\$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_sw imlaneSettings_\$type	string		☐	
agile_sw imlaneSettings_enabled	boolean		☐	
agile_sw imlaneSettings_id	string		☐	
agile_updateableBy_\$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_\$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id	string	ID	☐	
isDefault	boolean	Is Default	☐	
name	string	Name	☐	
previousSprint_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
previousSprint_agile_\$type	string		☐	
previousSprint_agile_hideOrphansSwimlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_\$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
start	int64	Start	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	

5.1.8 SprintIssueAttachmentsBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: `NotRequired`

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintIssueAttachmentsBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintIssueAttachmentsBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>agile_\$type</code>	string		☐	
<code>agile_colorCoding_\$type</code>	string		☐	
<code>agile_colorCoding_id</code>	string		☐	
<code>agile_columnSettings_\$type</code>	string		☐	
<code>agile_columnSettings_id</code>	string		☐	

Name	Data Type	Label	Required	Documentation
agile_currentSprint_\$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_\$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_\$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
agile_ow ner_avatarUrl	string		☐	
agile_ow ner_banned	boolean		☐	
agile_ow ner_email	string		☐	
agile_ow ner_fullName	string		☐	
agile_ow ner_guest	boolean		☐	
agile_ow ner_id	string		☐	
agile_ow ner_jabberAccountName	string		☐	
agile_ow ner_login	string		☐	
agile_ow ner_online	boolean		☐	
agile_ow ner_ringId	string		☐	
agile_sprintsSettings_\$type	string		☐	
agile_sprintsSettings_cardOnSeve ralSprints	boolean		☐	
agile_sprintsSettings_disableSprint s	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtask sOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_\$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_sw imlaneSettings_\$type	string		☐	
agile_sw imlaneSettings_enabled	boolean		☐	
agile_sw imlaneSettings_id	string		☐	
agile_updateableBy_\$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_\$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	

Name	Data Type	Label	Required	Documentation
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	

Name	Data Type	Label	Required	Documentation
parent_id	string		☐	
previousSprint_\$type	string		☐	
previousSprint_agile_\$type	string		☐	
previousSprint_agile_hideOrphans Swimlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtThe Top	boolean		☐	
previousSprint_agile_updateableBy ProjectBased	boolean		☐	
previousSprint_agile_visibleForProj ectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_\$ty pe	string		☐	
previousSprint_previousSprint_arc hived	boolean		☐	
previousSprint_previousSprint_fini sh	int64		☐	
previousSprint_previousSprint_goa l	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isD efault	boolean		☐	
previousSprint_previousSprint_na me	string		☐	
previousSprint_previousSprint_sta rt	int64		☐	
previousSprint_previousSprint_unr esolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesC ount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	

Name	Data Type	Label	Required	Documentation
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
start	int64	Start	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	

Name	Data Type	Label	Required	Documentation
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.9 SprintIssueCommentsBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintIssueCommentsBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintIssueCommentsBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
agile_\$type	string		☐	
agile_colorCoding_\$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_\$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_\$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_\$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_\$type	string		☐	
agile_originalEstimationField_aliases	string		☐	

Name	Data Type	Label	Required	Documentation
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_\$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_\$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_\$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_\$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_\$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_\$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	

Name	Data Type	Label	Required	Documentation
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_\$type	string		☐	
previousSprint_agile_\$type	string		☐	
previousSprint_agile_hideOrphansSwimlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_\$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	

Name	Data Type	Label	Required	Documentation
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.10 SprintIssueCustomFieldsBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintIssueCustomFieldsBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintIssueCustomFieldsBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
agile_\$type	string		☐	
agile_colorCoding_\$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_\$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_\$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_\$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	

Name	Data Type	Label	Required	Documentation
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_\$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdatable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_\$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_\$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_\$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_\$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_\$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_\$type	string		☐	
previousSprint_agile_\$type	string		☐	
previousSprint_agile_hideOrphansSwimlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_\$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	

Name	Data Type	Label	Required	Documentation
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.11 SprintIssueLinksBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintIssueLinksBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintIssueLinksBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
agile_\$type	string		☐	
agile_colorCoding_\$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_\$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_\$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_\$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	

Name	Data Type	Label	Required	Documentation
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_\$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdatable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_\$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_\$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_\$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_\$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_\$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_\$type	string		☐	
previousSprint_agile_\$type	string		☐	
previousSprint_agile_hideOrphans Swimlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtThe Top	boolean		☐	
previousSprint_agile_updateableBy ProjectBased	boolean		☐	
previousSprint_agile_visibleForProj ectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_\$ty pe	string		☐	
previousSprint_previousSprint_arc hived	boolean		☐	
previousSprint_previousSprint_fini sh	int64		☐	
previousSprint_previousSprint_goa l	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isD efault	boolean		☐	

Name	Data Type	Label	Required	Documentation
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.12 SprintIssues

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: `NotRequired`

Base Path: `sprints[*].issues[*]`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `SprintIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	

Name	Data Type	Label	Required	Documentation
agile_\$type	string		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_orphansAtTheTop	boolean		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
colorCoding_\$type	string		☐	
colorCoding_id	string		☐	
columnSettings_\$type	string		☐	
columnSettings_field_\$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
currentSprint_\$type_1	string		☐	
currentSprint_\$type	string		☐	
currentSprint_agile_\$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_commentsCount	int32		☐	
currentSprint_created	int64		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_description	string		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id_1	string		☐	
currentSprint_id	string		☐	
currentSprint_idReadable	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_isDraft	boolean		☐	
currentSprint_name	string		☐	
currentSprint_numberInProject	int64		☐	
currentSprint_previousSprint_\$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_resolved	int64		☐	
currentSprint_start	int64		☐	
currentSprint_summary	string		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
currentSprint_updated	int64		☐	
currentSprint_usesMarkdown	boolean		☐	
currentSprint_votes	int32		☐	
currentSprint_wikifiedDescription	string		☐	
description	string	Description	☐	
estimationField_\$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_\$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	

Name	Data Type	Label	Required	Documentation
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_\$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
hideOrphansSwimlane	boolean		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	

Name	Data Type	Label	Required	Documentation
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
previousSprint_\$type	string		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
resolved	int64	Resolved	☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_order	int32		☐	
start	int64	Start	☐	
status_type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
summary	string	Summary	☐	
swimlaneSettings_type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updateableBy_type	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

Name	Data Type	Label	Required	Documentation
visibleForProjectBased	boolean		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.13 SprintIssuesBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Base Path: `sprints[*].issues[*]`

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintIssuesBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintIssuesBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
agile_\$type	string		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_orphansAtTheTop	boolean		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
colorCoding_\$type	string		☐	
colorCoding_id	string		☐	
columnSettings_\$type	string		☐	
columnSettings_field_\$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
currentSprint_\$type_1	string		☐	
currentSprint_\$type	string		☐	
currentSprint_agile_\$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_archived	boolean		☐	
currentSprint_commentsCount	int32		☐	
currentSprint_created	int64		☐	
currentSprint_description	string		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id_1	string		☐	
currentSprint_id	string		☐	
currentSprint_idReadable	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_isDraft	boolean		☐	
currentSprint_name	string		☐	
currentSprint_numberInProject	int64		☐	
currentSprint_previousSprint_\$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_resolved	int64		☐	
currentSprint_start	int64		☐	
currentSprint_summary	string		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
currentSprint_updated	int64		☐	
currentSprint_usesMarkdown	boolean		☐	
currentSprint_votes	int32		☐	
currentSprint_wikifiedDescription	string		☐	
description	string	Description	☐	
estimationField_\$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_\$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	

Name	Data Type	Label	Required	Documentation
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_\$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
hideOrphansSwimlane	boolean		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	

Name	Data Type	Label	Required	Documentation
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdatable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
previousSprint_\$type	string		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
resolved	int64	Resolved	☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_\$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_order	int32		☐	
start	int64	Start	☐	
status_\$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
summary	string	Summary	☐	
swimlaneSettings_\$type	string		☐	
swimlaneSettings_enabled	boolean		☐	

Name	Data Type	Label	Required	Documentation
swimlaneSettings_id	string		☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.14 SprintIssuesBySprintId1

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintIssuesBySprintId1`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintIssuesBySprintId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
agile_\$type	string		☐	
agile_colorCoding_\$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_\$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_\$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_\$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_\$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	

Name	Data Type	Label	Required	Documentation
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_\$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_\$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_\$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_\$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_\$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	

Name	Data Type	Label	Required	Documentation
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_\$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	

Name	Data Type	Label	Required	Documentation
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_\$type	string		☐	
previousSprint_agile_\$type	string		☐	
previousSprint_agile_hideOrphans Swimlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtThe Top	boolean		☐	
previousSprint_agile_updateableBy ProjectBased	boolean		☐	
previousSprint_agile_visibleForProj ectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_\$ty pe	string		☐	
previousSprint_previousSprint_arc hived	boolean		☐	
previousSprint_previousSprint_fini sh	int64		☐	
previousSprint_previousSprint_goa l	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isD efault	boolean		☐	
previousSprint_previousSprint_na me	string		☐	
previousSprint_previousSprint_sta rt	int64		☐	
previousSprint_previousSprint_unr esolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesC ount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	

Name	Data Type	Label	Required	Documentation
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.15 SprintIssueTagsBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the `table NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SprintIssueTagsBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SprintIssueTagsBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
agile_\$type	string		☐	
agile_colorCoding_\$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_\$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_\$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_\$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_\$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	

Name	Data Type	Label	Required	Documentation
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_\$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_\$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_\$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_\$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_\$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	

Name	Data Type	Label	Required	Documentation
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_\$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_\$type	string		☐	
previousSprint_agile_\$type	string		☐	
previousSprint_agile_hideOrphansSwimlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_\$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	

Name	Data Type	Label	Required	Documentation
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
untagOnResolve	boolean		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	

Name	Data Type	Label	Required	Documentation
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.16 Sprints

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `sprints` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
colorCoding_\$type	string		☐	
colorCoding_id	string		☐	
columnSettings_\$type	string		☐	
columnSettings_field_\$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	

Name	Data Type	Label	Required	Documentation
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
currentSprint_\$type	string		☐	
currentSprint_agile_\$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_\$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
estimationField_\$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_\$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
hideOrphansSwimlane	boolean		☐	
id	string	ID	☐	
name	string	Name	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	

Name	Data Type	Label	Required	Documentation
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
status_\$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_\$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	

Name	Data Type	Label	Required	Documentation
updateableByProjectBased	boolean		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.17 Sprints1

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: `NotRequired`

Base Path: `sprints[*]`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `Sprints1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>agile_\$type</code>	string		☐	
<code>agile_hideOrphansSwimlane</code>	boolean		☐	
<code>agile_id</code>	string		☐	
<code>agile_name</code>	string		☐	
<code>agile_orphansAtTheTop</code>	boolean		☐	
<code>agile_updateableByProjectBased</code>	boolean		☐	
<code>agile_visibleForProjectBased</code>	boolean		☐	
<code>archived</code>	boolean	Archived	☐	
<code>colorCoding_\$type</code>	string		☐	
<code>colorCoding_id</code>	string		☐	
<code>columnSettings_\$type</code>	string		☐	
<code>columnSettings_field_\$type</code>	string		☐	
<code>columnSettings_field_aliases</code>	string		☐	
<code>columnSettings_field_hasRunningJob</code>	boolean		☐	
<code>columnSettings_field_id</code>	string		☐	
<code>columnSettings_field_isAutoAttached</code>	boolean		☐	
<code>columnSettings_field_isDisplayedInIssueList</code>	boolean		☐	
<code>columnSettings_field_isUpdateable</code>	boolean		☐	
<code>columnSettings_field_localizedName</code>	string		☐	
<code>columnSettings_field_name</code>	string		☐	
<code>columnSettings_field_ordinal</code>	int32		☐	
<code>columnSettings_id</code>	string		☐	
<code>currentSprint_\$type</code>	string		☐	
<code>currentSprint_agile_\$type</code>	string		☐	
<code>currentSprint_agile_hideOrphansSwimlane</code>	boolean		☐	
<code>currentSprint_agile_id</code>	string		☐	
<code>currentSprint_agile_name</code>	string		☐	
<code>currentSprint_agile_orphansAtTheTop</code>	boolean		☐	
<code>currentSprint_agile_updateableByProjectBased</code>	boolean		☐	
<code>currentSprint_agile_visibleForProjectBased</code>	boolean		☐	
<code>currentSprint_archived</code>	boolean		☐	
<code>currentSprint_finish</code>	int64		☐	

Name	Data Type	Label	Required	Documentation
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
estimationField_type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	

Name	Data Type	Label	Required	Documentation
hideOrphansSw imlane	boolean		☐	
id_1	string		☐	
id	string	ID	☐	
isDefault	boolean	Is Default	☐	
name_1	string		☐	
name	string	Name	☐	
originalEstimationField_\$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_\$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_\$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
previousSprint_\$type	string		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_\$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_\$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_\$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	

Name	Data Type	Label	Required	Documentation
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_orderId	int32		☐	
start	int64	Start	☐	
status_\$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_\$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

6 Schema: Articles

6.1 Tables

6.1.1 ArticleById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ArticleById`. A value must be provided at all times for required parameters, but optional

parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `ArticleById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
content_1	string		☐	
content	string	Content	☐	
created	int64	Created	☐	
externalArticle_\$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	

6.1.2 Articles: YouTrack Articles

Catalog: YouTrack

Schema: Articles

Label: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `Articles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
content_1	string		☐	
content	string	Content	☐	
created	int64	Created	☐	
externalArticle_\$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	

Name	Data Type	Label	Required	Documentation
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	

6.1.3 AttachmentById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: `NotRequired`

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `AttachmentById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `AttachmentById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>article_\$type_1</code>	string		☐	
<code>article_\$type</code>	string		☐	
<code>article_content_1</code>	string		☐	
<code>article_content</code>	string		☐	
<code>article_id_1</code>	string		☐	
<code>article_id</code>	string		☐	
<code>article_summary_1</code>	string		☐	
<code>article_summary</code>	string		☐	
<code>author_\$type_1</code>	string		☐	
<code>author_\$type</code>	string		☐	
<code>author_avatarUrl_1</code>	string		☐	
<code>author_avatarUrl</code>	string		☐	

Name	Data Type	Label	Required	Documentation
author_banned_1	boolean		☐	
author_banned	boolean		☐	
author_email_1	string		☐	
author_email	string		☐	
author_fullName_1	string		☐	
author_fullName	string		☐	
author_guest_1	boolean		☐	
author_guest	boolean		☐	
author_id_1	string		☐	
author_id	string		☐	
author_jabberAccountName_1	string		☐	
author_jabberAccountName	string		☐	
author_login_1	string		☐	
author_login	string		☐	
author_online_1	boolean		☐	
author_online	boolean		☐	
author_ringId_1	string		☐	
author_ringId	string		☐	
base64Content_1	string		☐	
base64Content	string	Base64 Content	☐	
charset_1	string		☐	
charset	string	Charset	☐	
comment_\$type_1	string		☐	
comment_\$type	string		☐	
comment_created_1	int64		☐	
comment_created	int64		☐	
comment_id_1	string		☐	
comment_id	string		☐	
comment_text_1	string		☐	
comment_text	string		☐	
comment_updated_1	int64		☐	
comment_updated	int64		☐	
content_1	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
draft_1	boolean		☐	
draft	boolean	Draft	☐	
extension_1	string		☐	
extension	string	Extension	☐	

Name	Data Type	Label	Required	Documentation
externalArticle_\$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
metaData_1	string		☐	
metaData	string	Metadata	☐	
mimeType_1	string		☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed_1	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type_1	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
size_1	int64		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
url_1	string		☐	
url	string	URL	☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.4 Attachments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: `NotRequired`

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `Attachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
article_\$type_1	string		☐	
article_\$type	string		☐	
article_content_1	string		☐	
article_content	string		☐	

Name	Data Type	Label	Required	Documentation
article_id_1	string		☐	
article_id	string		☐	
article_summary_1	string		☐	
article_summary	string		☐	
author_\$type_1	string		☐	
author_\$type	string		☐	
author_avatarUrl_1	string		☐	
author_avatarUrl	string		☐	
author_banned_1	boolean		☐	
author_banned	boolean		☐	
author_email_1	string		☐	
author_email	string		☐	
author_fullName_1	string		☐	
author_fullName	string		☐	
author_guest_1	boolean		☐	
author_guest	boolean		☐	
author_id_1	string		☐	
author_id	string		☐	
author_jabberAccountName_1	string		☐	
author_jabberAccountName	string		☐	
author_login_1	string		☐	
author_login	string		☐	
author_online_1	boolean		☐	
author_online	boolean		☐	
author_ringId_1	string		☐	
author_ringId	string		☐	
base64Content_1	string		☐	
base64Content	string	Base64 Content	☐	
charset_1	string		☐	
charset	string	Charset	☐	
comment_\$type_1	string		☐	
comment_\$type	string		☐	
comment_created_1	int64		☐	
comment_created	int64		☐	
comment_id_1	string		☐	
comment_id	string		☐	
comment_text_1	string		☐	
comment_text	string		☐	
comment_updated_1	int64		☐	
comment_updated	int64		☐	
content_1	string		☐	

Name	Data Type	Label	Required	Documentation
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
draft_1	boolean		☐	
draft	boolean	Draft	☐	
extension_1	string		☐	
extension	string	Extension	☐	
externalArticle_\$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
metaData_1	string		☐	
metaData	string	Metadata	☐	
mimeType_1	string		☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed_1	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type_1	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
size_1	int64		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
url_1	string		☐	
url	string	URL	☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.5 ChildArticleAttachments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: `NotRequired`

Base Path: `childArticles[*].attachments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `ChildArticleAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type_3	string		☐	
\$type	string		☐	
base64Content_1	string		☐	
base64Content	string	Base64 Content	☐	
charset_1	string		☐	
charset	string	Charset	☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created_3	int64		☐	
created	int64	Created	☐	
draft_1	boolean		☐	
draft	boolean	Draft	☐	
extension_1	string		☐	
extension	string	Extension	☐	
externalArticle_\$type_1	string		☐	
externalArticle_\$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id_3	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
metaData_1	string		☐	

Name	Data Type	Label	Required	Documentation
metaData	string	Metadata	☐	
mimeType_1	string		☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_\$type	string		☐	
parentArticle_base64Content	string		☐	
parentArticle_charset	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_draft	boolean		☐	
parentArticle_extension	string		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_metaData	string		☐	
parentArticle_mimeType	string		☐	
parentArticle_name	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_removed	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_size	int64		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_url	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	

Name	Data Type	Label	Required	Documentation
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
removed_1	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type_1	string		☐	
reporter_\$type_2	string		☐	
reporter_\$type_3	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
size_1	int64		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated_3	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type_1	string		☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
url_1	string		☐	
url	string	URL	☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.6 ChildArticleAttachmentsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: `NotRequired`

Base Path: `childArticles[*].attachments[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ChildArticleAttachmentsById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `ChildArticleAttachmentsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type_3	string		☐	
\$type	string		☐	
base64Content_1	string		☐	
base64Content	string	Base64 Content	☐	
charset_1	string		☐	
charset	string	Charset	☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created_3	int64		☐	
created	int64	Created	☐	
draft_1	boolean		☐	
draft	boolean	Draft	☐	
extension_1	string		☐	

Name	Data Type	Label	Required	Documentation
extension	string	Extension	☐	
externalArticle_\$type_1	string		☐	
externalArticle_\$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id_3	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
metaData_1	string		☐	
metaData	string	Metadata	☐	
mimeType_1	string		☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_\$type	string		☐	
parentArticle_base64Content	string		☐	
parentArticle_charset	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_draft	boolean		☐	
parentArticle_extension	string		☐	
parentArticle_externalArticle_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_metaData	string		☐	
parentArticle_mimeType	string		☐	
parentArticle_name	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_removed	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_size	int64		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_url	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
removed_1	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type_1	string		☐	
reporter_\$type_2	string		☐	
reporter_\$type_3	string		☐	
reporter_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
size_1	int64		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated_3	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type_1	string		☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
url_1	string		☐	
url	string	URL	☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	

Name	Data Type	Label	Required	Documentation
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.7 ChildArticleComments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: `NotRequired`

Base Path: `childArticles[*].comments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `ChildArticleComments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
externalArticle_\$type_1	string		☐	
externalArticle_\$type	string		☐	
externalArticle_id_1	string		☐	

Name	Data Type	Label	Required	Documentation
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_\$type	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_text	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type_2	string		☐	
reporter_\$type_3	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type_1	string		☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.8 ChildArticleCommentsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: `NotRequired`

Base Path: `childArticles[*].comments[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ChildArticleCommentsById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `ChildArticleCommentsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
externalArticle_\$type_1	string		☐	
externalArticle_\$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	

Name	Data Type	Label	Required	Documentation
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_\$type	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_text	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type_2	string		☐	
reporter_\$type_3	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type_1	string		☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.9 ChildArticles

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: `NotRequired`

Base Path: `childArticles[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `ChildArticles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	

Name	Data Type	Label	Required	Documentation
created_1	int64		☐	
created	int64	Created	☐	
externalArticle_\$type_1	string		☐	
externalArticle_\$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type_2	string		☐	
reporter_\$type_3	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type_1	string		☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.10 ChildArticlesById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: `NotRequired`

Base Path: `childArticles[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ChildArticlesById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `ChildArticlesById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created	int64	Created	☐	
externalArticle_\$type_1	string		☐	
externalArticle_\$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id	string	ID	☐	

Name	Data Type	Label	Required	Documentation
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type_2	string		☐	
reporter_\$type_3	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type_1	string		☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	

Name	Data Type	Label	Required	Documentation
visibility_id	string		☐	

6.1.11 ChildChildArticles

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: `NotRequired`

Base Path: `childArticles[*].childArticles[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `ChildChildArticles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content_4	string		☐	
content_5	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
externalArticle_\$type_1	string		☐	
externalArticle_\$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	

Name	Data Type	Label	Required	Documentation
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren_2	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar_2	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable_2	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal_2	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_\$type	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content_2	string		☐	
parentArticle_content_3	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren_2	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar_2	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_idReadable_2	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal_2	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary_2	string		☐	
parentArticle_summary_3	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type_2	string		☐	
reporter_\$type_3	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary_4	string		☐	
summary_5	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_\$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.12 ChildChildArticlesById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: /articles/{id}

Update YouTrack API URL: /articles/{id}

Delete YouTrack API URL: /articles/{id}

Field Selection Method: NotRequired

Base Path: childArticles[*].childArticles[*]

Select YouTrack API Operation: get /articles/{id}

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChildChildArticlesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function ChildChildArticlesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content_4	string		☐	
content_5	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
externalArticle_\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
externalArticle_\$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren_2	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar_2	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable_2	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal_2	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_\$type	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content_2	string		☐	
parentArticle_content_3	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren_2	boolean		☐	
parentArticle_hasChildren	boolean		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar_2	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable_2	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal_2	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary_2	string		☐	
parentArticle_summary_3	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type_2	string		☐	
reporter_\$type_3	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary_4	string		☐	
summary_5	string		☐	

Name	Data Type	Label	Required	Documentation
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type_1	string		☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type_3	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.13 CommentAttachments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: `NotRequired`

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `CommentAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>article_content</code>	string		☐	
<code>article_created</code>	int64		☐	
<code>article_hasChildren</code>	boolean		☐	
<code>article_hasStar</code>	boolean		☐	
<code>article_idReadable</code>	string		☐	
<code>article_ordinal</code>	int64		☐	
<code>article_summary</code>	string		☐	
<code>article_updated</code>	int64		☐	
<code>author_\$type</code>	string		☐	
<code>author_avatarUrl</code>	string		☐	
<code>author_banned</code>	boolean		☐	
<code>author_email</code>	string		☐	
<code>author_fullName</code>	string		☐	
<code>author_guest</code>	boolean		☐	
<code>author_id</code>	string		☐	
<code>author_jabberAccountName</code>	string		☐	
<code>author_login</code>	string		☐	
<code>author_online</code>	boolean		☐	
<code>author_ringId</code>	string		☐	
<code>base64Content</code>	string	Base64 Content	☐	
<code>charset</code>	string	Charset	☐	
<code>content_1</code>	string		☐	

Name	Data Type	Label	Required	Documentation
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
draft	boolean	Draft	☐	
extension	string	Extension	☐	
externalArticle_\$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
ordinal	int64	Ordinal	☐	
parentArticle_\$type	string		☐	
parentArticle_base64Content	string		☐	
parentArticle_charset	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created	int64		☐	
parentArticle_draft	boolean		☐	
parentArticle_extension	string		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_metaData	string		☐	
parentArticle_mimeType	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_name	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_removed	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_size	int64		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_url	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type_1	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary	string	Summary	☐	

Name	Data Type	Label	Required	Documentation
text	string	Text	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
url	string	URL	☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id	string		☐	

6.1.14 CommentAttachmentsByIssueId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: `NotRequired`

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CommentAttachmentsByIssueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CommentAttachmentsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
article_content	string		☐	
article_created	int64		☐	
article_hasChildren	boolean		☐	
article_hasStar	boolean		☐	
article_idReadable	string		☐	
article_ordinal	int64		☐	
article_summary	string		☐	
article_updated	int64		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	

Name	Data Type	Label	Required	Documentation
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
content_1	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
draft	boolean	Draft	☐	
extension	string	Extension	☐	
externalArticle_\$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
ordinal	int64	Ordinal	☐	
parentArticle_\$type	string		☐	
parentArticle_base64Content	string		☐	
parentArticle_charset	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created	int64		☐	
parentArticle_draft	boolean		☐	
parentArticle_extension	string		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_metaData	string		☐	
parentArticle_mimeType	string		☐	
parentArticle_name	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_removed	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_size	int64		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_url	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type_1	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
url	string	URL	☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id	string		☐	

6.1.15 Comments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: /articles

Delete YouTrack API URL: /articles

Field Selection Method: NotRequired

Base Path: comments[*]

Select YouTrack API Operation: get /articles

Table Function Columns

The columns of the table function `Comments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
article_content	string		☐	
article_created	int64		☐	
article_hasChildren	boolean		☐	
article_hasStar	boolean		☐	
article_idReadable	string		☐	
article_ordinal	int64		☐	
article_summary	string		☐	
article_updated	int64		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
content_1	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created	int64	Created	☐	
externalArticle_\$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	

Name	Data Type	Label	Required	Documentation
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id	string		☐	

6.1.16 CommentsByIssueId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: `NotRequired`

Base Path: `comments[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CommentsByIssueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CommentsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>article_content</code>	string		☐	
<code>article_created</code>	int64		☐	
<code>article_hasChildren</code>	boolean		☐	
<code>article_hasStar</code>	boolean		☐	
<code>article_idReadable</code>	string		☐	
<code>article_ordinal</code>	int64		☐	
<code>article_summary</code>	string		☐	
<code>article_updated</code>	int64		☐	
<code>author_\$type</code>	string		☐	
<code>author_avatarUrl</code>	string		☐	
<code>author_banned</code>	boolean		☐	

Name	Data Type	Label	Required	Documentation
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
content_1	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created	int64	Created	☐	
externalArticle_\$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_\$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_\$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_\$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_\$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type_1	string		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updatedBy_\$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
visibility_\$type_1	string		☐	
visibility_\$type_2	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id	string		☐	

6.1.17 GroupById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/groups/{id}`

Insert YouTrack API URL: `/groups/{id}`

Update YouTrack API URL: `/groups/{id}`

Delete YouTrack API URL: `/groups/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /groups/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `GroupById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `GroupById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id	string	ID	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_createdBy_\$type	string		☐	
teamForProject_createdBy_avatarUrl	string		☐	
teamForProject_createdBy_banned	boolean		☐	
teamForProject_createdBy_email	string		☐	
teamForProject_createdBy_fullName	string		☐	
teamForProject_createdBy_guest	boolean		☐	
teamForProject_createdBy_id	string		☐	
teamForProject_createdBy_jabberAccountName	string		☐	
teamForProject_createdBy_login	string		☐	
teamForProject_createdBy_online	boolean		☐	
teamForProject_createdBy_ringId	string		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_leader_\$type	string		☐	
teamForProject_leader_avatarUrl	string		☐	
teamForProject_leader_banned	boolean		☐	
teamForProject_leader_email	string		☐	
teamForProject_leader_fullName	string		☐	
teamForProject_leader_guest	boolean		☐	
teamForProject_leader_id	string		☐	
teamForProject_leader_jabberAccountName	string		☐	
teamForProject_leader_login	string		☐	
teamForProject_leader_online	boolean		☐	
teamForProject_leader_ringId	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	

Name	Data Type	Label	Required	Documentation
teamForProject_startingNumber	int64		☐	
teamForProject_team_\$type	string		☐	
teamForProject_team_allUsersGroup	boolean		☐	
teamForProject_team_icon	string		☐	
teamForProject_team_id	string		☐	
teamForProject_team_name	string		☐	
teamForProject_team_ringId	string		☐	
teamForProject_team_usersCount	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

6.1.18 Groups

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/groups`

Insert YouTrack API URL: `/groups`

Update YouTrack API URL: `/groups`

Delete YouTrack API URL: `/groups`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /groups`

Table Function Columns

The columns of the table function `Groups` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id	string	ID	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_createdBy_\$type	string		☐	
teamForProject_createdBy_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
teamForProject_createdBy_banned	boolean		☐	
teamForProject_createdBy_email	string		☐	
teamForProject_createdBy_fullName	string		☐	
teamForProject_createdBy_guest	boolean		☐	
teamForProject_createdBy_id	string		☐	
teamForProject_createdBy_jabberAccountName	string		☐	
teamForProject_createdBy_login	string		☐	
teamForProject_createdBy_online	boolean		☐	
teamForProject_createdBy_ringId	string		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_leader_\$type	string		☐	
teamForProject_leader_avatarUrl	string		☐	
teamForProject_leader_banned	boolean		☐	
teamForProject_leader_email	string		☐	
teamForProject_leader_fullName	string		☐	
teamForProject_leader_guest	boolean		☐	
teamForProject_leader_id	string		☐	
teamForProject_leader_jabberAccountName	string		☐	
teamForProject_leader_login	string		☐	
teamForProject_leader_online	boolean		☐	
teamForProject_leader_ringId	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_team_\$type	string		☐	
teamForProject_team_allUsersGroup	boolean		☐	
teamForProject_team_icon	string		☐	
teamForProject_team_id	string		☐	
teamForProject_team_name	string		☐	
teamForProject_team_ringId	string		☐	
teamForProject_team_usersCount	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

6.1.19 IssueLinkTypes

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueLinkTypes`

Insert YouTrack API URL: `/issueLinkTypes`

Update YouTrack API URL: `/issueLinkTypes`

Delete YouTrack API URL: `/issueLinkTypes`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueLinkTypes`

Table Function Columns

The columns of the table function `IssueLinkTypes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type</code>	string		☐	
<code>aggregation</code>	boolean	Aggregation	☐	
<code>directed</code>	boolean	Directed	☐	
<code>id</code>	string	ID	☐	
<code>localizedName</code>	string	Localized Name	☐	
<code>localizedSourceToTarget</code>	string	Localized Source to Target	☐	
<code>localizedTargetToSource</code>	string	Localized Target to Source	☐	
<code>name</code>	string	Name	☐	
<code>readOnly</code>	boolean	Read-only	☐	
<code>sourceToTarget</code>	string	Source to Target	☐	
<code>targetToSource</code>	string	Target to Source	☐	

6.1.20 IssueLinkTypesById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueLinkTypes/{id}`

Insert YouTrack API URL: `/issueLinkTypes/{id}`

Update YouTrack API URL: `/issueLinkTypes/{id}`

Delete YouTrack API URL: `/issueLinkTypes/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueLinkTypes/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueLinkTypesById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueLinkTypesById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
aggregation	boolean	Aggregation	☐	
directed	boolean	Directed	☐	
id	string	ID	☐	
localizedName	string	Localized Name	☐	
localizedSourceToTarget	string	Localized Source to Target	☐	
localizedTargetToSource	string	Localized Target to Source	☐	
name	string	Name	☐	
readOnly	boolean	Read-only	☐	
sourceToTarget	string	Source to Target	☐	
targetToSource	string	Target to Source	☐	

6.1.21 IssueTagAttachmentIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagAttachmentIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagAttachmentIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>author_\$type</code>	string		☐	
<code>author_avatarUrl</code>	string		☐	
<code>author_banned</code>	boolean		☐	

Name	Data Type	Label	Required	Documentation
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
comment_\$type	string		☐	
comment_created	int64		☐	
comment_deleted	boolean		☐	
comment_id	string		☐	
comment_text	string		☐	
comment_textPreview	string		☐	
comment_updated	int64		☐	
comment_usesMarkdown	boolean		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	

Name	Data Type	Label	Required	Documentation
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.22 IssueTagById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

6.1.23 IssueTagById2

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagById2`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagById2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.24 IssueTagCommentAttachmentIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: `NotRequired`

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagCommentAttachmentIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagCommentAttachmentIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.25 IssueTagCommentIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `comments[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagCommentIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagCommentIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	

Name	Data Type	Label	Required	Documentation
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updated_1	int64		☐	

Name	Data Type	Label	Required	Documentation
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.26 IssueTagCustomFieldIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `customFields[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagCustomFieldIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagCustomFieldIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
projectCustomField_\$type	string		☐	
projectCustomField_canBeEmpty	boolean		☐	
projectCustomField_emptyFieldText	string		☐	
projectCustomField_hasRunningJob	boolean		☐	
projectCustomField_id	string		☐	
projectCustomField_isPublic	boolean		☐	
projectCustomField_ordinal	int32		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	

Name	Data Type	Label	Required	Documentation
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.27 IssueTagIssueAttachments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: `NotRequired`

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssueAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	

Name	Data Type	Label	Required	Documentation
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyTo Email	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_starting Number	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.28 IssueTagIssueAttachmentsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagIssueAttachmentsById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagIssueAttachmentsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.29 IssueTagIssueById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagIssueById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagIssueById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>color_\$type</code>	string		☐	
<code>color_background</code>	string		☐	
<code>color_foreground</code>	string		☐	

Name	Data Type	Label	Required	Documentation
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	

Name	Data Type	Label	Required	Documentation
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.30 IssueTagIssueComments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssueComments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	

Name	Data Type	Label	Required	Documentation
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	

Name	Data Type	Label	Required	Documentation
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.31 IssueTagIssueCommentsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagIssueCommentsById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagIssueCommentsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
untagOnResolve	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.32 IssueTagIssueCustomFields

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: `NotRequired`

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssueCustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyTo Email	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_starting Number	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.33 IssueTagIssueLinks

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: `NotRequired`

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssueLinks` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	

Name	Data Type	Label	Required	Documentation
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortcodeName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortcodeName	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.34 IssueTagIssueLinksById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagIssueLinksById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagIssueLinksById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.35 IssueTagIssues

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: `NotRequired`

Base Path: `issues[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortcodeName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.36 IssueTagIssuesCustomFieldsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: `NotRequired`

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagIssuesCustomFieldsById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagIssuesCustomFieldsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.37 IssueTagIssuesTags

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: `NotRequired`

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssuesTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type_1	string		☐	
owner_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	

Name	Data Type	Label	Required	Documentation
summary	string	Summary	☐	
untagOnResolve_1	boolean		☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.38 IssueTagIssueTagsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagIssueTagsById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagIssueTagsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	

Name	Data Type	Label	Required	Documentation
draftOwnerRingId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type_1	string		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	

Name	Data Type	Label	Required	Documentation
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve_1	boolean		☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.39 IssueTagLinkIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `links[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagLinkIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagLinkIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	

Name	Data Type	Label	Required	Documentation
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
linkType_\$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	

Name	Data Type	Label	Required	Documentation
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.40 IssueTagLinkIssuesByTagId1

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `links[*].issues[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagLinkIssuesByTagId1`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagLinkIssuesByTagId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	

Name	Data Type	Label	Required	Documentation
draftOwnerRingId	string		☐	
externalIssue_type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_type_1	string		☐	
parent_type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	

Name	Data Type	Label	Required	Documentation
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_\$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	

Name	Data Type	Label	Required	Documentation
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	

Name	Data Type	Label	Required	Documentation
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	

Name	Data Type	Label	Required	Documentation
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.41 IssueTagLinkTrimmedIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: `NotRequired`

Base Path: `links[*].trimmedIssues[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagLinkTrimmedIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagLinkTrimmedIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_\$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type_1	string		☐	
parent_\$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	

Name	Data Type	Label	Required	Documentation
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	

Name	Data Type	Label	Required	Documentation
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	

Name	Data Type	Label	Required	Documentation
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.42 IssueTags: YouTrack Issue Tags

Catalog: YouTrack

Schema: Articles

Label: Issue Tags

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	

Name	Data Type	Label	Required	Documentation
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

6.1.43 TagIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `TagIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `TagIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

Name	Data Type	Label	Required	Documentation
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.44 TagIssuesByTagId2

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `TagIssuesByTagId2`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `TagIssuesByTagId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	

Name	Data Type	Label	Required	Documentation
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_\$type_1	string		☐	
parent_\$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	

Name	Data Type	Label	Required	Documentation
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_\$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	

Name	Data Type	Label	Required	Documentation
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

7 Schema: Backups

7.1 Tables

7.1.1 DatabaseBackupById

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/backups/{id}`

Insert YouTrack API URL: `/admin/databaseBackup/backups/{id}`

Update YouTrack API URL: `/admin/databaseBackup/backups/{id}`

Delete YouTrack API URL: `/admin/databaseBackup/backups/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/databaseBackup/backups/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `DatabaseBackupById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `DatabaseBackupById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
creationDate	int64	Creation Date	☐	
id	string	ID	☐	
link	string	Link	☐	
name	string	Name	☐	
size	int64	Size	☐	

7.1.2 DatabaseBackups

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/backups`

Insert YouTrack API URL: `/admin/databaseBackup/backups`

Update YouTrack API URL: `/admin/databaseBackup/backups`

Delete YouTrack API URL: /admin/databaseBackup/backups

Field Selection Method: NotRequired

Select YouTrack API Operation: get /admin/databaseBackup/backups

Table Function Columns

The columns of the table function DatabaseBackups are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
creationDate	int64	Creation Date	☐	
id	string	ID	☐	
link	string	Link	☐	
name	string	Name	☐	
size	int64	Size	☐	

7.1.3 DatabaseBackupSettingBackupStatuses

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the YouTrack API.

Select YouTrack API URL: /admin/databaseBackup/settings/backupStatus

Insert YouTrack API URL: /admin/databaseBackup/settings/backupStatus

Update YouTrack API URL: /admin/databaseBackup/settings/backupStatus

Delete YouTrack API URL: /admin/databaseBackup/settings/backupStatus

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/databaseBackup/settings/backupStatus

Table Function Columns

The columns of the table function DatabaseBackupSettingBackupStatuses are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
backupCancelled	boolean	Backup Cancelled	☐	
backupError_\$type	string		☐	
backupError_date	int64		☐	
backupError_errorMessage	string		☐	
backupError_id	string		☐	

Name	Data Type	Label	Required	Documentation
backupInProgress	boolean	Backup in Progress	☐	
id	string	ID	☐	

7.1.4 DatabaseBackupSettings

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings`

Insert YouTrack API URL: `/admin/databaseBackup/settings`

Update YouTrack API URL: `/admin/databaseBackup/settings`

Delete YouTrack API URL: `/admin/databaseBackup/settings`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /admin/databaseBackup/settings`

Table Function Columns

The columns of the table function `DatabaseBackupSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
archiveFormat	string	Archive Format	☐	
availableDiskSpace	int64	Available Disk Space	☐	
backupStatus_\$type	string		☐	
backupStatus_backupCancelled	boolean		☐	
backupStatus_backupError_\$type	string		☐	
backupStatus_backupError_date	int64		☐	
backupStatus_backupError_errorMessage	string		☐	
backupStatus_backupError_id	string		☐	
backupStatus_backupInProgress	boolean		☐	
backupStatus_id	string		☐	
cronExpression	string	Cron Expression	☐	
filesToKeep	int32	Files to Keep	☐	
id	string	ID	☐	
isOn	boolean	Is On	☐	
location	string	Location	☐	

7.1.5 NotifiedUserSavedQuerySettings

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings`

Insert YouTrack API URL: `/admin/databaseBackup/settings`

Update YouTrack API URL: `/admin/databaseBackup/settings`

Delete YouTrack API URL: `/admin/databaseBackup/settings`

Field Selection Method: NotRequired

Base Path: `notifiedUsers[*].savedQueries[*]`

Select YouTrack API Operation: `get /admin/databaseBackup/settings`

Table Function Columns

The columns of the table function `NotifiedUserSavedQuerySettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>archiveFormat</code>	string	Archive Format	☐	
<code>availableDiskSpace</code>	int64	Available Disk Space	☐	
<code>avatarUrl</code>	string	Avatar (URL)	☐	
<code>backupStatus_\$type</code>	string		☐	
<code>backupStatus_backupCancelled</code>	boolean		☐	
<code>backupStatus_backupError_\$type</code>	string		☐	
<code>backupStatus_backupError_date</code>	int64		☐	
<code>backupStatus_backupError_errorMessage</code>	string		☐	
<code>backupStatus_backupError_id</code>	string		☐	
<code>backupStatus_backupInProgress</code>	boolean		☐	
<code>backupStatus_id</code>	string		☐	
<code>banned</code>	boolean	Banned	☐	
<code>cronExpression</code>	string	Cron Expression	☐	
<code>email</code>	string	Email	☐	
<code>filesToKeep</code>	int32	Files to Keep	☐	
<code>fullName</code>	string	Full Name	☐	
<code>guest</code>	boolean	Guest	☐	
<code>id_1</code>	string		☐	

Name	Data Type	Label	Required	Documentation
id_2	string		☐	
id	string	ID	☐	
isOn	boolean	Is On	☐	
jabberAccountName	string	Jabber Account Name	☐	
location	string	Location	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

7.1.6 NotifiedUserSettings

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings`

Insert YouTrack API URL: `/admin/databaseBackup/settings`

Update YouTrack API URL: `/admin/databaseBackup/settings`

Delete YouTrack API URL: `/admin/databaseBackup/settings`

Field Selection Method: `NotRequired`

Base Path: `notifiedUsers[*]`

Select YouTrack API Operation: `get /admin/databaseBackup/settings`

Table Function Columns

The columns of the table function `NotifiedUserSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
archiveFormat	string	Archive Format	☐	
availableDiskSpace	int64	Available Disk Space	☐	
avatarUrl	string	Avatar (URL)	☐	
backupStatus_\$type	string		☐	
backupStatus_backupCancelled	boolean		☐	

Name	Data Type	Label	Required	Documentation
backupStatus_backupError_\$type	string		☐	
backupStatus_backupError_date	int64		☐	
backupStatus_backupError_errorMessage	string		☐	
backupStatus_backupError_id	string		☐	
backupStatus_backupInProgress	boolean		☐	
backupStatus_id	string		☐	
banned	boolean	Banned	☐	
cronExpression	string	Cron Expression	☐	
email	string	Email	☐	
filesToKeep	int32	Files to Keep	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isOn	boolean	Is On	☐	
jabberAccountName	string	Jabber Account Name	☐	
location	string	Location	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

7.1.7 NotifiedUserTagSettings

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings`

Insert YouTrack API URL: `/admin/databaseBackup/settings`

Update YouTrack API URL: `/admin/databaseBackup/settings`

Delete YouTrack API URL: `/admin/databaseBackup/settings`

Field Selection Method: `NotRequired`

Base Path: `notifiedUsers[*].tags[*]`

Select YouTrack API Operation: `get /admin/databaseBackup/settings`

Table Function Columns

The columns of the table function `NotifiedUserTagSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
archiveFormat	string	Archive Format	☐	
availableDiskSpace	int64	Available Disk Space	☐	
avatarUrl	string	Avatar (URL)	☐	
backupStatus_\$type	string		☐	
backupStatus_backupCancelled	boolean		☐	
backupStatus_backupError_\$type	string		☐	
backupStatus_backupError_date	int64		☐	
backupStatus_backupError_errorMessage	string		☐	
backupStatus_backupError_id	string		☐	
backupStatus_backupInProgress	boolean		☐	
backupStatus_id	string		☐	
banned	boolean	Banned	☐	
cronExpression	string	Cron Expression	☐	
email	string	Email	☐	
filesToKeep	int32	Files to Keep	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isOn	boolean	Is On	☐	
jabberAccountName	string	Jabber Account Name	☐	
location	string	Location	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

8 Schema: CustomFields

8.1 Tables

8.1.1 CustomFieldAggregatedUserSavedQueriesByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*].savedQueries[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldAggregatedUserSavedQueriesByUserBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldAggregatedUserSavedQueriesByUserBundleId` are shown below.

Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

8.1.2 CustomFieldAggregatedUsersByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: `NotRequired`

Base Path: `aggregatedUsers[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldAggregatedUsersByUserBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldAggregatedUsersByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

8.1.3 CustomFieldAggregatedUserTagsByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: `NotRequired`

Base Path: `aggregatedUsers[*].tags[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldAggregatedUserTagsByUserBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldAggregatedUserTagsByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	

Name	Data Type	Label	Required	Documentation
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

8.1.4 CustomFieldBuildBundles

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Field Selection Method: `NotRequired`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/build`

Table Function Columns

The columns of the table function `CustomFieldBuildBundles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.5 CustomFieldBuildByBuildBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Field Selection Method: `NotRequired`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/build/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldBuildByBuildBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldBuildByBuildBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.6 CustomFieldBuildByBuildBundleIdAndElementId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Field Selection Method: `NotRequired`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldBuildByBuildBundleIdAndElementId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
<code>buildBundleElementId</code>	string	☒		
<code>id</code>	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldBuildByBuildBundleIdAndElementId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type</code>	string		☐	
<code>assembleDate</code>	int64	Assembly Date	☐	
<code>bundle_\$type</code>	string		☐	

Name	Data Type	Label	Required	Documentation
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.7 CustomFieldBuildValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Field Selection Method: `NotRequired`

Base Path: `values[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/build`

Table Function Columns

The columns of the table function `CustomFieldBuildValues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
assembleDate	int64	Assembly Date	☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	

Name	Data Type	Label	Required	Documentation
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.8 CustomFieldBuildValuesByBuildBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/build/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldBuildValuesByBuildBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldBuildValuesByBuildBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
assembleDate	int64	Assembly Date	☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	

Name	Data Type	Label	Required	Documentation
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.9 CustomFieldBuildValuesByBuildBundleId1

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/build/{id}/values`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldBuildValuesByBuildBundleId1`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldBuildValuesByBuildBundleId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
assembleDate	int64	Assembly Date	☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.10 CustomFieldEnumBundleByEnumFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/enum/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldEnumBundleByEnumFieldBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldEnumBundleByEnumFieldBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.11 CustomFieldEnumBundles

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/enum`

Table Function Columns

The columns of the table function `CustomFieldEnumBundles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.12 CustomFieldEnumBundleValuesByEnumFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/enum/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldEnumBundleValuesByEnumFieldBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

CustomFieldEnumBundleValuesByEnumFieldBundleId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.13 CustomFieldEnumByEnumFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the YouTrack API.

Select YouTrack API URL: /admin/customFieldSettings/bundles/enum/{id}/values

Insert YouTrack API URL: /admin/customFieldSettings/bundles/enum/{id}/values

Update YouTrack API URL: /admin/customFieldSettings/bundles/enum/{id}/values

Delete YouTrack API URL: /admin/customFieldSettings/bundles/enum/{id}/values

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/enum/{id}/values

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldEnumByEnumFieldBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function CustomFieldEnumByEnumFieldBundleId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	

Name	Data Type	Label	Required	Documentation
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.14 CustomFieldEnumByEnumFieldBundleIdAndElementId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldEnumByEnumFieldBundleIdAndElementId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
enumBundleElementId	string	☒		

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldEnumByEnumFieldBundleIdAndElementId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.15 CustomFieldEnumValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/enum`

Table Function Columns

The columns of the table function `CustomFieldEnumValues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.16 CustomFieldIndividualUsers

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: /admin/customFieldSettings/bundles/user

Update YouTrack API URL: /admin/customFieldSettings/bundles/user

Delete YouTrack API URL: /admin/customFieldSettings/bundles/user

Field Selection Method: NotRequired

Base Path: individuals[*]

Select YouTrack API Operation: get /admin/customFieldSettings/bundles/user

Table Function Columns

The columns of the table function CustomFieldIndividualUsers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

8.1.17 CustomFieldIndividualUserSavedQueries

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the YouTrack API.

Select YouTrack API URL: /admin/customFieldSettings/bundles/user

Insert YouTrack API URL: /admin/customFieldSettings/bundles/user

Update YouTrack API URL: /admin/customFieldSettings/bundles/user

Delete YouTrack API URL: /admin/customFieldSettings/bundles/user

Field Selection Method: NotRequired

Base Path: `individuals[*].savedQueries[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldIndividualUserSavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>avatarUrl</code>	string	Avatar (URL)	☐	
<code>banned</code>	boolean	Banned	☐	
<code>email</code>	string	Email	☐	
<code>fullName</code>	string	Full Name	☐	
<code>guest</code>	boolean	Guest	☐	
<code>id_1</code>	string		☐	
<code>id_2</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>isUpdateable</code>	boolean	Is Updateable	☐	
<code>jabberAccountName</code>	string	Jabber Account Name	☐	
<code>login</code>	string	Login	☐	
<code>name</code>	string	Name	☐	
<code>online</code>	boolean	Online	☐	
<code>profiles_\$type</code>	string		☐	
<code>profiles_id</code>	string		☐	
<code>query</code>	string	Query	☐	
<code>ringId</code>	string	Ring ID	☐	

8.1.18 CustomFieldIndividualUserSavedQueriesByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `individuals[*].savedQueries[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldIndividualUserSavedQueriesByUserBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldIndividualUserSavedQueriesByUserBundleId` are shown below.

Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

8.1.19 CustomFieldIndividualUsersByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `individuals[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldIndividualUsersByUserBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldIndividualUsersByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

8.1.20 CustomFieldIndividualUserTags

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: `NotRequired`

Base Path: `individuals[*].tags[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldIndividualUserTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

8.1.21 CustomFieldIndividualUserTagsByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `individuals[*].tags[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldIndividualUserTagsByUserBundleId`. A value must be provided at all times for

required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldIndividualUserTagsByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

8.1.22 CustomFieldInstancesByCustomFieldPrototypeId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Field Selection Method: NotRequired

Base Path: `instances[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/customFields/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldInstancesByCustomFieldPrototypeId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldInstancesByCustomFieldPrototypeId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>aliases</code>	string	Aliases	☐	
<code>canBeEmpty</code>	boolean	Nullable	☐	

Name	Data Type	Label	Required	Documentation
condition_\$type	string		☐	
condition_id	string		☐	
emptyFieldText	string	Empty Field Text	☐	
field_\$type	string		☐	
field_aliases	string		☐	
field_hasRunningJob	boolean		☐	
field_id	string		☐	
field_isAutoAttached	boolean		☐	
field_isDisplayedInIssueList	boolean		☐	
field_isUpdateable	boolean		☐	
field_localizedName	string		☐	
field_name	string		☐	
field_ordinal	int32		☐	
fieldDefaults_\$type	string		☐	
fieldDefaults_canBeEmpty	boolean		☐	
fieldDefaults_emptyFieldText	string		☐	
fieldDefaults_id	string		☐	
fieldDefaults_isPublic	boolean		☐	
fieldDefaults_parent_\$type	string		☐	
fieldDefaults_parent_aliases	string		☐	
fieldDefaults_parent_hasRunningJob	boolean		☐	
fieldDefaults_parent_id	string		☐	
fieldDefaults_parent_isAutoAttached	boolean		☐	
fieldDefaults_parent_isDisplayedInIssueList	boolean		☐	
fieldDefaults_parent_isUpdateable	boolean		☐	
fieldDefaults_parent_localizedName	string		☐	
fieldDefaults_parent_name	string		☐	
fieldDefaults_parent_ordinal	int32		☐	
fieldType_\$type	string		☐	
fieldType_id	string		☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id	string	ID	☐	
isAutoAttached	boolean	Is Auto-attached	☐	
isDisplayedInIssueList	boolean	Is Displayed in Issue List	☐	
isPublic	boolean	Is Public	☐	
isUpdateable	boolean	Is Updateable	☐	

Name	Data Type	Label	Required	Documentation
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	

8.1.23 CustomFieldOwnedFieldByOwnedFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/ownedField/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldOwnedFieldByOwnedFieldBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldOwnedFieldByOwnedFieldBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.24 CustomFieldOwnedFieldByOwnedFieldBundleIdAndElementId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldOwnedFieldByOwnedFieldBundleIdAndElementId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
ownedBundleElementId	string	☒		

Table Function Columns

The columns of the table function `CustomFieldOwnedFieldByOwnedFieldBundleIdAndElementId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
owner_profiles_id	string		☐	
owner_ringId	string		☐	

8.1.25 CustomFieldOwnedFieldByValueId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/ownedField/{id}/values`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldOwnedFieldByValueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldOwnedFieldById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	

8.1.26 CustomFieldOwnedFields

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/ownedField

Table Function Columns

The columns of the table function CustomFieldOwnedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.27 CustomFieldOwnedFieldValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the YouTrack API.

Select YouTrack API URL: /admin/customFieldSettings/bundles/ownedField

Insert YouTrack API URL: /admin/customFieldSettings/bundles/ownedField

Update YouTrack API URL: /admin/customFieldSettings/bundles/ownedField

Delete YouTrack API URL: /admin/customFieldSettings/bundles/ownedField

Field Selection Method: NotRequired

Base Path: values[*]

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/ownedField

Table Function Columns

The columns of the table function CustomFieldOwnedFieldValues are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	

Name	Data Type	Label	Required	Documentation
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	

8.1.28 CustomFieldOwnedFieldValuesByOwnedFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Inventive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: /admin/customFieldSettings/bundles/ownedField/{id}

Insert YouTrack API URL: /admin/customFieldSettings/bundles/ownedField/{id}

Update YouTrack API URL: /admin/customFieldSettings/bundles/ownedField/{id}

Delete YouTrack API URL: /admin/customFieldSettings/bundles/ownedField/{id}

Field Selection Method: NotRequired

Base Path: values[*]

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/ownedField/{id}

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldOwnedFieldValuesByOwnedFieldBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function CustomFieldOwnedFieldValuesByOwnedFieldBundleId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	

Name	Data Type	Label	Required	Documentation
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	

8.1.29 CustomFields

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields`

Update YouTrack API URL: `/admin/customFieldSettings/customFields`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /admin/customFieldSettings/customFields`

Table Function Columns

The columns of the table function `CustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type</code>	string		☐	
<code>aliases</code>	string	Aliases	☐	
<code>fieldDefaults_\$type</code>	string		☐	
<code>fieldDefaults_canBeEmpty</code>	boolean		☐	
<code>fieldDefaults_emptyFieldText</code>	string		☐	
<code>fieldDefaults_id</code>	string		☐	
<code>fieldDefaults_isPublic</code>	boolean		☐	
<code>fieldDefaults_parent_\$type</code>	string		☐	
<code>fieldDefaults_parent_aliases</code>	string		☐	
<code>fieldDefaults_parent_hasRunningJob</code>	boolean		☐	
<code>fieldDefaults_parent_id</code>	string		☐	
<code>fieldDefaults_parent_isAutoAttached</code>	boolean		☐	
<code>fieldDefaults_parent_isDisplayedInIssueList</code>	boolean		☐	
<code>fieldDefaults_parent_isUpdateable</code>	boolean		☐	
<code>fieldDefaults_parent_localizedName</code>	string		☐	
<code>fieldDefaults_parent_name</code>	string		☐	
<code>fieldDefaults_parent_ordinal</code>	int32		☐	
<code>fieldType_\$type</code>	string		☐	
<code>fieldType_id</code>	string		☐	
<code>hasRunningJob</code>	boolean	Has Running Job	☐	
<code>id</code>	string	ID	☐	
<code>isAutoAttached</code>	boolean	Is Auto-attached	☐	
<code>isDisplayedInIssueList</code>	boolean	Is Displayed in Issue List	☐	

Name	Data Type	Label	Required	Documentation
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.30 CustomFieldsByCustomFieldPrototypeId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/customFields/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldsByCustomFieldPrototypeId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldsByCustomFieldPrototypeId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
aliases	string	Aliases	☐	
fieldDefaults_\$type	string		☐	
fieldDefaults_canBeEmpty	boolean		☐	
fieldDefaults_emptyFieldText	string		☐	
fieldDefaults_id	string		☐	
fieldDefaults_isPublic	boolean		☐	
fieldDefaults_parent_\$type	string		☐	
fieldDefaults_parent_aliases	string		☐	
fieldDefaults_parent_hasRunningJob	boolean		☐	
fieldDefaults_parent_id	string		☐	
fieldDefaults_parent_isAutoAttached	boolean		☐	
fieldDefaults_parent_isDisplayedInIssueList	boolean		☐	
fieldDefaults_parent_isUpdateable	boolean		☐	
fieldDefaults_parent_localizedName	string		☐	
fieldDefaults_parent_name	string		☐	
fieldDefaults_parent_ordinal	int32		☐	
fieldType_\$type	string		☐	
fieldType_id	string		☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
isAutoAttached	boolean	Is Auto-attached	☐	
isDisplayedInIssueList	boolean	Is Displayed in Issue List	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.31 CustomFieldsByCustomFieldPrototypeId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/fieldDefaults`

Insert YouTrack API URL: /admin/customFieldSettings/customFields/{id}/fieldDefaults

Update YouTrack API URL: /admin/customFieldSettings/customFields/{id}/fieldDefaults

Delete YouTrack API URL: /admin/customFieldSettings/customFields/{id}/fieldDefaults

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/customFieldSettings/customFields/{id}/fieldDefaults

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldsByCustomFieldPrototypeId2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function CustomFieldsByCustomFieldPrototypeId2 are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
canBeEmpty	boolean	Nullable	☐	
emptyFieldText	string	Empty Field Text	☐	
id	string	ID	☐	
isPublic	boolean	Is Public	☐	
parent_\$type	string		☐	
parent_aliases	string		☐	
parent_fieldDefaults_\$type	string		☐	
parent_fieldDefaults_canBeEmpty	boolean		☐	
parent_fieldDefaults_emptyFieldText	string		☐	

Name	Data Type	Label	Required	Documentation
parent_fieldDefaults_id	string		☐	
parent_fieldDefaults_isPublic	boolean		☐	
parent_fieldType_\$type	string		☐	
parent_fieldType_id	string		☐	
parent_hasRunningJob	boolean		☐	
parent_id	string		☐	
parent_isAutoAttached	boolean		☐	
parent_isDisplayedInIssueList	boolean		☐	
parent_isUpdateable	boolean		☐	
parent_localizedName	string		☐	
parent_name	string		☐	
parent_ordinal	int32		☐	

8.1.32 CustomFieldsByCustomFieldPrototypeld3

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/instances`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/instances`

Update YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/instances`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/instances`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/customFields/{id}/instances`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldsByCustomFieldPrototypeld3`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldsByCustomFieldPrototypeId3` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
canBeEmpty	boolean	Nullable	☐	
condition_\$type	string		☐	
condition_id	string		☐	
condition_parent_\$type	string		☐	
condition_parent_canBeEmpty	boolean		☐	
condition_parent_emptyFieldText	string		☐	
condition_parent_hasRunningJob	boolean		☐	
condition_parent_id	string		☐	
condition_parent_isPublic	boolean		☐	
condition_parent_ordinal	int32		☐	
emptyFieldText	string	Empty Field Text	☐	
field_\$type	string		☐	
field_aliases	string		☐	
field_fieldDefaults_\$type	string		☐	
field_fieldDefaults_canBeEmpty	boolean		☐	
field_fieldDefaults_emptyFieldText	string		☐	
field_fieldDefaults_id	string		☐	
field_fieldDefaults_isPublic	boolean		☐	
field_fieldType_\$type	string		☐	
field_fieldType_id	string		☐	
field_hasRunningJob	boolean		☐	
field_id	string		☐	
field_isAutoAttached	boolean		☐	
field_isDisplayedInIssueList	boolean		☐	
field_isUpdateable	boolean		☐	
field_localizedName	string		☐	
field_name	string		☐	
field_ordinal	int32		☐	
hasRunningJob	boolean	Has Running Job	☐	

Name	Data Type	Label	Required	Documentation
id	string	ID	☐	
isPublic	boolean	Is Public	☐	
ordinal	int32	Ordinal	☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	

Name	Data Type	Label	Required	Documentation
project_template	boolean		☐	

8.1.33 CustomFieldStateBundleById

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/state/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldStateBundleById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldStateBundleById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	

Name	Data Type	Label	Required	Documentation
isUpdateable	boolean	Is Updateable	☐	

8.1.34 CustomFieldStateBundles

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/state`

Table Function Columns

The columns of the table function `CustomFieldStateBundles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.35 CustomFieldStateBundleValues2ByStateBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/state/{id}/values`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldStateBundleValues2ByStateBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldStateBundleValues2ByStateBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
isResolved	boolean	Is Resolved	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	

Name	Data Type	Label	Required	Documentation
ordinal	int32	Ordinal	☐	

8.1.36 CustomFieldStateBundleValuesByStateBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/state/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldStateBundleValuesByStateBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldStateBundleValuesByStateBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isResolved	boolean	Is Resolved	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.37 CustomFieldStateByStateBundleIdAndElementId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}`

Insert YouTrack API URL: /admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}

Update YouTrack API URL: /admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}

Delete YouTrack API URL: /admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldStateByStateBundleIdAndElementId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
stateBundleElementId	string	☒		

Table Function Columns

The columns of the table function

CustomFieldStateByStateBundleIdAndElementId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
isResolved	boolean	Is Resolved	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.38 CustomFieldStateValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/state`

Table Function Columns

The columns of the table function `CustomFieldStateValues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>bundle_\$type_1</code>	string		☐	
<code>bundle_\$type</code>	string		☐	
<code>bundle_id_1</code>	string		☐	
<code>bundle_id</code>	string		☐	
<code>bundle_isUpdateable_1</code>	boolean		☐	
<code>bundle_isUpdateable</code>	boolean		☐	
<code>color_\$type_1</code>	string		☐	
<code>color_\$type</code>	string		☐	

Name	Data Type	Label	Required	Documentation
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isResolved	boolean	Is Resolved	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.39 CustomFieldUserBundles

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `groups[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUserBundles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

8.1.40 CustomFieldUserBundleUsers

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUserBundleUsers` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

8.1.41 CustomFieldUserBundleUserSavedQueries

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*].savedQueries[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUserBundleUserSavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	

Name	Data Type	Label	Required	Documentation
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

8.1.42 CustomFieldUserBundleUserTags

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*].tags[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUserBundleUserTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	

Name	Data Type	Label	Required	Documentation
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

8.1.43 CustomFieldUserByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUserByUserBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUserByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.44 CustomFieldUserByUserBundleId1

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUserByUserBundleId1`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUserByUserBundleId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.45 CustomFieldUserByUserBundleId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation:
get `/admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUserByUserBundleId2`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUserByUserBundleId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.46 CustomFieldUserGroupsByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `groups[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUserGroupsByUserBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUserGroupsByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

8.1.47 CustomFieldUserGroupsByUserBundleId1

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups`

Insert YouTrack API URL: /admin/customFieldSettings/bundles/user/{id}/groups

Update YouTrack API URL: /admin/customFieldSettings/bundles/user/{id}/groups

Delete YouTrack API URL: /admin/customFieldSettings/bundles/user/{id}/groups

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/user/{id}/groups

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserGroupsByUserBundleId1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function CustomFieldUserGroupsByUserBundleId1 are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id	string	ID	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_createdBy_\$type	string		☐	
teamForProject_createdBy_avatar Url	string		☐	
teamForProject_createdBy_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
teamForProject_createdBy_email	string		☐	
teamForProject_createdBy_fullName	string		☐	
teamForProject_createdBy_guest	boolean		☐	
teamForProject_createdBy_id	string		☐	
teamForProject_createdBy_jabberAccountName	string		☐	
teamForProject_createdBy_login	string		☐	
teamForProject_createdBy_online	boolean		☐	
teamForProject_createdBy_ringId	string		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_leader_\$type	string		☐	
teamForProject_leader_avatarUrl	string		☐	
teamForProject_leader_banned	boolean		☐	
teamForProject_leader_email	string		☐	
teamForProject_leader_fullName	string		☐	
teamForProject_leader_guest	boolean		☐	
teamForProject_leader_id	string		☐	
teamForProject_leader_jabberAccountName	string		☐	
teamForProject_leader_login	string		☐	
teamForProject_leader_online	boolean		☐	
teamForProject_leader_ringId	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_team_\$type	string		☐	
teamForProject_team_allUsersGroup	boolean		☐	
teamForProject_team_icon	string		☐	
teamForProject_team_id	string		☐	
teamForProject_team_name	string		☐	
teamForProject_team_ringId	string		☐	
teamForProject_team_usersCount	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

8.1.48 CustomFieldUsers

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUsers` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>isUpdateable</code>	boolean	Is Updateable	☐	

8.1.49 CustomFieldUsersByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: `NotRequired`

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	

Name	Data Type	Label	Required	Documentation
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.50 CustomFieldUsersByUserBundleId1

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId1`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>avatarUrl</code>	string	Avatar (URL)	☐	
<code>banned</code>	boolean	Banned	☐	
<code>email</code>	string	Email	☐	
<code>fullName</code>	string	Full Name	☐	
<code>guest</code>	boolean	Guest	☐	
<code>id_1</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>jabberAccountName</code>	string	Jabber Account Name	☐	
<code>login</code>	string	Login	☐	
<code>name</code>	string	Name	☐	
<code>online</code>	boolean	Online	☐	
<code>owner_\$type</code>	string		☐	
<code>owner_avatarUrl</code>	string		☐	
<code>owner_banned</code>	boolean		☐	
<code>owner_email</code>	string		☐	

Name	Data Type	Label	Required	Documentation
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.51 CustomFieldUsersByUserBundleId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId2`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.52 CustomFieldUsersByUserBundleId3

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId3`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId3` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

8.1.53 CustomFieldUsersByUserBundleId4

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId4`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId4` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_usePlainText Emails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

8.1.54 CustomFieldUsersByUserBundleId5

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId5`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
userId	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId5` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.55 CustomFieldUsersByUserBundleId6

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId6`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
userId	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId6` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.56 CustomFieldUsersByUserBundleId7

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: `NotRequired`

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId7`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
userId	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId7` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	

Name	Data Type	Label	Required	Documentation
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	

Name	Data Type	Label	Required	Documentation
wikifiedDescription	string	Wikified Description	☐	

8.1.57 CustomFieldUsersByUserBundleId8

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId8`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
userId	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId8` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.58 CustomFieldUsersByUserBundleId9

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: `NotRequired`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserBundleId9`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
userId	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId9` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	

Name	Data Type	Label	Required	Documentation
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

8.1.59 CustomFieldUsersByUserBundleIdAndGroupId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: /admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}

Insert YouTrack API URL: /admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}

Update YouTrack API URL: /admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}

Delete YouTrack API URL: /admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleIdAndGroupId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
userGroupId	string	☒		

Table Function Columns

The columns of the table function CustomFieldUsersByUserBundleIdAndGroupId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id	string	ID	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
teamForProject_createdBy_\$type	string		☐	
teamForProject_createdBy_avatar Url	string		☐	
teamForProject_createdBy_banned	boolean		☐	
teamForProject_createdBy_email	string		☐	
teamForProject_createdBy_fullNam e	string		☐	
teamForProject_createdBy_guest	boolean		☐	
teamForProject_createdBy_id	string		☐	
teamForProject_createdBy_jabber AccountName	string		☐	
teamForProject_createdBy_login	string		☐	
teamForProject_createdBy_online	boolean		☐	
teamForProject_createdBy_ringId	string		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_leader_\$type	string		☐	
teamForProject_leader_avatarUrl	string		☐	
teamForProject_leader_banned	boolean		☐	
teamForProject_leader_email	string		☐	
teamForProject_leader_fullName	string		☐	
teamForProject_leader_guest	boolean		☐	
teamForProject_leader_id	string		☐	
teamForProject_leader_jabberAcco untName	string		☐	
teamForProject_leader_login	string		☐	
teamForProject_leader_online	boolean		☐	
teamForProject_leader_ringId	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_team_\$type	string		☐	
teamForProject_team_allUsersGrou p	boolean		☐	
teamForProject_team_icon	string		☐	
teamForProject_team_id	string		☐	
teamForProject_team_name	string		☐	
teamForProject_team_ringId	string		☐	
teamForProject_team_usersCount	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

8.1.60 CustomFieldUsersByUserId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUsersByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.61 CustomFieldUserTagsByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers

Field Selection Method: NotRequired

Base Path: tags[*]

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserTagsByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function CustomFieldUserTagsByUserBundleId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	

Name	Data Type	Label	Required	Documentation
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

Name	Data Type	Label	Required	Documentation
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.62 CustomFieldUserTagsByUserBundleId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation:
get `/admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldUserTagsByUserBundleId2`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldUserTagsByUserBundleId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	

Name	Data Type	Label	Required	Documentation
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.63 CustomFieldVersionByProjectVersionBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/version/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldVersionByProjectVersionBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldVersionByProjectVersionBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.64 CustomFieldVersions

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/version`

Table Function Columns

The columns of the table function `CustomFieldVersions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.65 CustomFieldVersionValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Delete YouTrack API URL: /admin/customFieldSettings/bundles/version

Field Selection Method: NotRequired

Base Path: values[*]

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/version

Table Function Columns

The columns of the table function CustomFieldVersionValues are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
archived	boolean	Archived	☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
released	boolean	Released	☐	

Name	Data Type	Label	Required	Documentation
releaseDate	int64	Release Date	☐	

8.1.66 CustomFieldVersionValuesByProjectVersionBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/version/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldVersionValuesByProjectVersionBundleId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

`CustomFieldVersionValuesByProjectVersionBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
archived	boolean	Archived	☐	
bundle_\$type_1	string		☐	
bundle_\$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_\$type_1	string		☐	
color_\$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
released	boolean	Released	☐	
releaseDate	int64	Release Date	☐	

8.1.67 CustomFieldVersionValuesByProjectVersionBundleId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: /admin/customFieldSettings/bundles/version/{id}/values

Insert YouTrack API URL: /admin/customFieldSettings/bundles/version/{id}/values

Update YouTrack API URL: /admin/customFieldSettings/bundles/version/{id}/values

Delete YouTrack API URL: /admin/customFieldSettings/bundles/version/{id}/values

Field Selection Method: NotRequired

Select YouTrack API Operation:

get /admin/customFieldSettings/bundles/version/{id}/values

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldVersionValuesByProjectVersionBundleId2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select \* from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function

CustomFieldVersionValuesByProjectVersionBundleId2 are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
archived	boolean	Archived	☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	

Name	Data Type	Label	Required	Documentation
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	
released	boolean	Released	☐	
releaseDate	int64	Release Date	☐	

8.1.68 CustomFieldVersionValuesByProjectVersionBundleId3

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:

`get /admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldVersionValuesByProjectVersionBundleId3`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		
versionBundleElementId	string	☒		

Table Function Columns

The columns of the table function `CustomFieldVersionValuesByProjectVersionBundleId3` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
archived	boolean	Archived	☐	
bundle_\$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	
released	boolean	Released	☐	
releaseDate	int64	Release Date	☐	

8.1.69 InstanceCustomFields

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields`

Update YouTrack API URL: `/admin/customFieldSettings/customFields`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields`

Field Selection Method: `NotRequired`

Base Path: `instances[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/customFields`

Table Function Columns

The columns of the table function `InstanceCustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
aliases	string	Aliases	☐	
canBeEmpty	boolean	Nullable	☐	
condition_\$type	string		☐	
condition_id	string		☐	
emptyFieldText	string	Empty Field Text	☐	
field_\$type	string		☐	
field_aliases	string		☐	
field_hasRunningJob	boolean		☐	
field_id	string		☐	
field_isAutoAttached	boolean		☐	
field_isDisplayedInIssueList	boolean		☐	
field_isUpdateable	boolean		☐	
field_localizedName	string		☐	
field_name	string		☐	
field_ordinal	int32		☐	
fieldDefaults_\$type	string		☐	
fieldDefaults_canBeEmpty	boolean		☐	
fieldDefaults_emptyFieldText	string		☐	
fieldDefaults_id	string		☐	
fieldDefaults_isPublic	boolean		☐	
fieldDefaults_parent_\$type	string		☐	
fieldDefaults_parent_aliases	string		☐	
fieldDefaults_parent_hasRunningJob	boolean		☐	
fieldDefaults_parent_id	string		☐	
fieldDefaults_parent_isAutoAttached	boolean		☐	
fieldDefaults_parent_isDisplayedInIssueList	boolean		☐	
fieldDefaults_parent_isUpdateable	boolean		☐	
fieldDefaults_parent_localizedName	string		☐	
fieldDefaults_parent_name	string		☐	
fieldDefaults_parent_ordinal	int32		☐	
fieldType_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
fieldType_id	string		☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id	string	ID	☐	
isAutoAttached	boolean	Is Auto-attached	☐	
isDisplayedInIssueList	boolean	Is Displayed in Issue List	☐	
isPublic	boolean	Is Public	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	

8.1.70 Types

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/types`

Insert YouTrack API URL: `/admin/customFieldSettings/types`

Update YouTrack API URL: `/admin/customFieldSettings/types`

Delete YouTrack API URL: `/admin/customFieldSettings/types`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/customFieldSettings/types`

Table Function Columns

The columns of the table function `Types` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	

9 Schema: Issues

9.1 Tables

9.1.1 AttachmentById

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: `NotRequired`

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `AttachmentById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `AttachmentById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
comment_\$type	string		☐	
comment_created	int64		☐	
comment_deleted	boolean		☐	
comment_id	string		☐	
comment_text	string		☐	
comment_textPreview	string		☐	
comment_updated	int64		☐	
comment_usesMarkdown	boolean		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceTarget	string		☐	

Name	Data Type	Label	Required	Documentation
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	

Name	Data Type	Label	Required	Documentation
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.2 Attachments

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `Attachments`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p> <p>To show more than one custom field, use this parameter several times.</p> <p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `Attachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
comment_\$type	string		☐	
comment_created	int64		☐	
comment_deleted	boolean		☐	
comment_id	string		☐	
comment_text	string		☐	
comment_textPreview	string		☐	
comment_updated	int64		☐	
comment_usesMarkdown	boolean		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	

Name	Data Type	Label	Required	Documentation
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.3 CommentAttachments

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CommentAttachments`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p> <p>To show more than one custom field, use this parameter several times.</p> <p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `CommentAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	

Name	Data Type	Label	Required	Documentation
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	

Name	Data Type	Label	Required	Documentation
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	

Name	Data Type	Label	Required	Documentation
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.4 CommentAttachmentsByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the `table NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CommentAttachmentsByIssueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CommentAttachmentsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	

Name	Data Type	Label	Required	Documentation
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	

Name	Data Type	Label	Required	Documentation
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.5 Comments

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Base Path: `comments[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `Comments`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p><p>To show more than one custom field, use this parameter several times.</p><p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `Comments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	

Name	Data Type	Label	Required	Documentation
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.6 CommentsByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `comments[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CommentsByIssueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CommentsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>author_\$type</code>	string		☐	

Name	Data Type	Label	Required	Documentation
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	

Name	Data Type	Label	Required	Documentation
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type_1	string		☐	
visibility_\$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	

Name	Data Type	Label	Required	Documentation
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.7 CustomFields

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Base Path: `customFields[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFields`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than

Name	Data Type	Required	Default Value	Documentation
				one custom field, use this parameter several times.
query	string	☐		Issues search query. Read more about search syntax here: https://www.jetbrains.com/help/youtrack/incloud/?Search-and-Command-Attributes Search Query Reference

Table Function Columns

The columns of the table function `CustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	

Name	Data Type	Label	Required	Documentation
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
projectCustomField_\$type	string		☐	
projectCustomField_canBeEmpty	boolean		☐	
projectCustomField_emptyFieldText	string		☐	
projectCustomField_hasRunningJob	boolean		☐	
projectCustomField_id	string		☐	
projectCustomField_isPublic	boolean		☐	
projectCustomField_ordinal	int32		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.8 CustomFieldsByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `customFields[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `CustomFieldsByIssueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `CustomFieldsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	

Name	Data Type	Label	Required	Documentation
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
projectCustomField_\$type	string		☐	
projectCustomField_canBeEmpty	boolean		☐	
projectCustomField_emptyFieldText	string		☐	

Name	Data Type	Label	Required	Documentation
projectCustomField_hasRunningJob	boolean		☐	
projectCustomField_id	string		☐	
projectCustomField_isPublic	boolean		☐	
projectCustomField_ordinal	int32		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	

Name	Data Type	Label	Required	Documentation
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.9 IssueById

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	

Name	Data Type	Label	Required	Documentation
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.10 IssueLinksByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}/links`

Insert YouTrack API URL: `/issues/{id}/links`

Update YouTrack API URL: `/issues/{id}/links`

Delete YouTrack API URL: `/issues/{id}/links`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issues/{id}/links`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueLinksByIssueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueLinksByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
direction	string	Direction	☐	
id	string	ID	☐	
linkType_\$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	

9.1.11 Issues

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `Issues`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p> <p>To show more than one custom field, use this parameter several times.</p> <p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `Issues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	

Name	Data Type	Label	Required	Documentation
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	

Name	Data Type	Label	Required	Documentation
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.12 IssueTags: YouTrack Issue Tags

Catalog: YouTrack

Schema: Issues

Label: Issue Tags

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTags`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p><p>To show more than one custom field, use this parameter several times.</p><p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `IssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_\$type_1	string		☐	
parent_\$type	string		☐	
parent_commentsCount	int32		☐	

Name	Data Type	Label	Required	Documentation
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_\$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	

Name	Data Type	Label	Required	Documentation
subtasks_w ikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Dow n	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	

Name	Data Type	Label	Required	Documentation
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.13 LinkById

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the `table NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `links[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `LinkById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `LinkById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
linkType_\$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	

Name	Data Type	Label	Required	Documentation
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.14 LinkIssues

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Base Path: `links[*].issues[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `LinkIssues`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p> <p>To show more than one custom field, use this parameter several times.</p> <p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `LinkIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_\$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	

Name	Data Type	Label	Required	Documentation
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type_1	string		☐	
parent_\$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_\$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	

Name	Data Type	Label	Required	Documentation
wikifiedDescription	string	Wikified Description	☐	

9.1.15 LinkIssuesByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `links[*].issues[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `LinkIssuesByIssueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `LinkIssuesByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
\$type_2	string		☐	
\$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_\$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	

Name	Data Type	Label	Required	Documentation
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type_1	string		☐	
parent_\$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_\$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	

Name	Data Type	Label	Required	Documentation
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	

Name	Data Type	Label	Required	Documentation
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.16 Links

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Base Path: `links[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `Links`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p><p>To show more than one custom field, use this parameter several

Name	Data Type	Required	Default Value	Documentation
				times.</p><p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `Links` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	

Name	Data Type	Label	Required	Documentation
linkType_\$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	

Name	Data Type	Label	Required	Documentation
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.17 LinkTrimmedIssues

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Base Path: `links[*].trimmedIssues[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `LinkTrimmedIssues`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p><p>To show more than one custom field, use this parameter several times.</p><p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `LinkTrimmedIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type_1	string		☐	
parent_\$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	

Name	Data Type	Label	Required	Documentation
parent_w ikifiedDescription	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccount Name	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountNam e	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	

Name	Data Type	Label	Required	Documentation
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.18 LinkTrimmedIssuesByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: `NotRequired`

Base Path: `links[*].trimmedIssues[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `LinkTrimmedIssuesByIssueId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `LinkTrimmedIssuesByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_\$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
parent_\$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	

Name	Data Type	Label	Required	Documentation
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	

Name	Data Type	Label	Required	Documentation
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.19 TagById

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: `NotRequired`

Base Path: `tags[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `TagById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour.

Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `TagById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	

Name	Data Type	Label	Required	Documentation
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.20 TagIssuesByTagId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: `NotRequired`

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `TagIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `TagIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_\$type_1	string		☐	
parent_\$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	

Name	Data Type	Label	Required	Documentation
parent_isDraft	boolean		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_\$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	

Name	Data Type	Label	Required	Documentation
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikiifiedDescription	string		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_\$type_1	string		☐	
subtasks_\$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Dow n	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
w atchers_\$type	string		☐	
w atchers_hasStar	boolean		☐	
w atchers_id	string		☐	
w ikifiedDescription_1	string		☐	
w ikifiedDescription	string	Wikified Description	☐	

9.1.21 Tags

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: `NotRequired`

Base Path: `tags[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `Tags`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		<p>The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them.</p> <p>To show more than one custom field, use this parameter several times.</p> <p>See Sample 2 for reference.</p>
query	string	☐		Issues search query. Read more about search syntax here: <a href="https://www.jetbrains.com/help/youtrack/incloud/?Search-

Name	Data Type	Required	Default Value	Documentation
				and-Command-Attributes">Search Query Reference

Table Function Columns

The columns of the table function `Tags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_\$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	

Name	Data Type	Label	Required	Documentation
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_\$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_\$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	

Name	Data Type	Label	Required	Documentation
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_\$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_\$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_\$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_id	string		☐	
subtasks_linkType_\$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_\$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

10 Schema: Native

10.1 Tables

10.1.1 NATIVEPLATFORMSCALARREQUESTS: YouTrack Native Platform Scalar Requests

Direct access to native API.

Catalog: YouTrack

Schema: Native

Alias: npt

Label: Native Platform Scalar Requests

Documentation:

The NativePlatformScalarRequests table provides direct access to the native API protocol over an established connection to the YouTrack API server. It will contain a new row for every row inserted with a native API request in PAYLOAD_TEXT with the results of unaltered forwarding of the payload to the YouTrack API server.

Retrieve: true

Insert: true

Update: false

Delete: false

View Columns

The columns of the view NATIVEPLATFORMSCALARREQUESTS are shown below. Each column has an SQL data type. A new non-null value must be provided for every required column at all times during insert.

Name	Data Type	Label	Required	Documentation
BLOB_PREFERRED	boolean	BLOB Preferred	☒	Indicator whether a BLOB result is preferred over text.
BOL_RESPONSE_CACHE_MAX_AGE_SEC	int32	Response Cache Maximum Age (sec)	☐	Maximum age in seconds of Bridge Online response cache entries to be used.
CONTENT_TYPE	string(240)	Content Type	☐	
DATE_ENDED	datetime	End Date	☒	
DATE_STARTED	datetime	Start Date	☒	
DRY_RUN	boolean	Run without Actions	☒	
DURATION_MS	int32	Duration (ms)	☒	
ERROR_MESSAGE_CODE	string(30)	Error Message Code	☐	
ERROR_MESSAGE_TEXT	string(32000)	Error Message Text	☐	
FAIL_ON_ERROR	boolean	Fail on Error	☒	Whether to raise an exception when processing the native request triggered an error from the provider.
HTTP_DISK_CACHE_MAX_AGE_SEC	int32	HTTP Disk Cache Maximum Age (sec)	☐	Maximum age in seconds of HTTP disk cache entries to be used.
HTTP_DISK_CACHE_SAVE	boolean	Save HTTP Disk Cache	☐	Whether results can be stored in HTTP disk cache.
HTTP_DISK_CACHE_USE	boolean	Use HTTP Disk Cache	☐	Whether results can be fetched from HTTP disk cache.
HTTP_MEMORY_CACHE_MAX_AGE_SEC	int32	HTTP Memory Cache Maximum Age (sec)	☐	Maximum age in seconds of HTTP memory cache entries to be used.
HTTP_MEMORY_CACHE_SAVE	boolean	Save HTTP Memory Cache	☐	Whether results can be stored in HTTP memory cache.
HTTP_MEMORY_CACHE_USE	boolean	Use HTTP Memory Cache	☐	Whether results can be fetched from HTTP memory cache.
HTTP_METHOD	string(30)	HTTP Method	☐	
HTTP_STATUS_CODE	int16	HTTP Status Code	☐	
ORIG_SYSTEM_GROUP	string(4000)	Original System Group	☐	
ORIG_SYSTEM_REFERENCE	string(4000)	Original System Reference	☐	
PAYLOAD_TEXT	string	Payload	☐	
RESULT_BLOB	byte[]	Result BLOB	☐	
RESULT_DATE_TIME_UTC	datetime		☐	
RESULT_NUMBER	decimal		☐	
RESULT_TEXT	string	Result Text	☐	
SUCCESSFUL	boolean	Successful	☒	
TIMEOUT_SEC	int32	Timeout (sec)	☐	Timeout in seconds.
TRANSACTION_ID	int32	Transaction ID	☒	Incrementing ID of the transaction.
URL	string(4000)	URL	☐	

11 Schema: SavedQueries

11.1 Tables

11.1.1 IssueAttachmentsBySavedQueryId

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueAttachmentsBySavedQueryId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueAttachmentsBySavedQueryId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	

Name	Data Type	Label	Required	Documentation
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	

Name	Data Type	Label	Required	Documentation
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.2 IssueByld

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: `NotRequired`

Base Path: `issues[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueByld`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.3 IssueCommentsBySavedQueryId

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueCommentsBySavedQueryId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueCommentsBySavedQueryId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortcodeName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.4 IssueCustomFieldsBySavedQueryId

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: `NotRequired`

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueCustomFieldsBySavedQueryId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueCustomFieldsBySavedQueryId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	
<code>draftOwner_\$type</code>	string		☐	
<code>draftOwner_avatarUrl</code>	string		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	

Name	Data Type	Label	Required	Documentation
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.5 Issues

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: `NotRequired`

Base Path: `issues[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `Issues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	

Name	Data Type	Label	Required	Documentation
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.6 IssuesAttachments

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: `NotRequired`

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>base64Content</code>	string	Base64 Content	☐	
<code>charset</code>	string	Charset	☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created_1</code>	int64		☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	
<code>draft</code>	boolean	Draft	☐	
<code>draftOwner_\$type</code>	string		☐	
<code>draftOwner_avatarUrl</code>	string		☐	
<code>draftOwner_banned</code>	boolean		☐	
<code>draftOwner_email</code>	string		☐	
<code>draftOwner_fullName</code>	string		☐	
<code>draftOwner_guest</code>	boolean		☐	
<code>draftOwner_id</code>	string		☐	
<code>draftOwner_jabberAccountName</code>	string		☐	
<code>draftOwner_login</code>	string		☐	
<code>draftOwner_online</code>	boolean		☐	
<code>draftOwner_ringId</code>	string		☐	
<code>extension</code>	string	Extension	☐	
<code>externalIssue_\$type</code>	string		☐	
<code>externalIssue_id</code>	string		☐	
<code>externalIssue_key</code>	string		☐	
<code>externalIssue_name</code>	string		☐	
<code>externalIssue_url</code>	string		☐	
<code>id_1</code>	string		☐	
<code>id_2</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>idReadable</code>	string	Readable ID	☐	

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortcode	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	

Name	Data Type	Label	Required	Documentation
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.7 IssuesComments

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: `NotRequired`

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesComments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created_1</code>	int64		☐	
<code>created</code>	int64	Created	☐	
<code>deleted</code>	boolean	Deleted	☐	
<code>description</code>	string	Description	☐	
<code>draftOwner_\$type</code>	string		☐	
<code>draftOwner_avatarUrl</code>	string		☐	
<code>draftOwner_banned</code>	boolean		☐	
<code>draftOwner_email</code>	string		☐	
<code>draftOwner_fullName</code>	string		☐	
<code>draftOwner_guest</code>	boolean		☐	
<code>draftOwner_id</code>	string		☐	
<code>draftOwner_jabberAccountName</code>	string		☐	
<code>draftOwner_login</code>	string		☐	
<code>draftOwner_online</code>	boolean		☐	
<code>draftOwner_ringId</code>	string		☐	
<code>externalIssue_\$type</code>	string		☐	
<code>externalIssue_id</code>	string		☐	
<code>externalIssue_key</code>	string		☐	
<code>externalIssue_name</code>	string		☐	
<code>externalIssue_url</code>	string		☐	
<code>id_1</code>	string		☐	
<code>id_2</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>idReadable</code>	string	Readable ID	☐	
<code>isDraft</code>	boolean	Is Draft	☐	

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.8 IssuesCustomFields

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: `NotRequired`

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesCustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	
<code>draftOwner_\$type</code>	string		☐	
<code>draftOwner_avatarUrl</code>	string		☐	
<code>draftOwner_banned</code>	boolean		☐	
<code>draftOwner_email</code>	string		☐	
<code>draftOwner_fullName</code>	string		☐	
<code>draftOwner_guest</code>	boolean		☐	
<code>draftOwner_id</code>	string		☐	
<code>draftOwner_jabberAccountName</code>	string		☐	
<code>draftOwner_login</code>	string		☐	
<code>draftOwner_online</code>	boolean		☐	
<code>draftOwner_ringId</code>	string		☐	
<code>externalIssue_\$type</code>	string		☐	
<code>externalIssue_id</code>	string		☐	
<code>externalIssue_key</code>	string		☐	
<code>externalIssue_name</code>	string		☐	
<code>externalIssue_url</code>	string		☐	
<code>id_1</code>	string		☐	
<code>id_2</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>idReadable</code>	string	Readable ID	☐	
<code>isDraft</code>	boolean	Is Draft	☐	
<code>name_1</code>	string		☐	
<code>name</code>	string	Name	☐	
<code>numberInProject</code>	int64	Number in Project	☐	
<code>owner_\$type</code>	string		☐	
<code>owner_avatarUrl</code>	string		☐	
<code>owner_banned</code>	boolean		☐	
<code>owner_email</code>	string		☐	

Name	Data Type	Label	Required	Documentation
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.9 IssuesLinks

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: `NotRequired`

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesLinks` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	

Name	Data Type	Label	Required	Documentation
\$type_2	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	

Name	Data Type	Label	Required	Documentation
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.10 IssuesLinksById

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssuesLinksById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssuesLinksById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.11 IssuesTags

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: `NotRequired`

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type_1	string		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	

Name	Data Type	Label	Required	Documentation
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortcodeName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.12 IssueTagsBySavedQueryId

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `IssueTagsBySavedQueryId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `IssueTagsBySavedQueryId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	

Name	Data Type	Label	Required	Documentation
owner_\$type_1	string		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	

Name	Data Type	Label	Required	Documentation
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archiveId	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.13 SavedQueries: YouTrack Saved Queries

Catalog: YouTrack

Schema: SavedQueries

Label: Saved Queries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `SavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
query	string	Query	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

11.1.14 SavedQueryById

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SavedQueryById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SavedQueryById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
query	string	Query	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

12 Schema: Users

12.1 Tables

12.1.1 IssueTags: YouTrack Issue Tags

Catalog: YouTrack

Schema: Users

Label: Issue Tags

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: `NotRequired`

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `IssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>avatarUrl</code>	string	Avatar (URL)	☐	
<code>banned</code>	boolean	Banned	☐	
<code>color_\$type</code>	string		☐	
<code>color_background</code>	string		☐	
<code>color_foreground</code>	string		☐	
<code>color_id</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	
<code>email</code>	string	Email	☐	
<code>fullName</code>	string	Full Name	☐	
<code>guest</code>	boolean	Guest	☐	
<code>id_1</code>	string		☐	
<code>id_2</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>idReadable</code>	string	Readable ID	☐	
<code>isDraft</code>	boolean	Is Draft	☐	
<code>jabberAccountName</code>	string	Jabber Account Name	☐	
<code>login</code>	string	Login	☐	
<code>name</code>	string	Name	☐	
<code>numberInProject</code>	int64	Number in Project	☐	
<code>online</code>	boolean	Online	☐	

Name	Data Type	Label	Required	Documentation
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.2 Me

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `Me` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	

Name	Data Type	Label	Required	Documentation
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

12.1.3 MyIssueTags

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: `NotRequired`

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `MyIssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>avatarUrl</code>	string	Avatar (URL)	☐	
<code>banned</code>	boolean	Banned	☐	
<code>color_\$type</code>	string		☐	
<code>color_background</code>	string		☐	
<code>color_foreground</code>	string		☐	
<code>color_id</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	
<code>email</code>	string	Email	☐	
<code>fullName</code>	string	Full Name	☐	
<code>guest</code>	boolean	Guest	☐	
<code>id_1</code>	string		☐	
<code>id_2</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>idReadable</code>	string	Readable ID	☐	
<code>isDraft</code>	boolean	Is Draft	☐	
<code>jabberAccountName</code>	string	Jabber Account Name	☐	
<code>login</code>	string	Login	☐	
<code>name</code>	string	Name	☐	
<code>numberInProject</code>	int64	Number in Project	☐	
<code>online</code>	boolean	Online	☐	

Name	Data Type	Label	Required	Documentation
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.4 MySavedQueries

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: `NotRequired`

Base Path: `savedQueries[*]`

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `MySavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.5 MySavedQueriesIssues

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: `NotRequired`

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `MySavedQueriesIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

Name	Data Type	Label	Required	Documentation
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.6 MyTags

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: `NotRequired`

Base Path: `tags[*]`

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `MyTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type</code>	string		☐	
<code>avatarUrl</code>	string	Avatar (URL)	☐	
<code>banned</code>	boolean	Banned	☐	
<code>color_\$type</code>	string		☐	
<code>color_background</code>	string		☐	
<code>color_foreground</code>	string		☐	
<code>color_id</code>	string		☐	
<code>email</code>	string	Email	☐	
<code>fullName</code>	string	Full Name	☐	
<code>guest</code>	boolean	Guest	☐	
<code>id_1</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>jabberAccountName</code>	string	Jabber Account Name	☐	
<code>login</code>	string	Login	☐	
<code>name</code>	string	Name	☐	
<code>online</code>	boolean	Online	☐	

Name	Data Type	Label	Required	Documentation
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.7 ProfileTimeTrackingsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/profiles/timetracking`

Insert YouTrack API URL: `/users/{id}/profiles/timetracking`

Update YouTrack API URL: `/users/{id}/profiles/timetracking`

Delete YouTrack API URL: `/users/{id}/profiles/timetracking`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/profiles/timetracking`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `ProfileTimeTrackingsByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `ProfileTimeTrackingsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
periodFormat_\$type	string		☐	
periodFormat_id	string		☐	

12.1.8 SavedQueries: YouTrack Saved Queries

Catalog: YouTrack

Schema: Users

Label: Saved Queries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: `NotRequired`

Base Path: `savedQueries[*]`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `SavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	

Name	Data Type	Label	Required	Documentation
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_usePlainText Emails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.9 SavedQueryById

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SavedQueryById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SavedQueryById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_usersCount	int64		☐	

12.1.10 SavedQueryIssues

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: `NotRequired`

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `SavedQueryIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	

Name	Data Type	Label	Required	Documentation
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.11 SavedQueryIssuesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: `NotRequired`

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `SavedQueryIssuesByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `SavedQueryIssuesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.12 TagById

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: `NotRequired`

Base Path: `tags[*]`

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `TagById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `TagById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	

Name	Data Type	Label	Required	Documentation
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.13 TagIssuesByTagId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `TagIssuesByTagId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `TagIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

Name	Data Type	Label	Required	Documentation
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.14 Tags

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: `NotRequired`

Base Path: `tags[*]`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `Tags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	

Name	Data Type	Label	Required	Documentation
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.15 UserById

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserById`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	

Name	Data Type	Label	Required	Documentation
profiles_notifications_usePlainText Emails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

12.1.16 UserGeneralProfilesBySprintId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/profiles/general`

Insert YouTrack API URL: `/users/{id}/profiles/general`

Update YouTrack API URL: `/users/{id}/profiles/general`

Delete YouTrack API URL: `/users/{id}/profiles/general`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/profiles/general`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserGeneralProfilesBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserGeneralProfilesBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
dateFieldFormat_\$type	string		☐	
dateFieldFormat_datePattern	string		☐	
dateFieldFormat_id	string		☐	
dateFieldFormat_pattern	string		☐	
dateFieldFormat_presentation	string		☐	
id	string	ID	☐	
locale_\$type	string		☐	
locale_community	boolean		☐	
locale_id	string		☐	
locale_language	string		☐	
locale_locale	string		☐	
locale_name	string		☐	
timezone_\$type	string		☐	
timezone_id	string		☐	
timezone_offset	int32		☐	
timezone_presentation	string		☐	

12.1.17 UserIssueAttachmentSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: `NotRequired`

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueAttachmentSavedQueriesByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueAttachmentSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.18 UserIssueAttachmentTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueAttachmentTagsByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueAttachmentTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	

Name	Data Type	Label	Required	Documentation
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.19 UserIssueCommentSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueCommentSavedQueriesByUserId`. A value must be provided at all times for

required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueCommentSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	

Name	Data Type	Label	Required	Documentation
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.20 UserIssueCommentTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: `NotRequired`

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueCommentTagsByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueCommentTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>color_\$type</code>	string		☐	
<code>color_background</code>	string		☐	
<code>color_foreground</code>	string		☐	
<code>color_id</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created_1</code>	int64		☐	
<code>created</code>	int64	Created	☐	
<code>deleted</code>	boolean	Deleted	☐	

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.21 UserIssueCustomFieldSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: `NotRequired`

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueCustomFieldSavedQueriesByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueCustomFieldSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortcodeName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.22 UserIssueCustomFieldTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: `NotRequired`

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueCustomFieldTagsByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueCustomFieldTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.23 UserIssueLinkSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueLinkSavedQueriesByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueLinkSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	

Name	Data Type	Label	Required	Documentation
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	

Name	Data Type	Label	Required	Documentation
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.24 UserIssueLinkSavedQueryTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: `NotRequired`

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueLinkSavedQueryTagsByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueLinkSavedQueryTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>color_\$type</code>	string		☐	
<code>color_background</code>	string		☐	
<code>color_foreground</code>	string		☐	
<code>color_id</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	
<code>direction</code>	string	Direction	☐	
<code>draftOwner_\$type</code>	string		☐	
<code>draftOwner_avatarUrl</code>	string		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	

Name	Data Type	Label	Required	Documentation
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	

Name	Data Type	Label	Required	Documentation
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	

Name	Data Type	Label	Required	Documentation
wikifiedDescription	string	Wikified Description	☐	

12.1.25 UserIssueSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueSavedQueriesByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	

Name	Data Type	Label	Required	Documentation
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.26 UserIssueTagSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueTagSavedQueriesByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueTagSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
<code>\$type_1</code>	string		☐	
<code>\$type_2</code>	string		☐	
<code>\$type</code>	string		☐	
<code>commentsCount</code>	int32	Comments Count	☐	
<code>created</code>	int64	Created	☐	
<code>description</code>	string	Description	☐	
<code>draftOwner_\$type</code>	string		☐	
<code>draftOwner_avatarUrl</code>	string		☐	
<code>draftOwner_banned</code>	boolean		☐	
<code>draftOwner_email</code>	string		☐	
<code>draftOwner_fullName</code>	string		☐	
<code>draftOwner_guest</code>	boolean		☐	
<code>draftOwner_id</code>	string		☐	
<code>draftOwner_jabberAccountName</code>	string		☐	
<code>draftOwner_login</code>	string		☐	
<code>draftOwner_online</code>	boolean		☐	
<code>draftOwner_ringId</code>	string		☐	
<code>externalIssue_\$type</code>	string		☐	
<code>externalIssue_id</code>	string		☐	
<code>externalIssue_key</code>	string		☐	
<code>externalIssue_name</code>	string		☐	
<code>externalIssue_url</code>	string		☐	
<code>id_1</code>	string		☐	
<code>id_2</code>	string		☐	
<code>id</code>	string	ID	☐	
<code>idReadable</code>	string	Readable ID	☐	
<code>isDraft</code>	boolean	Is Draft	☐	
<code>name_1</code>	string		☐	
<code>name</code>	string	Name	☐	
<code>numberInProject</code>	int64	Number in Project	☐	
<code>owner_\$type_1</code>	string		☐	
<code>owner_\$type</code>	string		☐	
<code>owner_avatarUrl</code>	string		☐	
<code>owner_banned</code>	boolean		☐	
<code>owner_email</code>	string		☐	
<code>owner_fullName</code>	string		☐	
<code>owner_guest</code>	boolean		☐	

Name	Data Type	Label	Required	Documentation
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.27 UserIssueTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: `NotRequired`

Base Path: `issues[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueTagsByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a

pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	

Name	Data Type	Label	Required	Documentation
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_\$type	string		☐	

Name	Data Type	Label	Required	Documentation
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archiveId	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.28 UserIssueTagsByUserId1

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserIssueTagsByUserId1`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserIssueTagsByUserId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type_1	string		☐	
\$type_2	string		☐	
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_\$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	

Name	Data Type	Label	Required	Documentation
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_\$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_\$type_1	string		☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_\$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_\$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_\$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve_1	boolean		☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_\$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Markdown	☐	
visibility_\$type	string		☐	
visibility_id	string		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_\$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	

Name	Data Type	Label	Required	Documentation
watchers_\$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.29 UserNotificationProfilesBySprintId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/profiles/notifications`

Insert YouTrack API URL: `/users/{id}/profiles/notifications`

Update YouTrack API URL: `/users/{id}/profiles/notifications`

Delete YouTrack API URL: `/users/{id}/profiles/notifications`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/profiles/notifications`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserNotificationProfilesBySprintId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserNotificationProfilesBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
autoWatchOnComment	boolean	Auto-watch on Comment	☐	
autoWatchOnCreate	boolean	Auto-watch on Create	☐	
autoWatchOnUpdate	boolean	Auto-watch on Update	☐	
autoWatchOnVote	boolean	Auto-watch on Vote	☐	
duplicateClusterNotificationsEnabled	boolean		☐	
emailNotificationsEnabled	boolean	Email Notifications Enabled	☐	
id	string	ID	☐	
jabberNotificationsEnabled	boolean	Jabber Notifications Enabled	☐	
mailboxIntegrationNotificationsEnabled	boolean		☐	
mentionNotificationsEnabled	boolean		☐	
notifyOnOwnChanges	boolean	Notify on Own Changes	☐	
usePlainTextEmails	boolean	Use Plain-text Emails	☐	

12.1.30 Users: YouTrack Users

Catalog: YouTrack

Schema: Users

Label: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `Users` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	

Name	Data Type	Label	Required	Documentation
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_\$type	string		☐	
profiles_general_\$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_\$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_\$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

12.1.31 UserSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserSavedQueriesByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `'select * from table(value1, value2, value3)'` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `'select * from table(name1 => value1, name3 => value3)'` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	

Name	Data Type	Label	Required	Documentation
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
query	string	Query	☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

12.1.32 UserTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserTagsByUserId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `UserTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
color_\$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_\$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_\$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
untagOnResolve	boolean		☐	
updateableBy_\$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortcode	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_\$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

12.1.33 WorkItemById

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/workItems/{id}`

Insert YouTrack API URL: `/workItems/{id}`

Update YouTrack API URL: `/workItems/{id}`

Delete YouTrack API URL: `/workItems/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /workItems/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `WorkItemById`. A value must be provided at all times for required parameters, but optional

parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☒		

Table Function Columns

The columns of the table function `workItemById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_profiles_\$type	string		☐	
author_profiles_id	string		☐	
author_ringId	string		☐	
created	int64	Created	☐	
creator_\$type	string		☐	
creator_avatarUrl	string		☐	
creator_banned	boolean		☐	
creator_email	string		☐	
creator_fullName	string		☐	
creator_guest	boolean		☐	
creator_id	string		☐	
creator_jabberAccountName	string		☐	

Name	Data Type	Label	Required	Documentation
creator_login	string		☐	
creator_online	boolean		☐	
creator_profiles_\$type	string		☐	
creator_profiles_id	string		☐	
creator_ringId	string		☐	
date	int64	Date	☐	
duration_\$type	string		☐	
duration_id	string		☐	
duration_minutes	int32		☐	
duration_presentation	string		☐	
id	string	ID	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_draftOwner_\$type	string		☐	
issue_draftOwner_avatarUrl	string		☐	
issue_draftOwner_banned	boolean		☐	
issue_draftOwner_email	string		☐	
issue_draftOwner_fullName	string		☐	
issue_draftOwner_guest	boolean		☐	
issue_draftOwner_id	string		☐	
issue_draftOwner_jabberAccountName	string		☐	
issue_draftOwner_login	string		☐	
issue_draftOwner_online	boolean		☐	
issue_draftOwner_ringId	string		☐	
issue_externalIssue_\$type	string		☐	
issue_externalIssue_id	string		☐	
issue_externalIssue_key	string		☐	
issue_externalIssue_name	string		☐	
issue_externalIssue_url	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_parent_\$type	string		☐	
issue_parent_direction	string		☐	
issue_parent_id	string		☐	
issue_project_archived	boolean		☐	
issue_project_description	string		☐	

Name	Data Type	Label	Required	Documentation
issue_project_fromEmail	string		☐	
issue_project_iconUrl	string		☐	
issue_project_replyToEmail	string		☐	
issue_project_shortName	string		☐	
issue_project_startingNumber	int64		☐	
issue_project_template	boolean		☐	
issue_reporter_\$type	string		☐	
issue_reporter_avatarUrl	string		☐	
issue_reporter_banned	boolean		☐	
issue_reporter_email	string		☐	
issue_reporter_fullName	string		☐	
issue_reporter_guest	boolean		☐	
issue_reporter_id	string		☐	
issue_reporter_jabberAccountName	string		☐	
issue_reporter_login	string		☐	
issue_reporter_online	boolean		☐	
issue_reporter_ringId	string		☐	
issue_resolved	int64		☐	
issue_subtasks_\$type	string		☐	
issue_subtasks_direction	string		☐	
issue_subtasks_id	string		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_updater_\$type	string		☐	
issue_updater_avatarUrl	string		☐	
issue_updater_banned	boolean		☐	
issue_updater_email	string		☐	
issue_updater_fullName	string		☐	
issue_updater_guest	boolean		☐	
issue_updater_id	string		☐	
issue_updater_jabberAccountName	string		☐	
issue_updater_login	string		☐	
issue_updater_online	boolean		☐	
issue_updater_ringId	string		☐	
issue_usesMarkdown	boolean		☐	
issue_visibility_\$type	string		☐	
issue_visibility_id	string		☐	
issue_voters_\$type	string		☐	
issue_voters_hasVote	boolean		☐	

Name	Data Type	Label	Required	Documentation
issue_voters_id	string		☐	
issue_votes	int32		☐	
issue_watchers_\$type	string		☐	
issue_watchers_hasStar	boolean		☐	
issue_watchers_id	string		☐	
issue_wikifiedDescription	string		☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
type_\$type	string		☐	
type_autoAttached	boolean		☐	
type_id	string		☐	
type_name	string		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Markdown	☐	

12.1.34 WorkItems: YouTrack Work Items

Catalog: YouTrack

Schema: Users

Label: Work Items

This is a read-only table function. The YouTrack API may not support changing the data or the Invariant SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/workItems`

Insert YouTrack API URL: `/workItems`

Update YouTrack API URL: `/workItems`

Delete YouTrack API URL: `/workItems`

Field Selection Method: `NotRequired`

Select YouTrack API Operation: `get /workItems`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `WorkItems`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
author	string	☐		Parameter to filter work items by there author. Could specify few values of database id or login or Hub id or 'me' for current logged in user
createdEnd	int32	☐		The end timestamp of the interval for work items created date.
createdStart	int32	☐		The start timestamp of the interval for work items created date.
creator	string	☐		Parameter to filter work items by there creator. Could specify few values of database id or login or Hub id or 'me' for current logged in user
end	int32	☐		The end timestamp of the interval for work items date.
endDate	datetime	☐		The end date of the interval for work items date.
query	string	☐		Issues search query. Read more about search syntax here: https://www.jetbrains.com/help/youtrack/incloud/?Search-and-Command-Attributes >Search Query Reference
start	int32	☐		The start timestamp of the interval for work items date.
startDate	datetime	☐		The start date of the interval for work items date.
updatedEnd	int32	☐		The end timestamp of the interval for work items updated date.
updatedStart	int32	☐		The start timestamp of the interval for work items updated date.

Table Function Columns

The columns of the table function `workItems` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
\$type	string		☐	
author_\$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	

Name	Data Type	Label	Required	Documentation
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_profiles_\$type	string		☐	
author_profiles_id	string		☐	
author_ringId	string		☐	
created	int64	Created	☐	
creator_\$type	string		☐	
creator_avatarUrl	string		☐	
creator_banned	boolean		☐	
creator_email	string		☐	
creator_fullName	string		☐	
creator_guest	boolean		☐	
creator_id	string		☐	
creator_jabberAccountName	string		☐	
creator_login	string		☐	
creator_online	boolean		☐	
creator_profiles_\$type	string		☐	
creator_profiles_id	string		☐	
creator_ringId	string		☐	
date	int64	Date	☐	
duration_\$type	string		☐	
duration_id	string		☐	
duration_minutes	int32		☐	
duration_presentation	string		☐	
id	string	ID	☐	
issue_\$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_draftOwner_\$type	string		☐	
issue_draftOwner_avatarUrl	string		☐	
issue_draftOwner_banned	boolean		☐	
issue_draftOwner_email	string		☐	
issue_draftOwner_fullName	string		☐	
issue_draftOwner_guest	boolean		☐	
issue_draftOwner_id	string		☐	

Name	Data Type	Label	Required	Documentation
issue_draftOwner_jabberAccountName	string		☐	
issue_draftOwner_login	string		☐	
issue_draftOwner_online	boolean		☐	
issue_draftOwner_ringId	string		☐	
issue_externalIssue_\$type	string		☐	
issue_externalIssue_id	string		☐	
issue_externalIssue_key	string		☐	
issue_externalIssue_name	string		☐	
issue_externalIssue_url	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_parent_\$type	string		☐	
issue_parent_direction	string		☐	
issue_parent_id	string		☐	
issue_project_archived	boolean		☐	
issue_project_description	string		☐	
issue_project_fromEmail	string		☐	
issue_project_iconUrl	string		☐	
issue_project_replyToEmail	string		☐	
issue_project_shortName	string		☐	
issue_project_startingNumber	int64		☐	
issue_project_template	boolean		☐	
issue_reporter_\$type	string		☐	
issue_reporter_avatarUrl	string		☐	
issue_reporter_banned	boolean		☐	
issue_reporter_email	string		☐	
issue_reporter_fullName	string		☐	
issue_reporter_guest	boolean		☐	
issue_reporter_id	string		☐	
issue_reporter_jabberAccountName	string		☐	
issue_reporter_login	string		☐	
issue_reporter_online	boolean		☐	
issue_reporter_ringId	string		☐	
issue_resolved	int64		☐	
issue_subtasks_\$type	string		☐	
issue_subtasks_direction	string		☐	
issue_subtasks_id	string		☐	

Name	Data Type	Label	Required	Documentation
issue_summary	string		☐	
issue_updated	int64		☐	
issue_updater_\$type	string		☐	
issue_updater_avatarUrl	string		☐	
issue_updater_banned	boolean		☐	
issue_updater_email	string		☐	
issue_updater_fullName	string		☐	
issue_updater_guest	boolean		☐	
issue_updater_id	string		☐	
issue_updater_jabberAccountName	string		☐	
issue_updater_login	string		☐	
issue_updater_online	boolean		☐	
issue_updater_ringId	string		☐	
issue_usesMarkdown	boolean		☐	
issue_visibility_\$type	string		☐	
issue_visibility_id	string		☐	
issue_voters_\$type	string		☐	
issue_voters_hasVote	boolean		☐	
issue_voters_id	string		☐	
issue_votes	int32		☐	
issue_watchers_\$type	string		☐	
issue_watchers_hasStar	boolean		☐	
issue_watchers_id	string		☐	
issue_wikifiedDescription	string		☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
type_\$type	string		☐	
type_autoAttached	boolean		☐	
type_id	string		☐	
type_name	string		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	

13 Schema: Views

13.1 Views

13.1.1 IDTypes

Each YouTrack ID consists of an entity ID, a dash as separator and a sequence number. IDTypes maps the entity ID of YouTrack IDs to an entity name.

Catalog: YouTrack

Schema: Views

This is a read-only view. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

View Columns

The columns of the view `IDTypes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
DESCRIPTION	string(80)	Description	☒	
ID	int16	ID	☒	

- \$ -

- A -

agile_estimationField_ordinal 97, 101, 108, 114, 120, 140, 146
 agile_hideOrphansSwimlane 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 agile_id 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 agile_name 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 agile_originalEstimationField_{\$type} 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_aliases 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_hasRunningJob 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_id 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_isAutoAttached 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_isDisplayedInIssueList 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_isUpdateable 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_localizedName 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_name 97, 101, 108, 114, 120, 140, 146
 agile_originalEstimationField_ordinal 97, 101, 108, 114, 120, 140, 146
 agile_orphansAtTheTop 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 agile_owner_{\$type} 97, 101, 108, 114, 120, 140, 146
 agile_owner_avatarUrl 97, 101, 108, 114, 120, 140, 146
 agile_owner_banned 97, 101, 108, 114, 120, 140, 146
 agile_owner_email 97, 101, 108, 114, 120, 140, 146
 agile_owner_fullName 97, 101, 108, 114, 120, 140, 146
 agile_owner_guest 97, 101, 108, 114, 120, 140, 146
 agile_owner_id 97, 101, 108, 114, 120, 140, 146
 agile_owner_jabberAccountName 97, 101, 108, 114, 120, 140, 146
 agile_owner_login 97, 101, 108, 114, 120, 140, 146
 agile_owner_online 97, 101, 108, 114, 120, 140, 146
 agile_owner_ringId 97, 101, 108, 114, 120, 140, 146
 agile_sprintsSettings_{\$type} 97, 101, 108, 114, 120, 140, 146
 agile_sprintsSettings_cardOnSeveralSprints 97, 101, 108, 114, 120, 140, 146
 agile_sprintsSettings_disableSprints 97, 101, 108, 114, 120, 140, 146
 agile_sprintsSettings_explicitQuery 97, 101, 108, 114, 120, 140, 146
 agile_sprintsSettings_hideSubtasksOfCards 97, 101, 108, 114, 120, 140, 146
 agile_sprintsSettings_id 97, 101, 108, 114, 120, 140, 146
 agile_sprintsSettings_isExplicit 97, 101, 108, 114, 120, 140, 146
 agile_status_{\$type} 97, 101, 108, 114, 120, 140, 146
 agile_status_hasJobs 97, 101, 108, 114, 120, 140, 146
 agile_status_id 97, 101, 108, 114, 120, 140, 146
 agile_status_valid 97, 101, 108, 114, 120, 140, 146
 agile_swimlaneSettings_{\$type} 97, 101, 108, 114, 120, 140, 146
 agile_swimlaneSettings_enabled 97, 101, 108, 114, 120, 140, 146
 agile_swimlaneSettings_id 97, 101, 108, 114, 120, 140, 146
 agile_updateableBy_{\$type} 97, 101, 108, 114, 120, 140, 146
 agile_updateableBy_allUsersGroup 97, 101, 108, 114, 120, 140, 146
 agile_updateableBy_icon 97, 101, 108, 114, 120, 140, 146
 agile_updateableBy_id 97, 101, 108, 114, 120, 140, 146
 agile_updateableBy_name 97, 101, 108, 114, 120, 140, 146
 agile_updateableBy_ringId 97, 101, 108, 114, 120, 140, 146
 agile_updateableBy_usersCount 97, 101, 108, 114, 120, 140, 146
 agile_updateableBy_projectBased 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 agile_visibleFor_{\$type} 97, 101, 108, 114, 120, 140, 146
 agile_visibleFor_allUsersGroup 97, 101, 108, 114, 120, 140, 146
 agile_visibleFor_icon 97, 101, 108, 114, 120, 140, 146
 agile_visibleFor_id 97, 101, 108, 114, 120, 140, 146
 agile_visibleFor_name 97, 101, 108, 114, 120, 140, 146
 agile_visibleFor_ringId 97, 101, 108, 114, 120, 140, 146
 agile_visibleFor_usersCount 97, 101, 108, 114, 120, 140, 146
 agile_visibleFor_projectBased 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 Aliases 408, 418, 420, 492
 All Users Group 262, 264, 433, 444, 445, 474
 Allocated Memory 53
 allocatedMemory 53
 Allow All Origins 22, 51

Allow Statistics Collection	52	Articles	168
allowAllOrigins	22, 51	assembleDate	387, 389, 390, 392
AllowedOriginRestSettings	22	Assembly Date	387, 389, 390, 392
allowStatisticsCollection	52	AttachmentByld	172, 495
allUsersGroup	262, 264, 433, 444, 445, 474	Attachments	179, 500
analysis-enforce-row-uniqueness	2	author	15, 18, 20, 757
api-access-token	2	author_\$type	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
api-client-id	2	author_\$type_1	172, 179
api-client-secret	2	author_avatarUrl	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
api-pre-expiry-refresh-sec	2	author_avatarUrl_1	172, 179
api-redirect-url	2	author_banned	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
api-refresh-token	2	author_banned_1	172, 179
api-scope	2	author_email	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
api-token-url	2	author_email_1	172, 179
api-url	2	author_fullName	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
AppearanceSettings	23	author_fullName_1	172, 179
appearanceSettings_\$type	24	author_guest	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
appearanceSettings_dateFieldFormat_\$type	24	author_guest_1	172, 179
appearanceSettings_dateFieldFormat_datePattern	24	author_id	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
appearanceSettings_dateFieldFormat_id	24	author_id_1	172, 179
appearanceSettings_dateFieldFormat_pattern	24	author_jabberAccountName	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
appearanceSettings_dateFieldFormat_presentation	24	author_jabberAccountName_1	172, 179
appearanceSettings_id	24	author_login	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
appearanceSettings_logo_\$type	24	author_login_1	172, 179
appearanceSettings_logo_id	24	author_online	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
appearanceSettings_logo_url	24	author_online_1	172, 179
appearanceSettings_timeZone_\$type	24	author_profiles_\$type	15, 17, 753, 757
appearanceSettings_timeZone_id	24	author_profiles_id	15, 17, 753, 757
appearanceSettings_timeZone_offset	24	author_ringId	15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
appearanceSettings_timeZone_presentation	24	author_ringId_1	172, 179
Archive Format	377, 378, 379, 380	autoAttached	55, 57
Archived	26, 30, 34, 38, 41, 45, 58, 65, 72, 79, 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157, 486, 488, 489, 491	Auto-attached	55, 57
archiveFormat	377, 378, 379, 380	Auto-watch on Comment	746
article_\$type	172, 179		
article_\$type_1	172, 179		
article_content	172, 179, 239, 245, 251, 256		
article_content_1	172, 179		
article_created	239, 245, 251, 256		
article_hasChildren	239, 245, 251, 256		
article_hasStar	239, 245, 251, 256		
article_id	172, 179		
article_id_1	172, 179		
article_idReadable	239, 245, 251, 256		
article_ordinal	239, 245, 251, 256		
article_summary	172, 179, 239, 245, 251, 256		
article_summary_1	172, 179		
article_updated	239, 245, 251, 256		
ArticleByld	163		

Auto-watch on Create 746
 Auto-watch on Update 746
 Auto-watch on Vote 746
 autoWatchOnComment 746
 autoWatchOnCreate 746
 autoWatchOnUpdate 746
 autoWatchOnVote 746
 Available Disk Space 377, 378, 379, 380
 Available Memory 53
 Available Processors 53
 availableDiskSpace 377, 378, 379, 380
 availableMemory 53
 availableProcessors 53
 Avatar (URL) 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 avatarUrl 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747

- B -

Backup Cancelled 376
 Backup in Progress 376
 backupCancelled 376
 backupError_\$type 376
 backupError_date 376
 backupError_errorMessage 376
 backupError_id 376
 backupInProgress 376
 backupStatus_\$type 377, 378, 379, 380
 backupStatus_backupCancelled 377, 378, 379, 380
 backupStatus_backupError_\$type 377, 378, 379, 380
 backupStatus_backupError_date 377, 378, 379, 380
 backupStatus_backupError_errorMessage 377, 378, 379, 380
 backupStatus_backupError_id 377, 378, 379, 380
 backupStatus_backupInProgress 377, 378, 379, 380
 backupStatus_id 377, 378, 379, 380
 Banned 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 Base URL 52

Base64 Content 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
 base64Content 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
 base64Content_1 172, 179, 185, 192
 baseUrl 52
 Before Cursor 18, 20
 beforeCursor 18, 20
 BLOB Preferred 604
 Blob String Cache Hit Rate 53
 BLOB_PREFERRED 604
 blobStringsCacheHitRate 53
 BOL_RESPONSE_CACHE_MAX_AGE_SEC 604
 buildBundleElementId 387
 bulk-delete-page-size-rows 2
 bulk-insert-page-size-bytes 2
 bulk-insert-page-size-rows 2
 bundle_\$type 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 486, 488, 489, 491
 bundle_\$type_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488
 bundle_id 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 486, 488, 489, 491
 bundle_id_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488
 bundle_isUpdateable 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 486, 488, 489, 491
 bundle_isUpdateable_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488

- C -

Cached Results Count in DB Queries Cache 53
 cachedResultsCountInDBQueriesCache 53
 canBeEmpty 408, 421, 423, 492
 categories 15, 18, 20
 category_\$type 15, 17, 20
 category_id 15, 17, 20
 Charset 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
 charset_1 172, 179, 185, 192
 ChildArticleAttachments 185
 ChildArticleAttachmentsById 192
 ChildArticleComments 200
 ChildArticleCommentsById 206
 ChildArticles 213
 ChildArticlesById 219
 ChildChildArticles 226

ChildChildArticlesById	232	columnSettings_field_name	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
color_\$type	273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 448, 454, 466, 470, 479, 482, 486, 488, 489, 491, 547, 587, 592, 599, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 737, 741, 751	columnSettings_field_ordinal	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
color_\$type_1	389, 390, 395, 399, 415, 416, 429, 432, 486, 488	columnSettings_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
color_background	273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 448, 454, 466, 470, 479, 482, 486, 488, 489, 491, 547, 587, 592, 599, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 737, 741, 751	comment_\$type	172, 179, 268, 495, 500
color_background_1	389, 390, 395, 399, 415, 416, 429, 432, 486, 488	comment_\$type_1	172, 179
color_foreground	273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 448, 454, 466, 470, 479, 482, 486, 488, 489, 491, 547, 587, 592, 599, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 737, 741, 751	comment_created	172, 179, 268, 495, 500
color_foreground_1	389, 390, 395, 399, 415, 416, 429, 432, 486, 488	comment_created_1	172, 179
color_id	273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 448, 454, 466, 470, 479, 482, 486, 488, 489, 491, 547, 587, 592, 599, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 737, 741, 751	comment_deleted	268, 495, 500
color_id_1	389, 390, 395, 399, 415, 416, 429, 432, 486, 488	comment_id	172, 179, 268, 495, 500
colorCoding_\$type	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	comment_id_1	172, 179
colorCoding_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	comment_text	172, 179, 268, 495, 500
columnSettings_\$type	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	comment_text_1	172, 179
columnSettings_field_\$type	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	comment_textPreview	268, 495, 500
columnSettings_field_aliases	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	comment_updated	172, 179, 268, 495, 500
columnSettings_field_hasRunningJob	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	comment_updated_1	172, 179
columnSettings_field_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	comment_usesMarkdown	268, 495, 500
columnSettings_field_isAutoAttached	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CommentAttachments	239, 506
columnSettings_field_isDisplayedInIssueList	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CommentAttachmentsByIssueId	245, 512
columnSettings_field_isUpdateable	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	Comments	251, 517
columnSettings_field_localizedName	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	Comments Count	26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
		CommentsByIssueId	256, 523
		commentsCount	26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
		commentsCount_1	349, 355, 368, 547, 558, 565, 576, 581, 592
		condition_\$type	408, 423, 492
		condition_id	408, 423, 492
		condition_parent_\$type	423
		condition_parent_canBeEmpty	423
		condition_parent_emptyFieldText	423
		condition_parent_hasRunningJob	423
		condition_parent_id	423
		condition_parent_isPublic	423
		condition_parent_ordinal	423
		Content	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256

Content Type 604
 content_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 content_2 185, 192, 200, 206, 213, 219, 226, 232
 content_3 185, 192, 200, 206, 213, 219, 226, 232
 content_4 226, 232
 content_5 226, 232
 CONTENT_TYPE 604
 created 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 753, 757
 created_1 26, 30, 101, 108, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 295, 299, 308, 312, 349, 355, 368, 495, 500, 506, 512, 517, 523, 547, 558, 565, 576, 581, 592, 606, 614, 626, 630, 694, 699, 703, 707
 created_2 172, 179, 185, 192, 200, 206, 226, 232, 239, 245, 280, 506, 512
 created_3 185, 192
 createdBy_\$type 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_\$type_1 45
 createdBy_avatarUrl 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_banned 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_email 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_fullName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_guest 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_id 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_id_1 45
 createdBy_jabberAccountName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_login 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_name 45
 createdBy_online 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_profiles_\$type 26, 30, 34, 38, 41, 45
 createdBy_profiles_id 26, 30, 34, 38, 41, 45
 createdBy_ringId 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 createdBy_untagOnResolve 45
 createdEnd 757
 createdStart 757
 Creation Date 374, 375
 creationDate 374, 375
 creator 757
 creator_\$type 753, 757
 creator_avatarUrl 753, 757
 creator_banned 753, 757
 creator_email 753, 757
 creator_fullName 753, 757
 creator_guest 753, 757
 creator_id 753, 757
 creator_jabberAccountName 753, 757
 creator_login 753, 757
 creator_online 753, 757
 creator_profiles_\$type 753, 757
 creator_profiles_id 753, 757
 creator_ringId 753, 757
 Cron Expression 377, 378, 379, 380
 cronExpression 377, 378, 379, 380
 currentSprint_\$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_\$type_1 65, 72, 126, 133
 currentSprint_agile_\$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_agile_hideOrphansSwimlane 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_agile_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_agile_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_agile_orphansAtTheTop 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_agile_updateableByProjectBased 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_agile_visibleForProjectBased 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_archived 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_commentsCount 65, 72, 126, 133
 currentSprint_created 65, 72, 126, 133
 currentSprint_description 65, 72, 126, 133
 currentSprint_finish 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_goal 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_id_1 65, 72, 126, 133
 currentSprint_idReadable 65, 72, 126, 133
 currentSprint_isDefault 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 currentSprint_isDraft 65, 72, 126, 133

currentSprint_name	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldIndividualUserSavedQueries	401
currentSprint_numberInProject	65, 72, 126, 133	CustomFieldIndividualUserSavedQueriesByUserBundled	402
currentSprint_previousSprint_\$type	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldIndividualUsersByUserBundled	404
currentSprint_previousSprint_archived	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldIndividualUserTags	405
currentSprint_previousSprint_finish	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldIndividualUserTagsByUserBundled	406
currentSprint_previousSprint_goal	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldInstancesByCustomFieldPrototypeld	408
currentSprint_previousSprint_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldOwnedFieldByOwnedFieldBundled	410
currentSprint_previousSprint_isDefault	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldOwnedFieldByOwnedFieldBundledAndElementId	411
currentSprint_previousSprint_name	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldOwnedFieldByValued	413
currentSprint_previousSprint_start	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldOwnedFields	414
currentSprint_previousSprint_unresolvedIssuesCount	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldOwnedFieldValues	415
currentSprint_resolved	65, 72, 126, 133	CustomFieldOwnedFieldValuesByOwnedFieldBundled	416
currentSprint_start	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	customFields	418, 500, 506, 517, 528, 543, 547, 558, 571, 576, 599
currentSprint_summary	65, 72, 126, 133	CustomFieldsByCustomFieldPrototypeld	420
currentSprint_unresolvedIssuesCount	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	CustomFieldsByCustomFieldPrototypeld2	421
currentSprint_updated	65, 72, 126, 133	CustomFieldsByCustomFieldPrototypeld3	423
currentSprint_usesMarkdown	65, 72, 126, 133	CustomFieldsByIssueId	533
currentSprint_votes	65, 72, 126, 133	CustomFieldStateBundleById	426
currentSprint_wikifiedDescription	65, 72, 126, 133	CustomFieldStateBundles	427
cursor	18, 20	CustomFieldStateBundleValues2ByStateBundled	427
CustomFieldAggregatedUserSavedQueriesByUserBundled	382	CustomFieldStateBundleValuesByStateBundled	429
CustomFieldAggregatedUsersByUserBundled	383	CustomFieldStateByStateBundledAndElementId	430
CustomFieldAggregatedUserTagsByUserBundled	384	CustomFieldStateValues	432
CustomFieldBuildBundles	386	CustomFieldUserBundles	433
CustomFieldBuildByBuildBundled	386	CustomFieldUserBundleUsers	434
CustomFieldBuildByBuildBundledAndElementId	387	CustomFieldUserBundleUserSavedQueries	435
CustomFieldBuildValues	389	CustomFieldUserBundleUserTags	436
CustomFieldBuildValuesByBuildBundled	390	CustomFieldUserByUserBundled	437
CustomFieldBuildValuesByBuildBundled1	392	CustomFieldUserByUserBundled1	438
CustomFieldEnumBundleByEnumFieldBundled	393	CustomFieldUserByUserBundled2	441
CustomFieldEnumBundles	394	CustomFieldUserGroupsByUserBundled	444
CustomFieldEnumBundleValuesByEnumFieldBundled	395	CustomFieldUserGroupsByUserBundled1	445
CustomFieldEnumByEnumFieldBundled	396	CustomFieldUsers	448
CustomFieldEnumByEnumFieldBundledAndElementId	398	CustomFieldUsersByUserBundled	448
CustomFieldEnumValues	399	CustomFieldUsersByUserBundled1	451
CustomFieldIndividualUsers	400	CustomFieldUsersByUserBundled2	454
		CustomFieldUsersByUserBundled3	457
		CustomFieldUsersByUserBundled4	459
		CustomFieldUsersByUserBundled5	461
		CustomFieldUsersByUserBundled6	464
		CustomFieldUsersByUserBundled7	466
		CustomFieldUsersByUserBundled8	470
		CustomFieldUsersByUserBundled9	472
		CustomFieldUsersByUserBundledAndGroupld	474

- CustomFieldUsersByUserId 477
- CustomFieldUserTagsByUserBundleId 479
- CustomFieldUserTagsByUserBundleId2 482
- CustomFieldVersionByProjectVersionBundleId 488
- CustomFieldVersions 486
- CustomFieldVersionValues 486
- CustomFieldVersionValuesByProjectVersionBundleId 488
- CustomFieldVersionValuesByProjectVersionBundleId2 489
- CustomFieldVersionValuesByProjectVersionBundleId3 491
-
- D -**
-
- Database Background Threads 53
- Database Location 53
- Database Queries Cache Hit Rate 53
- Database Size 53
- databaseBackgroundThreads 53
- DatabaseBackupById 374
- DatabaseBackups 375
- DatabaseBackupSettingBackupStatuses 376
- DatabaseBackupSettings 377
- databaseLocation 53
- databaseQueriesCacheHitRate 53
- databaseSize 53
- Date 753, 757
- DATE_ENDED 604
- DATE_STARTED 604
- dateFieldFormat_\$type 23, 693
- dateFieldFormat_datePattern 23, 693
- dateFieldFormat_id 23, 693
- dateFieldFormat_pattern 23, 693
- dateFieldFormat_presentation 23, 693
- Days a Week 56
- daysAWeek 56
- Deleted 30, 108, 280, 285, 308, 312, 506, 512, 517, 523, 614, 630, 703, 707
- DESCRIPTION 761
- description_1 26, 30, 34, 38, 41, 45, 65, 72, 349, 355, 368, 389, 390, 395, 399, 415, 416, 429, 432, 486, 488, 547, 558, 565, 576, 581, 592
- Directed 266
- Direction 38, 120, 320, 324, 345, 349, 355, 541, 554, 558, 565, 571, 576, 581, 638, 642, 720, 724
- download-error-400-bad-request-max-tries 2
- download-error-400-bad-request-sleep-initial-ms 2
- download-error-400-bad-request-sleep-max-ms 2
- download-error-400-bad-request-sleep-multiplicator 2
- download-error-408-request-timeout-max-tries 2
- download-error-408-request-timeout-sleep-initial-ms 2
- download-error-408-request-timeout-sleep-max-ms 2
- download-error-408-request-timeout-sleep-multiplicator 2
- download-error-422-bad-request-max-tries 2
- download-error-422-bad-request-sleep-initial-ms 2
- download-error-422-bad-request-sleep-max-ms 2
- download-error-422-bad-request-sleep-multiplicator 2
- download-error-429-too-many-requests-max-tries 2
- download-error-429-too-many-requests-sleep-initial-ms 2
- download-error-429-too-many-requests-sleep-max-ms 2
- download-error-429-too-many-requests-sleep-multiplicator 2
- download-error-502-server-unavailable-max-tries 2
- download-error-502-server-unavailable-sleep-initial-ms 2
- download-error-502-server-unavailable-sleep-max-ms 2
- download-error-502-server-unavailable-sleep-multiplicator 2
- download-error-503-server-unavailable-max-tries 2
- download-error-503-server-unavailable-sleep-initial-ms 2
- download-error-503-server-unavailable-sleep-max-ms 2
- download-error-503-server-unavailable-sleep-multiplicator 2
- download-error-504-gateway-timeout-max-tries 2
- download-error-504-gateway-timeout-sleep-initial-ms 2
- download-error-504-gateway-timeout-sleep-max-ms 2
- download-error-504-gateway-timeout-sleep-multiplicator 2
- download-error-590-network-connect-timeout-max-tries 2
- download-error-590-network-connect-timeout-sleep-initial-ms 2
- download-error-590-network-connect-timeout-sleep-max-ms 2
- download-error-590-network-connect-timeout-sleep-multiplicator 2
- download-error-599-network-connect-timeout-max-tries 2
- download-error-599-network-connect-timeout-sleep-initial-ms 2
- download-error-599-network-connect-timeout-sleep-max-ms 2
- download-error-599-network-connect-timeout-sleep-multiplicator 2

download-error-argument-exception-max-tries	2	draftOwner_\$type	26, 30, 34, 38, 41, 45, 101, 108,
download-error-argument-exception-sleep-initial-ms	2		114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299,
download-error-argument-exception-sleep-max-ms	2		304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345,
download-error-argument-exception-sleep-multiplicator	2		349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528,
download-error-internet-down-max-tries	2		533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587,
download-error-internet-down-sleep-initial-ms	2		592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638,
download-error-internet-down-sleep-max-ms	2		642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724,
download-error-internet-down-sleep-multiplicator	2		729, 733, 737, 741
download-error-io-exception-max-tries	2	draftOwner_avatarUrl	26, 30, 34, 38, 41, 45, 101,
download-error-io-exception-sleep-initial-ms	2		108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295,
download-error-io-exception-sleep-max-ms	2		299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340,
download-error-io-exception-sleep-multiplicator	2		345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523,
download-error-json-exception-max-tries	2		528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581,
download-error-json-exception-sleep-initial-ms	2		587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634,
download-error-json-exception-sleep-max-ms	2		638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720,
download-error-json-exception-sleep-multiplicator	2		724, 729, 733, 737, 741
download-error-other-exception-max-tries	2	draftOwner_banned	26, 30, 34, 38, 41, 45, 101,
download-error-other-exception-sleep-initial-ms	2		108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295,
download-error-other-exception-sleep-max-ms	2		299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340,
download-error-other-exception-sleep-multiplicator	2		345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523,
download-error-socket-exception-max-tries	2		528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581,
download-error-socket-exception-sleep-initial-ms	2		587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634,
download-error-socket-exception-sleep-max-ms	2		638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720,
download-error-socket-exception-sleep-multiplicator	2		724, 729, 733, 737, 741
download-error-web-exception-max-tries	2	draftOwner_email	26, 30, 34, 38, 41, 45, 101, 108,
download-error-web-exception-sleep-initial-ms	2		114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299,
download-error-web-exception-sleep-max-ms	2		304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345,
download-error-web-exception-sleep-multiplicator	2		349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528,
download-error-web-not-implemented-max-tries	2		533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587,
download-error-web-not-implemented-sleep-initial-ms	2		592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638,
download-error-web-not-implemented-sleep-max-ms	2		642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724,
download-error-web-not-implemented-sleep-multiplicator	2		729, 733, 737, 741
download-error-web-timeout-max-tries	2	draftOwner_fullName	26, 30, 34, 38, 41, 45, 101,
download-error-web-timeout-sleep-initial-ms	2		108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295,
download-error-web-timeout-sleep-max-ms	2		299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340,
download-error-web-timeout-sleep-multiplicator	2		345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523,
download-error-web-unauthorized-max-tries	2		528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581,
download-error-web-unauthorized-sleep-initial-ms	2		587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634,
download-error-web-unauthorized-sleep-max-ms	2		638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720,
download-error-web-unauthorized-sleep-multiplicator	2		724, 729, 733, 737, 741
draft	26, 101, 172, 179, 185, 192, 239, 245, 268,	draftOwner_guest	26, 30, 34, 38, 41, 45, 101, 108,
draft_1	172, 179, 185, 192		114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299,
			304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345,
			349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528,
			533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587,
			592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638,
			642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724,
			729, 733, 737, 741
		draftOwner_id	26, 30, 34, 38, 41, 45, 101, 108, 114,
			120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304,
			308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349,
			355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533,
			537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592,
			599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642,
			646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729,
			733, 737, 741

draftOwner_jabberAccountName 26, 30, 34, 38, 41,
 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285,
 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332,
 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512,
 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571,
 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626,
 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712,
 716, 720, 724, 729, 733, 737, 741
 draftOwner_login 26, 30, 34, 38, 41, 45, 101, 108,
 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299,
 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345,
 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528,
 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587,
 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638,
 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724,
 729, 733, 737, 741
 draftOwner_online 26, 30, 34, 38, 41, 45, 101, 108,
 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299,
 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345,
 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528,
 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587,
 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638,
 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724,
 729, 733, 737, 741
 draftOwner_profiles_\$type 268, 275, 280, 285, 290,
 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523,
 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581,
 587, 592, 599
 draftOwner_profiles_id 268, 275, 280, 285, 290,
 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523,
 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581,
 587, 592, 599
 draftOwner_ringId 26, 30, 34, 38, 41, 45, 101, 108,
 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299,
 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345,
 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528,
 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587,
 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638,
 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724,
 729, 733, 737, 741
 Driver 1
 DRY_RUN 604
 duplicateClusterNotificationsEnabled 746
 Duration (ms) 604
 duration_\$type 753, 757
 duration_id 753, 757
 duration_minutes 753, 757
 DURATION_MS 604
 duration_presentation 753, 757
 Email 378, 379, 380, 382, 383, 384, 400, 401, 402,
 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454,
 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658,
 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686,
 689, 691, 747
 Email Notifications Enabled 746
 EmailNotificationsEnabled 746
 EmailSettings_\$type 50
 EmailSettings_anonymous 50
 EmailSettings_from 50
 EmailSettings_host 50
 EmailSettings_id 50
 EmailSettings_isEnabled 50
 EmailSettings_login 50
 EmailSettings_mailProtocol 50
 EmailSettings_port 50
 EmailSettings_replyTo 50
 EmailSettings_sslKey_\$type 50
 EmailSettings_sslKey_id 50
 EmailSettings_sslKey_name 50
 Empty Field Text 408, 421, 423, 492
 emptyFieldText 408, 421, 423, 492
 end 15, 18, 20, 757
 End Date 604
 endDate 757
 enumBundleElementId 398
 Error 49
 Error Message Code 604
 Error Message Text 604
 ERROR_MESSAGE_CODE 604
 ERROR_MESSAGE_TEXT 604
 estimationField_\$type 58, 65, 72, 79, 85, 91, 126,
 133, 152, 157
 estimationField_aliases 58, 65, 72, 79, 85, 91, 126,
 133, 152, 157
 estimationField_fieldDefaults_\$type 58, 65, 72, 79,
 85, 91, 126, 133, 152, 157
 estimationField_fieldDefaults_canBeEmpty 58, 65,
 72, 79, 85, 91, 126, 133, 152, 157
 estimationField_fieldDefaults_emptyFieldText 58,
 65, 72, 79, 85, 91, 126, 133, 152, 157
 estimationField_fieldDefaults_id 58, 65, 72, 79, 85,
 91, 126, 133, 152, 157
 estimationField_fieldDefaults_isPublic 58, 65, 72,
 79, 85, 91, 126, 133, 152, 157
 estimationField_fieldType_\$type 58, 65, 72, 79, 85,
 91, 126, 133, 152, 157
 estimationField_fieldType_id 58, 65, 72, 79, 85, 91,
 126, 133, 152, 157

field_presentation 15, 17, 20
 fieldDefaults_\$type 408, 418, 420, 492
 fieldDefaults_canBeEmpty 408, 418, 420, 492
 fieldDefaults_emptyFieldText 408, 418, 420, 492
 fieldDefaults_id 408, 418, 420, 492
 fieldDefaults_isPublic 408, 418, 420, 492
 fieldDefaults_parent_\$type 408, 418, 420, 492
 fieldDefaults_parent_aliases 408, 418, 420, 492
 fieldDefaults_parent_hasRunningJob 408, 418, 420, 492
 fieldDefaults_parent_id 408, 418, 420, 492
 fieldDefaults_parent_isAutoAttached 408, 418, 420, 492
 fieldDefaults_parent_isDisplayedInIssueList 408, 418, 420, 492
 fieldDefaults_parent_isUpdateable 408, 418, 420, 492
 fieldDefaults_parent_localizedName 408, 418, 420, 492
 fieldDefaults_parent_name 408, 418, 420, 492
 fieldDefaults_parent_ordinal 408, 418, 420, 492
 fieldType_\$type 408, 418, 420, 492
 fieldType_id 408, 418, 420, 492
 Files to Keep 377, 378, 379, 380
 filesToKeep 377, 378, 379, 380
 Finish 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 First Day of Week 56
 firstDayOfWeek 56
 force-case-sensitive-identifiers 2
 forced-casing-identifiers 2
 From Email 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 fromEmail 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 Full Database Size 53
 Full Name 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 483, 484, 485, 486, 488, 489, 491, 492, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 fullDatabaseSize 53
 fullName 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 483, 484, 485, 486, 488, 489, 491, 492, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 Guest 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747

- H -

Has After 18, 20
 Has Before 18, 20
 Has Children 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 Has Running Job 387, 389, 390, 392, 395, 396, 398, 399, 408, 411, 413, 415, 416, 418, 420, 423, 427, 429, 430, 432, 486, 488, 489, 491, 492
 Has Star 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 hasAfter 18, 20
 hasBefore 18, 20
 hasChildren 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 hasChildren_1 185, 192, 200, 206, 213, 219, 226, 232
 hasChildren_2 226, 232
 hasRunningJob 387, 389, 390, 392, 395, 396, 398, 399, 408, 411, 413, 415, 416, 418, 420, 423, 427, 429, 430, 432, 486, 488, 489, 491, 492
 hasRunningJob_1 389, 390, 395, 399, 408, 415, 416, 429, 432, 486, 488, 492
 hasStar 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 hasStar_1 185, 192, 200, 206, 213, 219, 226, 232
 hasStar_2 226, 232
 hideOrphansSwimlane 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 HTTP Disk Cache Maximum Age (sec) 604
 HTTP Memory Cache Maximum Age (sec) 604
 HTTP Method 604
 HTTP Status Code 604
 HTTP_DISK_CACHE_MAX_AGE_SEC 604
 HTTP_DISK_CACHE_SAVE 604
 HTTP_DISK_CACHE_USE 604
 HTTP_MEMORY_CACHE_MAX_AGE_SEC 604
 HTTP_MEMORY_CACHE_SAVE 604
 HTTP_MEMORY_CACHE_USE 604
 HTTP_METHOD 604
 HTTP_STATUS_CODE 604
 http-disk-cache-compression-level 2
 http-disk-cache-directory 2
 http-disk-cache-ignore-write-errors 2
 http-disk-cache-max-age-sec 2
 http-get-timeout-max-ms 2
 http-get-timeout-ms 2

- G -

GlobalSettings 24
 Goal 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 GroupById 262
 Groups 264

http-memory-cache-compression-level	2	idReadable	26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
http-memory-cache-max-age-sec	2	idReadable_1	185, 192, 200, 206, 213, 219, 226, 232, 349, 355, 368, 547, 558, 565, 576, 581, 592
http-post-timeout-max-ms	2	idReadable_2	226, 232
http-post-timeout-ms	2	IDTypes	761
Icon	262, 264, 433, 444, 445, 474	ignore-http-400-errors	2
Icon (URL)	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	ignore-http-401-errors	2
iconUrl	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	ignore-http-402-errors	2
id	17, 58, 72, 85, 91, 97, 101, 108, 114, 120, 133, 140, 146, 163, 172, 192, 206, 219, 232, 245, 256, 262, 266, 268, 273, 275, 280, 285, 290, 299, 304, 312, 324, 332, 340, 345, 349, 355, 363, 368, 374, 382, 383, 384, 386, 387, 390, 392, 393, 395, 396, 398, 402, 404, 406, 408, 410, 411, 413, 416, 420, 421, 423, 426, 427, 429, 430, 437, 438, 441, 444, 445, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 474, 477, 479, 482, 485, 488, 489, 491, 495, 512, 523, 533, 537, 541, 554, 565, 581, 587, 592, 606, 610, 614, 618, 642, 650, 656, 672, 675, 680, 683, 686, 691, 693, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 746, 748, 751, 753	ignore-http-403-errors	2
id_1	20, 26, 30, 34, 38, 41, 45, 57, 58, 65, 72, 79, 91, 101, 108, 114, 120, 126, 133, 140, 146, 157, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 378, 379, 380, 382, 383, 384, 389, 390, 395, 399, 400, 401, 402, 404, 405, 406, 408, 415, 416, 429, 432, 433, 434, 435, 436, 438, 441, 444, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 486, 488, 492, 495, 500, 506, 512, 517, 523, 528, 533, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741	ignore-http-404-errors	2
id_2	26, 30, 34, 38, 45, 65, 72, 101, 108, 114, 120, 126, 133, 146, 172, 179, 185, 192, 200, 206, 226, 232, 239, 245, 280, 295, 299, 308, 312, 316, 320, 324, 332, 336, 340, 349, 355, 368, 378, 380, 382, 384, 389, 390, 395, 399, 401, 402, 405, 406, 415, 416, 429, 432, 435, 436, 438, 441, 448, 454, 461, 466, 486, 488, 506, 512, 547, 558, 565, 576, 581, 592, 606, 614, 618, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 733, 741	ignore-http-405-errors	2
id_3	185, 192	ignore-http-422-errors	2
		ignore-http-429-errors	2
		ignore-http-500-errors	2
		ignore-http-502-errors	2
		ignore-http-503-errors	2
		ignore-unknown-path-type	2
		ignore-values-unknown-path	2
		Installation Folder	53
		InstallationFolder	53
		InstanceCustomFields	492
		invalid-json-on-get-max-tries	2
		invalid-json-on-get-sleep-initial-ms	2
		invalid-json-on-get-sleep-max-ms	2
		invalid-json-on-get-sleep-multiplicator	2
		invalid-json-on-post-max-tries	2
		invalid-json-on-post-sleep-initial-ms	2
		invalid-json-on-post-sleep-max-ms	2
		invalid-json-on-post-sleep-multiplicator	2
		invantive-sql-compress-sparse-arrays	2
		invantive-sql-correct-invalid-date	2
		invantive-sql-forward-filters-to-data-containers	2
		invantive-sql-share-byte-arrays	2
		invantive-sql-share-strings	2
		invantive-sql-shuffle-fetch-results-data-containers	2
		invantive-use-cache	2
		Is Application Read-only	52
		Is Auto-attached	408, 418, 420, 492
		Is Default	91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
		Is Displayed in Issue List	408, 418, 420, 492

Is Draft 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 299, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 Is On 377, 378, 379, 380
 Is Public 408, 421, 423, 492
 Is Resolved 427, 429, 430, 432
 Is RTL 50
 Is Updateable 382, 383, 384, 386, 389, 390, 393, 394, 395, 399, 400, 401, 402, 404, 405, 406, 408, 410, 414, 415, 416, 418, 420, 426, 427, 429, 432, 433, 434, 435, 436, 437, 444, 448, 485, 486, 488, 492
 isApplicationReadOnly 52
 isAutoAttached 408, 418, 420, 492
 isDefault 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 isDisplayedInIssueList 408, 418, 420, 492
 isDraft 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 isDraft_1 349, 355, 368, 547, 558, 565, 576, 581, 592
 isOn 377, 378, 379, 380
 isPublic 408, 421, 423, 492
 isResolved 427, 429, 430, 432
 isRTL 50
 Issue Tags 45, 361, 547, 658
 issue_\$type 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_commentsCount 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_created 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_description 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_draftOwner_\$type 753, 757
 issue_draftOwner_avatarUrl 753, 757
 issue_draftOwner_banned 753, 757
 issue_draftOwner_email 753, 757
 issue_draftOwner_fullName 753, 757
 issue_draftOwner_guest 753, 757
 issue_draftOwner_id 753, 757
 issue_draftOwner_jabberAccountName 753, 757
 issue_draftOwner_login 753, 757
 issue_draftOwner_online 753, 757
 issue_draftOwner_ringId 753, 757
 issue_externalIssue_\$type 753, 757
 issue_externalIssue_id 753, 757
 issue_externalIssue_key 753, 757
 issue_externalIssue_name 753, 757
 issue_externalIssue_url 753, 757
 issue_id 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_idReadable 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_isDraft 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_numberInProject 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_parent_\$type 753, 757
 issue_parent_direction 753, 757
 issue_parent_id 753, 757
 issue_project_archived 753, 757
 issue_project_description 753, 757
 issue_project_fromEmail 753, 757
 issue_project_iconUrl 753, 757
 issue_project_replyToEmail 753, 757
 issue_project_shortName 753, 757
 issue_project_startingNumber 753, 757
 issue_project_template 753, 757
 issue_reporter_\$type 753, 757
 issue_reporter_avatarUrl 753, 757
 issue_reporter_banned 753, 757
 issue_reporter_email 753, 757
 issue_reporter_fullName 753, 757
 issue_reporter_guest 753, 757
 issue_reporter_id 753, 757
 issue_reporter_jabberAccountName 753, 757
 issue_reporter_login 753, 757
 issue_reporter_online 753, 757
 issue_reporter_ringId 753, 757
 issue_resolved 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_subtasks_\$type 753, 757
 issue_subtasks_direction 753, 757
 issue_subtasks_id 753, 757
 issue_summary 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_updated 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
 issue_updater_\$type 753, 757
 issue_updater_avatarUrl 753, 757
 issue_updater_banned 753, 757
 issue_updater_email 753, 757
 issue_updater_fullName 753, 757

issue_updater_guest	753, 757	IssueTagIssueLinksById	324
issue_updater_id	753, 757	IssueTagIssues	328
issue_updater_jabberAccountName	753, 757	IssueTagIssuesCustomFieldsById	332
issue_updater_login	753, 757	IssueTagIssuesTags	336
issue_updater_online	753, 757	IssueTagIssueTagsById	340
issue_updater_ringId	753, 757	IssueTagLinkIssuesByTagId	345
issue_usesMarkdown	268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757	IssueTagLinkIssuesByTagId1	349
issue_visibility_\$type	753, 757	IssueTagLinkTrimmedIssuesByTagId	355
issue_visibility_id	753, 757	IssueTags	45, 361, 547, 658
issue_voters_\$type	753, 757	IssueTagsBySavedQueryId	650
issue_voters_hasVote	753, 757	isUpdateable	382, 383, 384, 386, 389, 390, 393, 394, 395, 399, 400, 401, 402, 404, 405, 406, 408, 410, 414, 415, 416, 418, 420, 426, 427, 429, 432, 433, 434, 435, 436, 437, 444, 448, 485, 486, 488, 492
issue_voters_id	753, 757	- J -	
issue_votes	268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757		
issue_watchers_\$type	753, 757	Jabber Account Name	378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
issue_watchers_hasStar	753, 757	Jabber Notifications Enabled	746
issue_watchers_id	753, 757	jabberAccountName	378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
issue_wikifiedDescription	268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757	jabberNotificationsEnabled	746
IssueAttachments	26	jabberSettings_\$type	50
IssueAttachmentsBySavedQueryId	606	jabberSettings_host	50
IssueById	537, 610	jabberSettings_id	50
IssueComments	30	jabberSettings_isEnabled	50
IssueCommentsBySavedQueryId	614	jabberSettings_login	50
IssueCustomFields	34	jabberSettings_port	50
IssueCustomFieldsBySavedQueryId	618	jabberSettings_serviceName	50
IssueLinks	38	join-set-points-per-request	2
IssueLinksByIssueId	541	- L -	
IssueLinkTypes	266		
IssueLinkTypesById	266	leader_\$type	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
issueQuery	15, 18, 20	leader_\$type_1	45
Issues	41, 543, 623	leader_avatarUrl	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
IssuesAttachments	626	leader_banned	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
IssuesComments	630	leader_email	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
IssuesCustomFields	634	leader_fullName	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
IssuesLinks	638	leader_guest	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
IssuesLinksById	642	leader_id	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
IssuesTags	646	leader_id_1	45
IssueTagAttachmentIssuesByTagId	268		
IssueTagById	273		
IssueTagById2	275		
IssueTagCommentAttachmentIssuesByTagId	280		
IssueTagCommentIssuesByTagId	285		
IssueTagCustomFieldIssuesByTagId	290		
IssueTagIssueAttachments	295		
IssueTagIssueAttachmentsById	299		
IssueTagIssueById	304		
IssueTagIssueComments	308		
IssueTagIssueCommentsById	312		
IssueTagIssueCustomFields	316		
IssueTagIssueLinks	320		

leader_jabberAccountName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 leader_login 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 leader_name 45
 leader_online 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 leader_profiles_\$type 26, 30, 34, 38, 41, 45
 leader_profiles_id 26, 30, 34, 38, 41, 45
 leader_ringId 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 leader_untagOnResolve 45
 License 49
 license_\$type 24
 license_error 24
 license_id 24
 license_license 24
 license_username 24
 Licenses 49
 limit-partition-calls-left 2
 Link 374, 375
 LinkById 554
 LinkIssues 558
 LinkIssuesByIssueld 565
 Links 571
 LinkTrimmedIssues 576
 LinkTrimmedIssuesByIssueld 581
 linkType_\$type 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_aggregation 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_directed 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_id 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_localizedName 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_localizedSourceToTarget 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_localizedTargetToSource 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_name 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_readOnly 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_sourceToTarget 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 linkType_targetToSource 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
 locale_\$type 50, 693
 locale_community 50, 693
 locale_id 50, 693
 locale_language 50, 693
 locale_locale 50, 693
 locale_name 50, 693
 LocaleSettings 50
 localeSettings_\$type 24
 localeSettings_id 24
 localeSettings_isRTL 24
 localeSettings_locale_\$type 24
 localeSettings_locale_community 24
 localeSettings_locale_id 24
 localeSettings_locale_language 24
 localeSettings_locale_locale 24
 localeSettings_locale_name 24
 Localized Name 266, 395, 396, 398, 399, 408, 418, 420, 427, 429, 430, 432, 492
 Localized Source to Target 266
 Localized Target to Source 266
 localizedName 266, 395, 396, 398, 399, 408, 418, 420, 427, 429, 430, 432, 492
 localizedSourceToTarget 266
 localizedTargetToSource 266
 Location 377, 378, 379, 380
 Login 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 log-native-calls-to-disk-max-events 2
 log-native-calls-to-disk-max-seconds 2
 log-native-calls-to-disk-on-error 2
 log-native-calls-to-disk-on-success 2
 log-native-calls-to-trace 2
 logo_\$type 23
 logo_id 23
 logo_url 23
 Logs Location 53
 logsLocation 53

- M -

mailboxIntegrationNotificationsEnabled 746
 Max Export Items 52
 Max Upload File Size 52
 maxExportItems 52
 maximum-discovered-column-count 2
 maximum-length-identifiers 2
 max-odata-filters 2
 maxUploadFileSize 52
 max-url-length-accepted 2
 max-url-length-desired 2
 Me 661
 mentionNotificationsEnabled 746
 Metadata 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
 metaData_1 172, 179, 185, 192

metadata-cache-max-age-sec 2
 mimeType 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
 MIME-type 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
 mimeType_1 172, 179, 185, 192
 Minutes a Day 56
 minutesADay 56
 MyIssueTags 662
 MySavedQueries 665
 MySavedQueryissues 667
 MyTags 670
 notificationSettings_jabberSettings_\$type 24
 notificationSettings_jabberSettings_host 24
 notificationSettings_jabberSettings_id 24
 notificationSettings_jabberSettings_isEnabled 24
 notificationSettings_jabberSettings_login 24
 notificationSettings_jabberSettings_port 24
 notificationSettings_jabberSettings_serviceName 24
 NotifiedUserSavedQuerySettings 378
 NotifiedUserSettings 379
 NotifiedUserTagSettings 380
 Notify on Own Changes 746
 notifyOnOwnChanges 746
 npt 604
 Nullable 408, 421, 423, 492
 Number in Project 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 numberInProject 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 name_1 26, 34, 45, 58, 65, 72, 79, 91, 101, 114, 126, 133, 146, 157, 172, 179, 185, 192, 295, 299, 316, 332, 336, 340, 389, 390, 395, 399, 415, 416, 429, 432, 486, 488, 606, 618, 626, 634, 646, 650, 694, 699, 712, 716, 733, 741
 Native Platform Scalar Requests 604
 NATIVEPLATFORMSCALARREQUESTS 604
 Notification Analyzer Threads 53
 notificationAnalyzerThreads 53
 NotificationSettings 50
 notificationSettings_\$type 24
 notificationSettings_emailSettings_\$type 24
 notificationSettings_emailSettings_anonymous 24
 notificationSettings_emailSettings_from 24
 notificationSettings_emailSettings_host 24
 notificationSettings_emailSettings_id 24
 notificationSettings_emailSettings_isEnabled 24
 notificationSettings_emailSettings_login 24
 notificationSettings_emailSettings_mailProtocol 24
 notificationSettings_emailSettings_port 24
 notificationSettings_emailSettings_replyTo 24
 notificationSettings_id 24

- N -

Name 26, 30, 34, 38, 41, 45, 55, 57, 58, 65, 72, 79, 85, 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 152, 157, 172, 179, 185, 192, 239, 245, 262, 264, 266, 268, 273, 280, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 374, 375, 378, 380, 382, 384, 387, 389, 390, 392, 395, 396, 398, 399, 401, 402, 405, 406, 408, 411, 413, 415, 416, 418, 420, 427, 429, 430, 432, 433, 435, 436, 438, 441, 444, 446, 448, 451, 454, 461, 464, 466, 470, 474, 477, 479, 482, 486, 488, 489, 491, 492, 495, 500, 506, 512, 528, 533, 536, 541, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 706, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 750, 712, 716, 720, 724, 729, 733, 737, 741
 numberInProject 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 numberInProject_1 349, 355, 368, 547, 558, 565, 576, 581, 592
 486, 488, 606, 618, 626, 634, 646, 650, 694, 699, 712, 716, 733, 741

- O -

Native Platform Scalar Requests 604
 NATIVEPLATFORMSCALARREQUESTS 604
 Notification Analyzer Threads 53
 notificationAnalyzerThreads 53
 NotificationSettings 50
 notificationSettings_\$type 24
 notificationSettings_emailSettings_\$type 24
 notificationSettings_emailSettings_anonymous 24
 notificationSettings_emailSettings_from 24
 notificationSettings_emailSettings_host 24
 notificationSettings_emailSettings_id 24
 notificationSettings_emailSettings_isEnabled 24
 notificationSettings_emailSettings_login 24
 notificationSettings_emailSettings_mailProtocol 24
 notificationSettings_emailSettings_port 24
 notificationSettings_emailSettings_replyTo 24
 notificationSettings_id 24
 oauth-unauthorized-max-tries 2
 oauth-unauthorized-sleep-initial-ms 2
 oauth-unauthorized-sleep-max-ms 2
 oauth-unauthorized-sleep-multiplicator 2
 Online 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 onlineUsers_\$type 53
 onlineUsers_id 53
 onlineUsers_users 53
 Ordinal 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 387, 389, 390, 392, 395, 396, 398, 399, 408, 411, 413, 415, 416, 418, 420, 423, 427, 429, 430, 432, 486, 488, 489, 491, 492

ordinal_1 185, 192, 200, 206, 213, 219, 226, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 268, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 642, 643, 644, 645, 646, 647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 658, 659, 660, 661, 662, 663, 664, 665, 666, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 685, 686, 687, 688, 689, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719, 720, 721, 722, 723, 724, 725, 726, 727, 728, 729, 730, 731, 732, 733, 734, 735, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 761, 762, 763, 764, 765, 766, 767, 768, 769, 770, 771, 772, 773, 774, 775, 776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792, 793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 812, 813, 814, 815, 816, 817, 818, 819, 820, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 844, 845, 846, 847, 848, 849, 850, 851, 852, 853, 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 867, 868, 869, 870, 871, 872, 873, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 901, 902, 903, 904, 905, 906, 907, 908, 909, 910, 911, 912, 913, 914, 915, 916, 917, 918, 919, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 930, 931, 932, 933, 934, 935, 936, 937, 938, 939, 940, 941, 942, 943, 944, 945, 946, 947, 948, 949, 950, 951, 952, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 964, 965, 966, 967, 968, 969, 970, 971, 972, 973, 974, 975, 976, 977, 978, 979, 980, 981, 982, 983, 984, 985, 986, 987, 988, 989, 990, 991, 992, 993, 994, 995, 996, 997, 998, 999, 1000

owner_jabberAccountName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

owner_login 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

owner_name 336, 340, 646, 650, 733, 741

owner_online 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

owner_profiles_\$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 411, 413, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

owner_profiles_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 411, 413, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

owner_ringId 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

owner_untagOnResolve 336, 340, 646, 650, 733, 741

parent_\$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 421, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

parent_\$type_1 349, 355, 368, 547, 558, 565, 576, 581, 592

parent_aliases 421

parent_commentsCount 349, 355, 368, 547, 558, 565, 576, 581, 592

parent_created 349, 355, 368, 547, 558, 565, 576, 581, 592

parent_description 349, 355, 368, 547, 558, 565, 576, 581, 592

parent_direction 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 421, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

parent_fieldDefaults_\$type 421

parent_fieldDefaults_canBeEmpty 421

parent_fieldDefaults_emptyFieldText 421

parent_fieldDefaults_id 421

parent_fieldDefaults_isPublic 421

parent_fieldType_\$type 421

parent_fieldType_id 421

parent_hasRunningJob 421

parent_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 421, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

parent_id_1 349, 355, 368, 547, 558, 565, 576, 581, 592

parent_idReadable 349, 355, 368, 547, 558, 565, 576, 581, 592

parent_isAutoAttached 421

parent_isDisplayedInIssueList 421

parent_isDraft 349, 355, 368, 547, 558, 565, 576, 581, 592

parent_isUpdateable 421

parent_linkType_\$type 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_aggregation 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_directed 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_id 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_localizedName 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_localizedSourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_localizedTargetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_name 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_readOnly 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_sourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_linkType_targetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 parent_localizedName 421
 parent_name 421
 parent_numberInProject 349, 355, 368, 547, 558, 565, 576, 581, 592
 parent_ordinal 421
 parent_resolved 349, 355, 368, 547, 558, 565, 576, 581, 592
 parent_summary 349, 355, 368, 547, 558, 565, 576, 581, 592
 parent_updated 349, 355, 368, 547, 558, 565, 576, 581, 592
 parent_usesMarkdown 349, 355, 368, 547, 558, 565, 576, 581, 592
 parent_votes 349, 355, 368, 547, 558, 565, 576, 581, 592
 parent_wikifiedDescription 349, 355, 368, 547, 558, 565, 576, 581, 592
 parentArticle_\$type 185, 192, 200, 206, 226, 232, 239, 245
 parentArticle_base64Content 185, 192, 239, 245
 parentArticle_charset 185, 192, 239, 245
 parentArticle_content 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_content_1 185, 192, 200, 206, 213, 219, 226, 232
 parentArticle_content_2 226, 232
 parentArticle_content_3 226, 232
 parentArticle_created 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_created_1 185, 192, 200, 206, 213, 219, 226, 232, 239, 245
 parentArticle_created_2 185, 192, 200, 206, 226, 232
 parentArticle_draft 185, 192, 239, 245
 parentArticle_extension 185, 192, 239, 245
 parentArticle_externalArticle_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_externalArticle_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_externalArticle_key 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_externalArticle_name 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_externalArticle_url 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_hasChildren 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_hasChildren_1 185, 192, 200, 206, 213, 219, 226, 232
 parentArticle_hasChildren_2 226, 232
 parentArticle_hasStar 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_hasStar_1 185, 192, 200, 206, 213, 219, 226, 232
 parentArticle_hasStar_2 226, 232
 parentArticle_id 185, 192, 200, 206, 226, 232, 239, 245
 parentArticle_idReadable 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256

parentArticle_idReadable_1 185, 192, 200, 206, 213, 219, 226, 232
 parentArticle_idReadable_2 226, 232
 parentArticle_metaData 185, 192, 239, 245
 parentArticle_mimeType 185, 192, 239, 245
 parentArticle_name 185, 192, 239, 245
 parentArticle_ordinal 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_ordinal_1 185, 192, 200, 206, 213, 219, 226, 232
 parentArticle_ordinal_2 226, 232
 parentArticle_parentArticle_content 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_parentArticle_created 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_parentArticle_hasChildren 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_parentArticle_hasStar 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_parentArticle_idReadable 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_parentArticle_ordinal 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_parentArticle_summary 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_parentArticle_updated 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_project_archived 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_project_description 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_project_fromEmail 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_project_iconUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_project_replyToEmail 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_project_shortName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_project_startingNumber 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_project_template 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_removed 185, 192, 239, 245
 parentArticle_reporter_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_reporter_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_size 185, 192, 239, 245
 parentArticle_summary 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_summary_1 185, 192, 200, 206, 213, 219, 226, 232
 parentArticle_summary_2 226, 232
 parentArticle_summary_3 226, 232
 parentArticle_text 200, 206
 parentArticle_updated 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updated_1 185, 192, 200, 206, 213, 219, 226, 232, 239, 245
 parentArticle_updated_2 185, 192, 200, 206, 226, 232

parentArticle_updatedBy_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_updatedBy_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_url 185, 192, 239, 245
 parentArticle_visibility_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 parentArticle_visibility_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 partition-slot-based-rate-limit-length-ms 2
 partition-slot-based-rate-limit-slots 2
 Payload 604
 PAYLOAD_TEXT 604
 Pending Async Jobs 53
 pendingAsyncJobs 53
 periodFormat_\$type 672
 periodFormat_id 672
 pre-request-delay-ms 2
 previousSprint_\$type 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 previousSprint_agile_\$type 97, 101, 108, 114, 120, 140, 146
 previousSprint_agile_hideOrphansSwimlane 97, 101, 108, 114, 120, 140, 146
 previousSprint_agile_id 97, 101, 108, 114, 120, 140, 146
 previousSprint_agile_name 97, 101, 108, 114, 120, 140, 146
 previousSprint_agile_orphansAtTheTop 97, 101, 108, 114, 120, 140, 146
 previousSprint_agile_updateableByProjectBased 97, 101, 108, 114, 120, 140, 146
 previousSprint_agile_visibleForProjectBased 97, 101, 108, 114, 120, 140, 146
 previousSprint_archived 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 previousSprint_finish 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 previousSprint_goal 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 previousSprint_id 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 previousSprint_isDefault 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 previousSprint_name 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 previousSprint_previousSprint_\$type 97, 101, 108, 114, 120, 140, 146
 previousSprint_previousSprint_archived 97, 101, 108, 114, 120, 140, 146
 previousSprint_previousSprint_finish 97, 101, 108, 114, 120, 140, 146
 previousSprint_previousSprint_goal 97, 101, 108, 114, 120, 140, 146
 previousSprint_previousSprint_id 97, 101, 108, 114, 120, 140, 146
 previousSprint_previousSprint_isDefault 97, 101, 108, 114, 120, 140, 146
 previousSprint_previousSprint_name 97, 101, 108, 114, 120, 140, 146
 previousSprint_previousSprint_start 97, 101, 108, 114, 120, 140, 146
 previousSprint_previousSprint_unresolvedIssuesCount 97, 101, 108, 114, 120, 140, 146
 previousSprint_start 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 previousSprint_unresolvedIssuesCount 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
 profiles_\$type 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 profiles_general_\$type 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747

profiles_general_id 438, 441, 448, 451, 454, 457, profiles_notifications_notifyOnOwnChanges 438, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_id 378, 379, 380, 382, 383, 384, 400, 401 profiles_notifications_usePlainTextEmails 438, 441, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 680, 683, 686, 689, 691, 747
 profiles_notifications_\$type 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 686, 689, 691, 747
 profiles_notifications_autoWatchOnComment 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_autoWatchOnCreate 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_autoWatchOnUpdate 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_autoWatchOnVote 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_duplicateClusterNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_emailNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_id 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_jabberNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_mailboxIntegrationNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 profiles_notifications_mentionNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747 678, 680, 683, 686, 689, 691, 747
 project_\$type 349, 368, 547, 558, 565, 592
 project_archived 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 429, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 project_archived_1 185, 192, 200, 206, 213, 219, 226, 232
 project_commentsCount 349, 368, 547, 558, 565, 592
 project_created 349, 368, 547, 558, 565, 592
 project_createdBy_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 429, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 429, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 429, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 429, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599

project_createdBy_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_createdBy_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_description 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_description_1 185, 192, 200, 206, 213, 219, 226, 232, 349, 368, 547, 558, 565, 592
 project_fromEmail 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_fromEmail_1 185, 192, 200, 206, 213, 219, 226, 232
 project_iconUrl 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_id 349, 368, 547, 558, 565, 592
 project_idReadable 349, 368, 547, 558, 565, 592
 project_isDraft 349, 368, 547, 558, 565, 592
 project_leader_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599

project_leader_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_leader_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_numberInProject 349, 368, 547, 558, 565, 592
 project_replyToEmail 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_replyToEmail_1 185, 192, 200, 206, 213, 219, 226, 232
 project_resolved 349, 368, 547, 558, 565, 592
 project_shortName 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 project_shortName_1 185, 192, 200, 206, 213, 219, 226, 232
 project_startingNumber 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_summary 349, 368, 547, 558, 565, 592
 project_team_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_team_allUsersGroup 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_team_icon 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_team_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_team_name 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_team_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 project_team_usersCount 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599

project_template 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 project_template_1 185, 192, 200, 206, 213, 219, 226, 232
 project_updated 349, 368, 547, 558, 565, 592
 project_usesMarkdown 349, 368, 547, 558, 565, 592
 project_votes 349, 368, 547, 558, 565, 592
 project_wikifiedDescription 349, 368, 547, 558, 565, 592
 ProjectActivityPages 20
 ProjectBySprintId 58
 projectCustomField_\$type 290, 528, 533
 projectCustomField_canBeEmpty 290, 528, 533
 projectCustomField_emptyFieldText 290, 528, 533
 projectCustomField_hasRunningJob 290, 528, 533
 projectCustomField_id 290, 528, 533
 projectCustomField_isPublic 290, 528, 533
 projectCustomField_ordinal 290, 528, 533
 ProjectIssues 65
 ProjectIssuesBySprintId 72
 Projects 79

- Q -

query 378, 382, 401, 402, 435, 438, 441, 451, 461, 464, 477, 500, 506, 517, 528, 543, 547, 558, 571, 576, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 665, 667, 673, 675, 678, 680, 694, 703, 712, 720, 729, 733, 748, 757

- R -

Readable ID 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 readOnly 266
 Read-only 266
 Release Date 486, 488, 489, 491
 Released 486, 488, 489, 491
 ReleaseDate 486, 488, 489, 491
 Removed 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
 removed_1 172, 179, 185, 192
 Reply-to Email 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 replyToEmail 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 Report Calculator Threads 53
 reportCalculatorThreads 53
 reporter_\$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 reporter_\$type_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 reporter_\$type_2 185, 192, 200, 206, 213, 219, 226, 232
 reporter_\$type_3 185, 192, 200, 206, 213, 219, 226, 232
 reporter_avatarUrl 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 reporter_avatarUrl_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 reporter_avatarUrl_2 185, 192, 200, 206, 213, 219, 226, 232
 reporter_avatarUrl_3 185, 192, 200, 206, 213, 219, 226, 232
 reporter_banned 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 reporter_banned_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256

reporter_banned_2	185, 192, 200, 206, 213, 219, 226, 232	reporter_id	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 566, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_banned_3	185, 192, 200, 206, 213, 219, 226, 232	reporter_id_1	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_email	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 566, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741	reporter_id_2	185, 192, 200, 206, 213, 219, 226, 232
reporter_email_1	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256	reporter_id_3	185, 192, 200, 206, 213, 219, 226, 232
reporter_email_2	185, 192, 200, 206, 213, 219, 226, 232	reporter_jabberAccountName	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 566, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_email_3	185, 192, 200, 206, 213, 219, 226, 232	reporter_jabberAccountName_1	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_fullName	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 566, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741	reporter_jabberAccountName_2	185, 192, 200, 206, 213, 219, 226, 232
reporter_fullName_1	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256	reporter_jabberAccountName_3	185, 192, 200, 206, 213, 219, 226, 232
reporter_fullName_2	185, 192, 200, 206, 213, 219, 226, 232	reporter_login	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 566, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_fullName_3	185, 192, 200, 206, 213, 219, 226, 232	reporter_login_1	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_guest	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 566, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741	reporter_login_2	185, 192, 200, 206, 213, 219, 226, 232
reporter_guest_1	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256	reporter_login_3	185, 192, 200, 206, 213, 219, 226, 232
reporter_guest_2	185, 192, 200, 206, 213, 219, 226, 232	reporter_online	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 566, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_guest_3	185, 192, 200, 206, 213, 219, 226, 232		

reporter_online_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 reporter_online_2 185, 192, 200, 206, 213, 219, 226, 232
 reporter_online_3 185, 192, 200, 206, 213, 219, 226, 232
 reporter_profiles_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 reporter_profiles_\$type_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 reporter_profiles_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 reporter_profiles_id_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 reporter_ringId 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 reporter_ringId_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 reporter_ringId_2 185, 192, 200, 206, 213, 219, 226, 232
 reporter_ringId_3 185, 192, 200, 206, 213, 219, 226, 232
 requested-page-size 2
 Requests per Second 53
 requests-parallel-max 2
 requestsPerSecond 53
 Resolved 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 resolved_1 349, 355, 368, 547, 558, 565, 576, 581, 592
 Response Cache Maximum Age (sec) 604
 RestSettings 51
 restSettings_\$type 24
 restSettings_allowAllOrigins 24
 restSettings_id 24
 Result BLOB 604
 Result Text 604
 RESULT_BLOB 604
 RESULT_DATE_TIME_UTC 604
 RESULT_NUMBER 604
 RESULT_TEXT 604
 Reverse 15, 18, 20
 Ring ID 262, 264, 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 433, 434, 435, 436, 438, 441, 444, 445, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 474, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 ringId 262, 264, 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 433, 434, 435, 436, 438, 441, 444, 445, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 474, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
 Run without Actions 604

- S -

Save HTTP Disk Cache 604
 Save HTTP Memory Cache 604
 Saved Queries 654, 673
 SavedQueries 654, 673
 SavedQueryById 656, 675
 SavedQueryIssues 678
 SavedQueryIssuesByUserId 680
 service-url 2
 Short Name 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 shortName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
 simulate-http-400-errors 2
 simulate-http-400-errors-percentage 2
 simulate-http-401-errors 2
 simulate-http-401-errors-percentage 2
 simulate-http-403-errors 2
 simulate-http-403-errors-percentage 2
 simulate-http-408-errors 2
 simulate-http-408-errors-percentage 2
 simulate-http-429-errors 2
 simulate-http-429-errors-percentage 2
 simulate-http-500-errors 2
 simulate-http-500-errors-percentage 2
 simulate-http-502-errors 2
 simulate-http-502-errors-percentage 2
 simulate-http-503-errors 2
 simulate-http-503-errors-percentage 2
 simulate-http-protocol-errors 2
 simulate-http-timeout-errors 2
 simulate-http-timeout-errors-percentage 2

Size	26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 374, 375, 495, 500, 506, 512, 606, 626, 694, 699	sprintsSettings_sprintSyncField_\$type	58, 65, 72, 85, 91, 126, 133, 152, 157
size_1	172, 179, 185, 192	sprintsSettings_sprintSyncField_aliases	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
slot-based-rate-limit-length-ms	2	sprintsSettings_sprintSyncField_hasRunningJob	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
slot-based-rate-limit-slots	2	sprintsSettings_sprintSyncField_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
Source to Target	266	sprintsSettings_sprintSyncField_isAutoAttached	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sourceToTarget	266	sprintsSettings_sprintSyncField_isDisplayedInIssueList	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
SprintById	85	sprintsSettings_sprintSyncField_isUpdateable	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
SprintById1	91	sprintsSettings_sprintSyncField_localizedName	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
SprintById2	97	sprintsSettings_sprintSyncField_name	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
SprintIssueAttachmentsBySprintId	101	sprintsSettings_sprintSyncField_ordinal	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
SprintIssueCommentsBySprintId	108	standardize-identifiers	2
SprintIssueCustomFieldsBySprintId	114	standardize-identifiers-casing	2
SprintIssueLinksBySprintId	120	start	15, 18, 20, 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157, 757
SprintIssues	126	Start Date	604
SprintIssuesBySprintId	133	Start Time	53
SprintIssuesBySprintId1	140	startDate	757
SprintIssueTagsBySprintId	146	startedTime	53
Sprints	152	Starting Number	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
Sprints1	157	startingNumber	26, 30, 34, 38, 41, 45, 58, 65, 72, 79
sprintsSettings_\$type	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	stateBundleElementId	430
sprintsSettings_cardOnSeveralSprints	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	status_\$type	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_\$type	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	status_hasJobs	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_archived	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	status_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_finish	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	status_valid	58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_goal	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	subtasks_\$type	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
sprintsSettings_defaultSprint_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	subtasks_\$type_1	349, 355, 368, 547, 558, 565, 576, 581, 592
sprintsSettings_defaultSprint_isDefault	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	subtasks_commentsCount	349, 355, 368, 547, 558, 565, 576, 581, 592
sprintsSettings_defaultSprint_name	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	subtasks_created	349, 355, 368, 547, 558, 565, 576, 581, 592
sprintsSettings_defaultSprint_start	58, 65, 72, 79, 85, 91, 126, 133, 152, 157		
sprintsSettings_defaultSprint_unresolvedIssuesCount	58, 65, 72, 79, 85, 91, 126, 133, 152, 157		
sprintsSettings_disableSprints	58, 65, 72, 79, 85, 91, 126, 133, 152, 157		
sprintsSettings_explicitQuery	58, 65, 72, 79, 85, 91, 126, 133, 152, 157		
sprintsSettings_hideSubtasksOfCards	58, 65, 72, 79, 85, 91, 126, 133, 152, 157		
sprintsSettings_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157		
sprintsSettings_isExplicit	58, 65, 72, 79, 85, 91, 126, 133, 152, 157		

subtasks_description 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_direction 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_readOnly 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_sourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_targetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_numberInProject 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_resolved 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_summary 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_updated 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_idReadable 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_isDraft 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_linkType_\$type 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_aggregation 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_directed 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_id 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_localizedName 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_localizedSourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_localizedTargetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_name 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_readOnly 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_sourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_linkType_targetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
 subtasks_numberInProject 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_resolved 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_summary 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_updated 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_usesMarkdown 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_votes 349, 355, 368, 547, 558, 565, 576, 581, 592
 subtasks_wikifiedDescription 349, 355, 368, 547, 558, 565, 576, 581, 592
 Successful 604
 SUCCESSFUL 604
 Summary 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 373, 378, 383, 388, 393, 398, 403, 408, 413, 418, 423, 428, 433, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
 summary_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 349, 355, 368, 547, 558, 565, 576, 581, 592
 summary_2 185, 192, 200, 206, 213, 219, 226, 232
 summary_3 185, 192, 200, 206, 213, 219, 226, 232
 summary_4 226, 232
 summary_5 226, 232
 swagger-specification-file 2
 swagger-specification-http-disk-cache-max-age-sec 2
 swagger-specification-url 2
 swimlaneSettings_\$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 swimlaneSettings_enabled 58, 65, 72, 79, 85, 91, 126, 133, 152, 157

swimlaneSettings_id	58, 65, 72, 79, 85, 91, 126, 133, 152, 157	teamForProject_createdBy_banned	262, 264, 445, 474
SystemSettings	52	teamForProject_createdBy_email	262, 264, 445, 474
systemSettings_\$type	24	teamForProject_createdBy_fullName	262, 264, 445, 474
systemSettings_administratorEmail	24	teamForProject_createdBy_guest	262, 264, 445, 474
systemSettings_allowStatisticsCollection	24	teamForProject_createdBy_id	262, 264, 445, 474
systemSettings_baseUrl	24	teamForProject_createdBy_jabberAccountName	262, 264, 445, 474
systemSettings_id	24	teamForProject_createdBy_login	262, 264, 445, 474
systemSettings_isApplicationReadOnly	24	teamForProject_createdBy_online	262, 264, 445, 474
systemSettings_maxExportItems	24	teamForProject_createdBy_ringId	262, 264, 445, 474
systemSettings_maxUploadFileSize	24	teamForProject_description	262, 264, 433, 444, 445, 474
- T -			
TagById	587, 683	teamForProject_fromEmail	262, 264, 433, 444, 445, 474
TagIssuesByTagId	363, 592, 686	teamForProject_iconUrl	262, 264, 433, 444, 445, 474
TagIssuesByTagId2	368	teamForProject_leader_\$type	262, 264, 445, 474
Tags	599, 689	teamForProject_leader_avatarUrl	262, 264, 445, 474
Target member	15, 17, 20	teamForProject_leader_banned	262, 264, 445, 474
Target to Source	266	teamForProject_leader_email	262, 264, 445, 474
targetMember	15, 17, 20	teamForProject_leader_fullName	262, 264, 445, 474
targetToSource	266	teamForProject_leader_guest	262, 264, 445, 474
team_\$type	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	teamForProject_leader_id	262, 264, 445, 474
team_allUsersGroup	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	teamForProject_leader_jabberAccountName	262, 264, 445, 474
team_icon	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	teamForProject_leader_login	262, 264, 445, 474
team_id	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	teamForProject_leader_online	262, 264, 445, 474
team_name	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	teamForProject_leader_ringId	262, 264, 445, 474
team_ringId	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	teamForProject_replyToEmail	262, 264, 433, 444, 445, 474
team_teamForProject_archived	26, 30, 34, 38, 41, 45	teamForProject_shortName	262, 264, 433, 444, 445, 474
team_teamForProject_description	26, 30, 34, 38, 41, 45	teamForProject_startingNumber	262, 264, 433, 444, 445, 474
team_teamForProject_fromEmail	26, 30, 34, 38, 41, 45	teamForProject_team_\$type	262, 264, 445, 474
team_teamForProject_iconUrl	26, 30, 34, 38, 41, 45	teamForProject_team_allUsersGroup	262, 264, 445, 474
team_teamForProject_replyToEmail	26, 30, 34, 38, 41, 45	teamForProject_team_icon	262, 264, 445, 474
team_teamForProject_shortName	26, 30, 34, 38, 41, 45	teamForProject_team_id	262, 264, 445, 474
team_teamForProject_startingNumber	26, 30, 34, 38, 41, 45	teamForProject_team_name	262, 264, 445, 474
team_teamForProject_template	26, 30, 34, 38, 41, 45	teamForProject_team_ringId	262, 264, 445, 474
team_usersCount	26, 30, 34, 38, 41, 45, 58, 65, 72, 79	teamForProject_team_usersCount	262, 264, 445, 474
teamForProject_archived	262, 264, 433, 444, 445, 474	teamForProject_template	262, 264, 433, 444, 445, 474
teamForProject_createdBy_\$type	262, 264, 445, 474	Telemetry	53
teamForProject_createdBy_avatarUrl	262, 264, 445, 474	Template	26, 30, 34, 38, 41, 45, 58, 65, 72, 79

Text 22, 30, 108, 200, 206, 239, 245, 251, 256, 280, 285, 308, 312, 506, 512, 517, 523, 614, 630, 703, 707, 753, 757

Text Index Size 53

Text Preview 30, 108, 280, 285, 308, 312, 506, 512, 517, 523, 614, 630, 703, 707, 753, 757

textIndexSize 53

textPreview 30, 108, 280, 285, 308, 312, 506, 512, 517, 523, 614, 630, 703, 707, 753, 757

Thumbnail (URL) 26, 101, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699

thumbnailURL 26, 101, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699

Timeout (sec) 604

TIMEOUT_SEC 604

Timestamp 15, 17, 20

TimeTrackingSettings 54

TimeTrackingSettingWorkItemTypes 55

TimeTrackingSettingWorkItemTypesByWorkItemTypeId 55

TimeTrackingWorkTimeSettings 56

timezone_\$type 23, 693

timezone_id 23, 693

timezone_offset 23, 693

timezone_presentation 23, 693

Total Transactions 53

totalTransactions 53

Transaction ID 604

TRANSACTION_ID 604

Transactions per Second 53

transactionsPerSecond 53

type_\$type 753, 757

type_autoAttached 753, 757

type_id 753, 757

type_name 753, 757

Types 494

updateableBy_\$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

updateableBy_allUsersGroup 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

updateableBy_icon 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

updateableBy_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

updateableBy_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

updateableBy_ringId 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

updateableBy_teamForProject_archived 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

- U -

Unresolved Issue Count 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157

unresolvedIssuesCount 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157

untagOnResolve 45, 146, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 380, 384, 405, 406, 436, 448, 454, 466, 470, 479, 482, 547, 587, 592, 599, 646, 650, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 733, 737, 741, 751

untagOnResolve_1 336, 340, 741

updateableBy_teamForProject_description 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 Updated 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 753, 757
 updateableBy_teamForProject_fromEmail 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updated_1 26, 30, 101, 108, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 279, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 280, 285, 295, 299, 308, 312, 349, 355, 368, 495, 500, 506, 512, 517, 523, 547, 558, 565, 576, 581, 592, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updateableBy_teamForProject_iconUrl 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updated_2 172, 179, 185, 192, 200, 206, 226, 232, 239, 245, 280, 506, 512
 updateableBy_teamForProject_replyToEmail 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updated_3 185, 192
 updatedBy_\$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 updatedBy_\$type_1 185, 192, 200, 206, 213, 219, 226, 232
 updatedBy_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 updateableBy_teamForProject_shortName 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updatedBy_avatarUrl_1 185, 192, 200, 206, 213, 219, 226, 232
 updatedBy_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 updateableBy_teamForProject_startingNumber 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updatedBy_banned_1 185, 192, 200, 206, 213, 219, 226, 232
 updatedBy_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 updateableBy_teamForProject_template 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updatedBy_email_1 185, 192, 200, 206, 213, 219, 226, 232
 updatedBy_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 updateableBy_usersCount 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updatedBy_fullName_1 185, 192, 200, 206, 213, 219, 226, 232
 updatedBy_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 updateableByProjectBased 58, 65, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 updatedBy_guest_1 185, 192, 200, 206, 213, 219, 226, 232
 updatedBy_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 updatedBy_id_1 185, 192, 200, 206, 213, 219, 226, 232
 updatedBy_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
 updatedBy_jabberAccountName_1 185, 192, 200, 206, 213, 219, 226, 232
 updatedBy_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256

Uptime 53

URL	26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 604, 606, 626, 699	usesMarkdown	26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 753, 757
url_1	172, 179, 185, 192	usesMarkdown_1	30, 108, 280, 285, 308, 312, 349, 355, 368, 506, 512, 517, 523, 547, 558, 565, 576, 581, 592, 614, 630, 703, 707
Use HTTP Disk Cache	604	- V -	
Use HTTP Memory Cache	604		
Use Plain-text Emails	746	versionBundleElementId	491
use-batch-insert	2	visibility_\$type	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
Used Memory	53	visibility_\$type_1	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523
usedMemory	53	visibility_\$type_2	172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
use-http-disk-cache-read	2	visibility_\$type_3	172, 179, 185, 192, 200, 206, 213, 219, 226, 232
use-http-disk-cache-write	2	visibility_id	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
use-http-memory-cache-read	2	visibility_id_1	163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523
use-http-memory-cache-write	2	visibility_id_2	172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
usePlainTextEmails	746	visibility_id_3	172, 179, 185, 192, 200, 206, 213, 219, 226, 232
User Name	49	visibleFor_\$type	58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
UserById	691	- V -	
UserGeneralProfilesBySprintId	693		
userGroupId	474	- V -	
userId	461, 464, 466, 470, 472		
UserIssueAttachmentSavedQueriesByUserId	694	- V -	
UserIssueAttachmentTagsByUserId	699		
UserIssueCommentSavedQueriesByUserId	703	- V -	
UserIssueCommentTagsByUserId	707		
UserIssueCustomFieldSavedQueriesByUserId	712	- V -	
UserIssueCustomFieldTagsByUserId	716		
UserIssueLinkSavedQueriesByUserId	720	- V -	
UserIssueLinkSavedQueryTagsByUserId	724		
UserIssueSavedQueriesByUserId	729	- V -	
UserIssueTagSavedQueriesByUserId	733		
UserIssueTagsByUserId	737	- V -	
UserIssueTagsByUserId1	741		
username	49	- V -	
UserNotificationProfilesBySprintId	746		
Users	747	- V -	
Users Count	262, 264, 433, 444, 445, 474		
UserSavedQueriesByUserId	748	- V -	
usersCount	262, 264, 433, 444, 445, 474		
UserTagsByUserId	751	- V -	
Uses Mark Down	26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 753, 757		

visibleFor_allUsersGroup 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_teamForProject_fromEmail 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_teamForProject_iconUrl 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_teamForProject_replyToEmail 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_teamForProject_shortName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_teamForProject_startingNumber 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_teamForProject_template 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_ringId 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_usersCount 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleFor_teamForProject_archived 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 visibleForProjectBased 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
 visibleFor_teamForProject_description 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
 voters_type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

voters_hasVote	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741	WikifiedDescription	26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
voters_id	26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741	WikifiedDescription	26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
Votes	26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741	WikifiedDescription_1	349, 355, 368, 547, 558, 565, 576, 581, 592
		WorkItems	757
		WorkItemByld	753
		WorkItems	757
		workItemTypeId	55
		WorkItemTypeTimeTrackingSettings	57
		workTimeSettings_\$type	54, 57

- W -

watchers_\$type 26, 30, 34, 38, 41, 45, 101, 108,
 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299,
 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345,
 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528,
 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587,
 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638,
 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724,
 729, 733, 737, 741
 watchers_hasStar 26, 30, 34, 38, 41, 45, 101, 108, 114, 120,
 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308,
 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355,
 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537,
 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599,
 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646,
 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733,
 737, 741
 watchers_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140,
 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312,
 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363,
 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543,
 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606,
 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650,
 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737,
 741



invantive the **SQL** company

Invantive B.V.
Biesteweg 11
3849 RD Hierden
the Netherlands

Tel: +31 88 00 26 500
Fax: +31 84 22 58 178
info@invantive.com
invantive.com

IBAN NL25 BUNQ 2098 2586 07
Chamber of Industry and Commerce
13031406
VAT NL812602377B01
RSIN 8122602377
Managing Director: Guido Leenders
Registered office: Roermond